

PBA10F-24 Information

Heisener.com

Part Number PBA10F-24
Manufacturer Cosel USA, Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 24V 10W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PBA10F-24 Specifications

Manufacturer Part Number PBA10F-24 Manufacturer Cosel USA, Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series PBA Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 500mA Power (Watts) 10W Applications ITE (Commercial) Voltage - Isolation - Efficiency 77% Operating Temperature - Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension -	•	
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series PBA Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 500mA Power (Watts) 10W Applications ITE (Commercial) Voltage - Isolation - Efficiency 77% Operating Temperature - Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension -	Manufacturer Part Number	PBA10F-24
Package - Series PBA Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 500mA Power (Watts) 10W Applications ITE (Commercial) Voltage - Isolation - Efficiency 77% Operating Temperature - Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension -	Manufacturer	Cosel USA, Inc.
Package-SeriesPBATypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)500mAPower (Watts)10WApplicationsITE (Commercial)Voltage - Isolation-Efficiency77%Operating Temperature-FeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension-	Category	Power Supplies - External/Internal (Off-Board)
SeriesPBATypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)500mAPower (Watts)10WApplicationsITE (Commercial)Voltage - Isolation-Efficiency77%Operating Temperature-FeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension-		AC DC Converters
TypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)500mAPower (Watts)10WApplicationsITE (Commercial)Voltage - Isolation-Efficiency77%Operating Temperature-FeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension-	Package	-
Number of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)500mAPower (Watts)10WApplicationsITE (Commercial)Voltage - Isolation-Efficiency77%Operating Temperature-FeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension-	Series	PBA
Voltage - Input85 ~ 264 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)500mAPower (Watts)10WApplicationsITE (Commercial)Voltage - Isolation-Efficiency77%Operating Temperature-FeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension-	Type	Open Frame
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency Operating Temperature Features DC Input Capable, Universal Input Mounting Type Size / Dimension 24V 24V 24V 24V 24V 24V - Chassis Mount 50Input Capable, Universal Input Chassis Mount Size / Dimension	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency Operating Temperature Features DC Input Capable, Universal Input Mounting Type Size / Dimension - Capable Chassis Mount Size / Dimension - Capable Chassis Mount Chassis Mount Capable Chassis Mount Capable Capable Capable Chassis Mount Capable Ca	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Fower (Watts) Applications Voltage - Isolation Voltage - Isolation - Efficiency Operating Temperature Features DC Input Capable, Universal Input Mounting Type Size / Dimension - Chassis Mount Size / Dimension	Voltage - Output 1	24V
Voltage - Output 4 Current - Output (Max) Fower (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency 77% Operating Temperature Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension - Current - Output (Max) 500mA 10W 10W 10W 10W 10W 10W 10W 10	Voltage - Output 2	-
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Efficiency 77% Operating Temperature Features DC Input Capable, Universal Input Mounting Type Size / Dimension 500mA 10W 10W 10W 10W 10W 10E 10E 10E	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency 77% Operating Temperature - Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension -	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation - Efficiency 77% Operating Temperature - Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension -	Current - Output (Max)	500mA
Voltage - Isolation - Features - DC Input Capable, Universal Input Mounting Type Chassis Mount - Size / Dimension	Power (Watts)	10W
Efficiency 77% Operating Temperature - Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension -	Applications	ITE (Commercial)
Operating Temperature - Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension -	Voltage - Isolation	-
Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension -	Efficiency	77%
Mounting Type Chassis Mount Size / Dimension -	Operating Temperature	-
Size / Dimension -	Features	DC Input Capable, Universal Input
	Mounting Type	Chassis Mount
	Size / Dimension	-
Report errors?		Report errors?

PBA10F-24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PBA10F-24 Payment Methods



















PBA10F-24 Shipping Methods













If you have any question about PBA10F-24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com