

PBA15F-48 Information



For Reference Only

Part Number PBA15F-48
Manufacturer Cosel USA, Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 48V 15W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PBA15F-48 Specifications

| Manufacturer Part Number PBA15F-48 Manufacturer Cosel USA, Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series PBA Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 350mA Power (Watts) 15W Applications ITE (Commercial) Voltage - Isolation - Efficiency 78% Operating Temperature - Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension - Report errors? | • | |
|--|--------------------------|--|
| Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series PBA Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 350mA Power (Watts) 15W Applications ITE (Commercial) Voltage - Isolation - Efficiency 78% Operating Temperature - Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension - | Manufacturer Part Number | PBA15F-48 |
| Package - Series PBA Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 350mA Power (Watts) 15W Applications ITE (Commercial) Voltage - Isolation - Efficiency 78% Operating Temperature - Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension - | Manufacturer | Cosel USA, Inc. |
| Package - Series PBA Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 350mA Power (Watts) 15W Applications ITE (Commercial) Voltage - Isolation - Efficiency 78% Operating Temperature - Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension - | Category | Power Supplies - External/Internal (Off-Board) |
| Series PBA Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 350mA Power (Watts) 15W Applications ITE (Commercial) Voltage - Isolation - Efficiency 78% Operating Temperature - Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension - | | AC DC Converters |
| Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 350mA Power (Watts) 15W Applications ITE (Commercial) Voltage - Isolation - Efficiency 78% Operating Temperature - Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension - | Package | - |
| Number of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 148VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)350mAPower (Watts)15WApplicationsITE (Commercial)Voltage - Isolation-Efficiency78%Operating Temperature-FeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension- | Series | PBA |
| Voltage - Input85 ~ 264 VACVoltage - Output 148VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)350mAPower (Watts)15WApplicationsITE (Commercial)Voltage - Isolation-Efficiency78%Operating Temperature-FeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension- | Type | Open Frame |
| Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Fefficiency 78% Operating Temperature Features DC Input Capable, Universal Input Mounting Type Size / Dimension 48V 48V 48V 48V 48V 48V 48V 48 | Number of Outputs | 1 |
| Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Voltage - Isolation - Efficiency Operating Temperature Features DC Input Capable, Universal Input Mounting Type Size / Dimension - Size / Dimension | Voltage - Input | 85 ~ 264 VAC |
| Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency Operating Temperature Features DC Input Capable, Universal Input Mounting Type Size / Dimension - Chassis Mount Size / Dimension | Voltage - Output 1 | 48V |
| Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency 78% Operating Temperature Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension - - - Current - Output (Max) - 550mA - 15W 15W 15W 15W 15W 15W 15W | Voltage - Output 2 | - |
| Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency 78% Operating Temperature Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 350mA 15W 15W 17E (Commercial) - Commercial) - Commercial - Com | Voltage - Output 3 | - |
| Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency 78% Operating Temperature - Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension - | Voltage - Output 4 | - |
| Applications ITE (Commercial) Voltage - Isolation - Efficiency 78% Operating Temperature - Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension - | Current - Output (Max) | 350mA |
| Voltage - Isolation - Efficiency 78% Operating Temperature - Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension - | Power (Watts) | 15W |
| Efficiency 78% Operating Temperature - Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension - | Applications | ITE (Commercial) |
| Operating Temperature - Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension - | Voltage - Isolation | - |
| Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension - | Efficiency | 78% |
| Mounting Type Chassis Mount Size / Dimension - | Operating Temperature | - |
| Size / Dimension - | Features | DC Input Capable, Universal Input |
| | Mounting Type | Chassis Mount |
| Report errors? | Size / Dimension | - |
| | | Report errors? |

PBA15F-48 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PBA15F-48 Payment Methods



















PBA15F-48 Shipping Methods













If you have any question about PBA15F-48, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com