

PBC-032A2F7 Information

Heisener.com

Part Number PBC-032A2F7

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Power Relays, Over 2 Amps

Description RELAY CONTACTOR 3PST 32A 110V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PBC-032A2F7 Specifications

Manufacturer Part Number PBC-032A2F7 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series PBC Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 110VAC Contact Form 3PST-NO-DM (3 Form X) Contact Rating (Current) 32A Switching Voltage 380VAC - Max Turn On Voltage (Max) 93.5 VAC Turn Off Voltage (Min) 22 VAC Operate Time - Release Time - Features Finger-Safe (IP20) Terminals Mounting Type DIN Rail Termination Style Screw Terminal		
Category Relays Power Relays, Over 2 Amps Package - Series PBC Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 110VAC Contact Form 3PST-NO-DM (3 Form X) Contact Rating (Current) 32A Switching Voltage 380VAC - Max Turn On Voltage (Max) 93.5 VAC Turn Off Voltage (Min) 22 VAC Operate Time - Release Time - Features Finger-Safe (IP20) Terminals Mounting Type DIN Rail Termination Style Screw Terminal	Manufacturer Part Number	PBC-032A2F7
Package - Series PBC Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 110VAC Contact Form 3PST-NO-DM (3 Form X) Contact Rating (Current) 32A Switching Voltage 380VAC - Max Turn On Voltage (Max) 93.5 VAC Turn Off Voltage (Min) 22 VAC Operate Time - Release Time - Features Finger-Safe (IP20) Terminals Mounting Type DIN Rail Termination Style Screw Terminal	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series PBC Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 110VAC Contact Form 3PST-NO-DM (3 Form X) Contact Rating (Current) 32A Switching Voltage 380VAC - Max Turn On Voltage (Max) 93.5 VAC Turn Off Voltage (Min) 22 VAC Operate Time - Release Time - Features Finger-Safe (IP20) Terminals Mounting Type DIN Rail Termination Style Screw Terminal	Category	Relays
SeriesPBCRelay TypeContactorCoil TypeNon LatchingCoil Current-Coil Voltage110VACContact Form3PST-NO-DM (3 Form X)Contact Rating (Current)32ASwitching Voltage380VAC - MaxTurn On Voltage (Max)93.5 VACTurn Off Voltage (Min)22 VACOperate Time-Release Time-FeaturesFinger-Safe (IP20) TerminalsMounting TypeDIN RailTermination StyleScrew Terminal		Power Relays, Over 2 Amps
Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 110VAC Contact Form 3PST-NO-DM (3 Form X) Contact Rating (Current) 32A Switching Voltage 380VAC - Max Turn On Voltage (Max) 93.5 VAC Turn Off Voltage (Min) 22 VAC Operate Time - Release Time - Features Finger-Safe (IP20) Terminals Mounting Type DIN Rail Termination Style Screw Terminal	Package	-
Coil TypeNon LatchingCoil Current-Coil Voltage110VACContact Form3PST-NO-DM (3 Form X)Contact Rating (Current)32ASwitching Voltage380VAC - MaxTurn On Voltage (Max)93.5 VACTurn Off Voltage (Min)22 VACOperate Time-Release Time-FeaturesFinger-Safe (IP20) TerminalsMounting TypeDIN RailTermination StyleScrew Terminal	Series	PBC
Coil Current Coil Voltage 110VAC Contact Form 3PST-NO-DM (3 Form X) Contact Rating (Current) 32A Switching Voltage 380VAC - Max Turn On Voltage (Max) 93.5 VAC Turn Off Voltage (Min) 22 VAC Operate Time Release Time - Features Finger-Safe (IP20) Terminals Mounting Type DIN Rail Termination Style Screw Terminal	Relay Type	Contactor
Coil Voltage 110VAC Contact Form 3PST-NO-DM (3 Form X) Contact Rating (Current) 32A Switching Voltage 380VAC - Max Turn On Voltage (Max) 93.5 VAC Turn Off Voltage (Min) 22 VAC Operate Time - Release Time - Features Finger-Safe (IP20) Terminals Mounting Type DIN Rail Termination Style Screw Terminal	Coil Type	Non Latching
Contact Form 3PST-NO-DM (3 Form X) Contact Rating (Current) 32A Switching Voltage 380VAC - Max Turn On Voltage (Max) 93.5 VAC Turn Off Voltage (Min) 22 VAC Operate Time - Release Time - Features Finger-Safe (IP20) Terminals Mounting Type DIN Rail Termination Style Screw Terminal	Coil Current	-
Contact Rating (Current) Switching Voltage 380VAC - Max Turn On Voltage (Max) 93.5 VAC Turn Off Voltage (Min) 22 VAC Operate Time - Release Time - Features Finger-Safe (IP20) Terminals Mounting Type DIN Rail Termination Style Screw Terminal	Coil Voltage	110VAC
Switching Voltage 380VAC - Max Turn On Voltage (Max) 93.5 VAC Turn Off Voltage (Min) 22 VAC Operate Time - Release Time - Features Finger-Safe (IP20) Terminals Mounting Type DIN Rail Termination Style Screw Terminal	Contact Form	3PST-NO-DM (3 Form X)
Turn On Voltage (Max) 93.5 VAC Turn Off Voltage (Min) 22 VAC Operate Time - Release Time - Features Finger-Safe (IP20) Terminals Mounting Type DIN Rail Termination Style Screw Terminal	Contact Rating (Current)	32A
Turn Off Voltage (Min) 22 VAC Operate Time Release Time Features Finger-Safe (IP20) Terminals Mounting Type DIN Rail Termination Style Screw Terminal	Switching Voltage	380VAC - Max
Operate Time - Release Time - Features Finger-Safe (IP20) Terminals Mounting Type DIN Rail Termination Style Screw Terminal	Turn On Voltage (Max)	93.5 VAC
Release Time - Features Finger-Safe (IP20) Terminals Mounting Type DIN Rail Termination Style Screw Terminal	Turn Off Voltage (Min)	22 VAC
Features Finger-Safe (IP20) Terminals Mounting Type DIN Rail Termination Style Screw Terminal	Operate Time	-
Mounting Type DIN Rail Termination Style Screw Terminal	Release Time	-
Termination Style Screw Terminal	Features	Finger-Safe (IP20) Terminals
	Mounting Type	DIN Rail
Report errors?	Termination Style	Screw Terminal
		Report errors?

PBC-032A2F7 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PBC-032A2F7 Payment Methods



















PBC-032A2F7 Shipping Methods













If you have any question about PBC-032A2F7, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com