



PBN.2F.310.XLM Information

Heisener.com

Part Number PBN.2F.310.XLM

Manufacturer LEMO

Category Connectors, Interconnects

Circular Connectors

Description RCPT PNL MNT 10SKT CRIMP

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PBN.2F.310.XLM Specifications

Manufacturer Part Number PBN.2F.310.XLM Manufacturer LEMO Category Connectors, Interconnects Circular Connectors Circular Connectors Package - Series 2F Connector Type Receptacle, Female Sockets Number of Positions 10 Shell Size - Insert 310 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Push-Pull, Detent Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated - Current Rating 8A		
CategoryConnectors, InterconnectsPackage-Series2FConnector TypeReceptacle, Female SocketsNumber of Positions10Shell Size - Insert310Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypePush-Pull, Detent LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating8A	Manufacturer Part Number	PBN.2F.310.XLM
Circular Connectors Package - Series 2F Connector Type Receptacle, Female Sockets Number of Positions 10 Shell Size - Insert 310 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Push-Pull, Detent Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated Current Rating 8A	Manufacturer	LEMO
Package-Series2FConnector TypeReceptacle, Female SocketsNumber of Positions10Shell Size - Insert310Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypePush-Pull, Detent LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating8A	Category	Connectors, Interconnects
Series2FConnector TypeReceptacle, Female SocketsNumber of Positions10Shell Size - Insert310Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypePush-Pull, Detent LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating8A		Circular Connectors
Connector Type Receptacle, Female Sockets Number of Positions 10 Shell Size - Insert 310 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Push-Pull, Detent Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated - Current Rating 8A	Package	-
Number of Positions10Shell Size - Insert310Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypePush-Pull, Detent LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating8A	Series	2F
Shell Size - Insert310Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypePush-Pull, Detent LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating8A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Push-Pull, Detent Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated - Current Rating 8A	Number of Positions	10
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypePush-Pull, Detent LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating8A	Shell Size - Insert	310
Termination Crimp Fastening Type Push-Pull, Detent Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated Current Rating 8A	Shell Size, MIL	-
Fastening Type Push-Pull, Detent Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated - Current Rating 8A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated - Current Rating 8A	Termination	Crimp
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated - Current Rating 8A	Fastening Type	Push-Pull, Detent Lock
Shell Material, Finish Contact Finish Gold Features Backshell, Shielded Voltage - Rated Current Rating 8A	Orientation	N (Normal)
Contact Finish Gold Features Backshell, Shielded Voltage - Rated - Current Rating 8A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Backshell, Shielded Voltage - Rated - Current Rating 8A	Shell Material, Finish	Aluminum Alloy, Nickel Plated
Voltage - Rated - Current Rating 8A	Contact Finish	Gold
Current Rating 8A	Features	Backshell, Shielded
	Voltage - Rated	-
Report errors?	Current Rating	8A
		Report errors?

PBN.2F.310.XLM Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PBN.2F.310.XLM Payment Methods



















PBN.2F.310.XLM Shipping Methods













If you have any question about PBN.2F.310.XLM, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com