

PBO-3-S3.3 Information

Part Number PBO-3-S3.3 **Manufacturer** CUI Inc.

Category Power Supplies - Board Mount

AC DC Converters

Description AC DC CONVERTER 3.3V 3W

Package 12-SIP Module, 6 Leads

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PBO-3-S3.3 Specifications

Series PBO-3 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 600mA Power (Watts) 2W Applications ITE (Commercial) Features DC Input Capable, Universal Input Operating Temperature -40°C ~ 85°C (With Derating) Efficiency 63% Mounting Type Through Hole	-	
Category Power Supplies - Board Mount AC DC Converters Package 12-SIP Module, 6 Leads Series PBO-3 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 600mA Power (Watts) 2W Applications ITE (Commercial) Features DC Input Capable, Universal Input Operating Temperature -40°C ~ 85°C (With Derating) Efficiency 63% Mounting Type Through Hole	Manufacturer Part Number	PBO-3-S3.3
AC DC Converters Package 12-SIP Module, 6 Leads Series PBO-3 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 600mA Power (Watts) 2W Applications ITE (Commercial) Features DC Input Capable, Universal Input Operating Temperature -40°C ~ 85°C (With Derating) Efficiency 63% Mounting Type Through Hole	Manufacturer	CUI Inc.
Package 12-SIP Module, 6 Leads Series PBO-3 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 600mA Power (Watts) 2W Applications ITE (Commercial) Features DC Input Capable, Universal Input Operating Temperature -40°C ~ 85°C (With Derating) Efficiency 63% Mounting Type Through Hole	Category	Power Supplies - Board Mount
Series PBO-3 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 600mA Power (Watts) 2W Applications ITE (Commercial) Features DC Input Capable, Universal Input Operating Temperature -40°C ~ 85°C (With Derating) Efficiency 63% Mounting Type Through Hole		AC DC Converters
TypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 13.3VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)600mAPower (Watts)2WApplicationsITE (Commercial)FeaturesDC Input Capable, Universal InputOperating Temperature-40°C ~ 85°C (With Derating)Efficiency63%Mounting TypeThrough Hole	Package	12-SIP Module, 6 Leads
Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 600mA Power (Watts) 2W Applications ITE (Commercial) Features DC Input Capable, Universal Input Operating Temperature -40°C ~ 85°C (With Derating) Efficiency 63% Mounting Type Through Hole	Series	PBO-3
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Features DC Input Capable, Universal Input Operating Temperature -40°C ~ 85°C (With Derating) Efficiency Mounting Type Through Hole	Type	Open Frame
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 600mA Power (Watts) 2W Applications ITE (Commercial) Features DC Input Capable, Universal Input Operating Temperature -40°C ~ 85°C (With Derating) Efficiency 63% Mounting Type Through Hole	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Features DC Input Capable, Universal Input Operating Temperature -40°C ~ 85°C (With Derating) Efficiency Mounting Type Through Hole	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Features DC Input Capable, Universal Input Operating Temperature -40°C ~ 85°C (With Derating) Efficiency 63% Mounting Type Through Hole	Voltage - Output 1	3.3V
Voltage - Output 4 Current - Output (Max) 600mA Power (Watts) Applications ITE (Commercial) Features DC Input Capable, Universal Input Operating Temperature -40°C ~ 85°C (With Derating) Efficiency 63% Mounting Type Through Hole	Voltage - Output 2	-
Current - Output (Max) 600mA Power (Watts) 2W Applications ITE (Commercial) Features DC Input Capable, Universal Input Operating Temperature -40°C ~ 85°C (With Derating) Efficiency 63% Mounting Type Through Hole	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Features DC Input Capable, Universal Input Operating Temperature -40°C ~ 85°C (With Derating) Efficiency 63% Mounting Type Through Hole	Voltage - Output 4	-
Applications ITE (Commercial) Features DC Input Capable, Universal Input Operating Temperature -40°C ~ 85°C (With Derating) Efficiency 63% Mounting Type Through Hole	Current - Output (Max)	600mA
Features DC Input Capable, Universal Input Operating Temperature -40°C ~ 85°C (With Derating) Efficiency 63% Mounting Type Through Hole	Power (Watts)	2W
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ (With Derating) Efficiency 63% Mounting Type Through Hole	Applications	ITE (Commercial)
Efficiency 63% Mounting Type Through Hole	Features	DC Input Capable, Universal Input
Mounting Type Through Hole	Operating Temperature	-40° C ~ 85° C (With Derating)
	Efficiency	63%
	Mounting Type	Through Hole
Package / Case 12-SIP Module, 6 Leads	Package / Case	12-SIP Module, 6 Leads
Size / Dimension 1.38" L x 0.43" W x 0.71" H (35.0mm x 11.0mm x 18.0mm)	Size / Dimension	1.38" L x 0.43" W x 0.71" H (35.0mm x 11.0mm x 18.0mm)
Report errors?		Report errors?

PBO-3-S3.3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PBO-3-S3.3 Payment Methods



















PBO-3-S3.3 Shipping Methods













If you have any question about PBO-3-S3.3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com