

PC-120-200B40

PC-120-200B40 Information

Heisener.com	 PC-120-200B40 Pulse Electronics Power Transformers Power Transformers XFRMR LAMINATED 24VA THRU HOLE - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



PC-120-200B40 Specifications

Manufacturer Part NumberPC-120-200B40ManufacturerPuse Electronics PowerCategoryTransformersPackage-SeriesPC Pug-InTypeLaminated CoreVoltage - PrimaryISVVoltage - Secondary (Full Load)Parallel 60V, Series 120VCurrent - Output (Max)Parallel 400mA, Series 200mAPrimary Winding(s)SingleSecondary Winding(s)NoPower - Max44 VAMounting TypeThrough HoleSize / Dimension41.28mm L x 57.15mm WHeight - Seated (Max)500 VrmsWoltage - Isolation1500 VrmsWinding SiSize / DimensionSize / DimensionSize / DimensionMunting TypeSize / DimensionMunting TypeSize / DimensionMuse L s 57.15mm WSize / DimensionMuse L s 57.15mm WSize / DimensionMuse L s 50.15mm WSize / DimensionMuse L s Size / DimensionSize /		
CategoryTransformersPackage-SeriesPC Plug-InTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 60V, Series 120VCurrent - Output (Max)SinglePrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max44 VAMounting TypeFrinagh HoleSize / DimensionHorugh HoleSize / Dimension4.28mm Lx 57.15mm WHeight - Seated (Max)500VrmsWeight150Vrms	Manufacturer Part Number	PC-120-200B40
Power TransformersPackage-SeriesPC Plug-InTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 60V, Series 120VCurrent - Output (Max)Parallel 400mA, Series 200mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max24 VAMounting TypeThrough HoleSize / Dimension41.28mm Lx 57.15mm WHeight - Seated (Max)500VrmsVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)	Manufacturer	Pulse Electronics Power
Package.SeriesPC Plug-InTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Paralel 60V, Series 120VCurrent - Output (Max)Paralel 400mA, Series 200mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - MaxJarong HoleMounting TypeThrough HoleSize/ DimensionPC PinSize/ Dimension4.28mm L x 57.15mm WHeight - Seated (Max)3.493mmWeightStol WrmsWeightStol Wrms	Category	Transformers
SeriesPC Plug-InTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 60V, Series 120VCurrent - Output (Max)Parallel 400mA, Series 200mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max24 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 57.15mm WHeight - Seated (Max)34.93mmVoltage - Isolation500VrmsWeight0.75 lb (340.19g)		Power Transformers
TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 60V, Series 120VCurrent - Output (Max)Parallel 400mA, Series 200mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max24 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 57.15mm WHeight - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)	Package	-
AVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 60V, Series 120VCurrent - Output (Max)Parallel 400mA, Series 200mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max24 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 57.15mm WHeight - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)	Series	PC Plug-In
Voltage - Secondary (Full Load)Parallel 60V, Series 120VCurrent - Output (Max)Parallel 400mA, Series 200mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max24 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 57.15mm WHeight - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)	Туре	Laminated Core
Current - Output (Max)Parallel 400mA, Series 200mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max24 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 57.15mm WHeight - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)	Voltage - Primary	115V
Primary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max24 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 57.15mm WHeight - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)	Voltage - Secondary (Full Load)	Parallel 60V, Series 120V
Secondary Winding(s)DualCenter TapNoPower - Max24 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 57.15mm WHeight - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)	Current - Output (Max)	Parallel 400mA, Series 200mA
Center TapNoPower - Max24 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 57.15mm WHeight - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)	Primary Winding(s)	Single
Power - Max24 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 57.15mm WHeight - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 1b (340.19g)	Secondary Winding(s)	Dual
Mounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 57.15mm WHeight - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)	Center Tap	No
Termination StylePC PinSize / Dimension41.28mm L x 57.15mm WHeight - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)	Power - Max	24 VA
Size / Dimension41.28mm L x 57.15mm WHeight - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)	Mounting Type	Through Hole
Height - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)	Termination Style	PC Pin
Voltage - Isolation1500VrmsWeight0.75 lb (340.19g)	Size / Dimension	41.28mm L x 57.15mm W
Weight 0.75 lb (340.19g)	Height - Seated (Max)	34.93mm
	Voltage - Isolation	1500Vrms
Report errors?	Weight	0.75 lb (340.19g)
		Report errors?

PC-120-200B40 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

PC-120-200B40 Payment Methods



PC-120-200B40 Shipping Methods



If you have any question about PC-120-200B40, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com