

## PC-20-1200B16 Information

Heisener.com

Part Number PC-20-1200B16

Manufacturer Pulse Electronics Power

Category Transformers

**Power Transformers** 

**Description** XFRMR LAMINATED 24VA THRU HOLE

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# PC-20-1200B16 Specifications

Manufacturer         PC-20-1200B16           Manufacturer         Pulse Electronics Power           Category         Transformers           Package         -           Series         PC Plug-In           Type         Laminated Core           Voltage - Primary         115V           Voltage - Secondary (Full Load)         Parallel 10V, Series 20V           Current - Output (Max)         Parallel 2.4A, Series 1.2A           Primary Winding(s)         Single           Secondary Winding(s)         Dual           Center Tap         No           Power - Max         24 VA           Mounting Type         Through Hole           Termination Style         PC Pin           Size / Dimension         41.28mm L x 57.15mm W           Height - Seated (Max)         34.93mm           Voltage - Isolation         1500Vrms           Weight         0.75 lb (340.19g)		
Category         Transformers           Package         -           Series         PC Plug-In           Type         Laminated Core           Voltage - Primary         115V           Voltage - Secondary (Full Load)         Parallel 10V, Series 20V           Current - Output (Max)         Parallel 2.4A, Series 1.2A           Primary Winding(s)         Single           Secondary Winding(s)         Dual           Center Tap         No           Power - Max         24 VA           Mounting Type         Through Hole           Termination Style         PC Pin           Size / Dimension         41.28mm L x 57.15mm W           Height - Seated (Max)         34.93mm           Voltage - Isolation         1500Vrms           Weight         0.75 lb (340.19g)	Manufacturer Part Number	PC-20-1200B16
Package Power Transformers  Package PC Plug-In  Type Laminated Core Voltage - Primary Voltage - Secondary (Full Load) Parallel 10V, Series 20V  Current - Output (Max) Parallel 2.4A, Series 1.2A  Primary Winding(s) Single Secondary Winding(s) Dual  Center Tap No Power - Max Abounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Voltage - Isolation Power Transformers PC Plug-In  Laminated Core Parallel 10V, Series 20V  Davide 10V, Series 20V  Parallel 2.4A, Series 1.2A  Primary Winding(s) Pual Parallel 2.4A, Series 1.2A  Primary Winding(s) Pual Parallel 2.4A, Series 1.2A  Primary Winding(s) Pual Parallel 10V, Series 20V  Parallel 10V, Ser	Manufacturer	Pulse Electronics Power
Package         -           Series         PC Plug-In           Type         Laminated Core           Voltage - Primary         115V           Voltage - Secondary (Full Load)         Parallel 10V, Series 20V           Current - Output (Max)         Parallel 2.4A, Series 1.2A           Primary Winding(s)         Single           Secondary Winding(s)         Dual           Center Tap         No           Power - Max         24 VA           Mounting Type         Through Hole           Termination Style         PC Pin           Size / Dimension         41.28mm L x 57.15mm W           Height - Seated (Max)         34.93mm           Voltage - Isolation         1500Vrms           Weight         0.75 1b (340.19g)	Category	Transformers
SeriesPC Plug-InTypeLaminated CoreVoltage - Primary115 VVoltage - Secondary (Full Load)Parallel 10V, Series 20VCurrent - Output (Max)Parallel 2.4A, Series 1.2APrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max24 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 57.15mm WHeight - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)		Power Transformers
Type Laminated Core  Voltage - Primary 115V  Voltage - Secondary (Full Load) Parallel 10V, Series 20V  Current - Output (Max) Parallel 2.4A, Series 1.2A  Primary Winding(s) Single  Secondary Winding(s) Dual  Center Tap No Power - Max 24 VA  Mounting Type Through Hole  Termination Style PC Pin  Size / Dimension 41.28mm L x 57.15mm W  Height - Seated (Max) 34.93mm  Voltage - Isolation 1500Vrms  Weight 0.75 lb (340.19g)	Package	-
Voltage - Primary  Voltage - Secondary (Full Load)  Parallel 10V, Series 20V  Current - Output (Max)  Parallel 2.4A, Series 1.2A  Primary Winding(s)  Secondary Winding(s)  Secondary Winding(s)  Center Tap  No  Power - Max  August 1.24 VA  Mounting Type  Through Hole  Termination Style  Termination Style  PC Pin  Size / Dimension  41.28mm L x 57.15mm W  Height - Seated (Max)  Voltage - Isolation  Voltage - Isolation  Weight  1500Vrms  Weight	Series	PC Plug-In
Voltage - Secondary (Full Load)  Current - Output (Max)  Parallel 2.4A, Series 1.2A  Primary Winding(s)  Single  Secondary Winding(s)  Dual  Center Tap  No  Power - Max  Mounting Type  Through Hole  Termination Style  Size / Dimension  41.28mm L x 57.15mm W  Height - Seated (Max)  Voltage - Isolation  Weight  Parallel 10V, Series 20V  Parallel 10V, Series 1.2A  Primary Winding(s)  Single  Dual  10  Single  Secondary Winding(s)  10  10  10  10  10  10  10  10  10  1	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 24 VA Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Voltage - Isolation Parallel 2.4A, Series 1.2A Pranallel 2.4A, Series 1.2A Parallel 2.4A, Series 1.2A Parallel 2.4A, Series 1.2A Parallel 2.4A, Series 1.2A Parallel 2.4A, Series 1.2A Primary Winding(s)  Dual Po Po Po No Po Po Pi  41.28mm L x 57.15mm W Poltage - Isolation 1500Vrms Voltage - Isolation 0.75 lb (340.19g)	Voltage - Primary	115V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 24 VA Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Sight Single Single Single Single Single Single No Poul 140 No 140 No 140 140 140 140 140 140 140 140 140 140	Voltage - Secondary (Full Load)	Parallel 10V, Series 20V
Secondary Winding(s)DualCenter TapNoPower - Max24 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 57.15mm WHeight - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)	Current - Output (Max)	Parallel 2.4A, Series 1.2A
Center Tap No Power - Max 24 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 57.15mm W Height - Seated (Max) 34.93mm Voltage - Isolation 1500Vrms Weight 0.75 lb (340.19g)	Primary Winding(s)	Single
Power - Max  Mounting Type  Through Hole  Termination Style  PC Pin  Size / Dimension  41.28mm L x 57.15mm W  Height - Seated (Max)  Voltage - Isolation  1500Vrms  Weight  0.75 lb (340.19g)	Secondary Winding(s)	Dual
Mounting Type Through Hole  PC Pin  Size / Dimension 41.28mm L x 57.15mm W  Height - Seated (Max) 34.93mm  Voltage - Isolation 1500Vrms  Weight 0.75 lb (340.19g)	Center Tap	No
Termination Style PC Pin Size / Dimension 41.28mm L x 57.15mm W Height - Seated (Max) 34.93mm Voltage - Isolation 1500Vrms Weight 0.75 lb (340.19g)	Power - Max	24 VA
Size / Dimension 41.28mm L x 57.15mm W  Height - Seated (Max) 34.93mm  Voltage - Isolation 1500Vrms  Weight 0.75 lb (340.19g)	Mounting Type	Through Hole
Height - Seated (Max)  Voltage - Isolation  Seated (Max)  1500Vrms  0.75 lb (340.19g)	Termination Style	PC Pin
Voltage - Isolation 1500Vrms Weight 0.75 lb (340.19g)	Size / Dimension	41.28mm L x 57.15mm W
Weight 0.75 lb (340.19g)	Height - Seated (Max)	34.93mm
	Voltage - Isolation	1500Vrms
Report errors?	Weight	0.75 lb (340.19g)
•		Report errors?

### PC-20-1200B16 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## PC-20-1200B16 Payment Methods





















## PC-20-1200B16 Shipping Methods













If you have any question about PC-20-1200B16, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com