

PC-20-500 Information



For Reference Only

Part Number PC-20-500

Manufacturer Signal Transformer

Category Transformers
Power Transformers

Description XFRMR LAMINATED 10VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PC-20-500 Specifications

| Manufacturer Part Number Manufacturer Category Transformers Power Transformers Package - Series PC Type Laminated Core Voltage - Primary Voltage - Secondary (Full Load) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap No Power - Max Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight PC-20-500 Signal Transformer Transformers Power Tansformers Power Tansformers Power Jenasted (Max) Voltage - Isolation Signal Transformer Power Transformer Power Transformer Power Transformer Signal Transformer Power Transformer Power Transformer Power Transformer Power Jenasted (Max) Voltage - Isolation Voltage - Isolation Signal Transformer Power Trans | | |
|--|---------------------------------|---------------------------|
| Category Transformers Power Transformers Package - Series PC Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 10V, Series 20V Current - Output (Max) Parallel 1A, Series 500mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 36.50mm W Height - Seated (Max) 41.27mm Voltage - Isolation 1500Vrms Weight 0.563 lb (255.37g) | Manufacturer Part Number | PC-20-500 |
| Package Power Transformers Package PC Type Laminated Core Voltage - Primary I115V Voltage - Secondary (Full Load) Parallel 10V, Series 20V Current - Output (Max) Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max I0 VA Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Power - Isolation Power Transformers PC Laminated Core Parallel 10V, Series 20V Parallel 11A, Series 500mA Parallel 11A, Series 20V Parallel 10V, Series 20V Parallel 10V | Manufacturer | Signal Transformer |
| Package-SeriesPCTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 10V, Series 20VCurrent - Output (Max)Parallel 1A, Series 500mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max10 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.60mm L x 36.50mm WHeight - Seated (Max)41.27mmVoltage - Isolation1500VrmsWeight0.563 lb (255.37g) | Category | Transformers |
| SeriesPCTypeLaminated CoreVoltage - Primary115 VVoltage - Secondary (Full Load)Parallel 10V, Series 20VCurrent - Output (Max)Parallel 1A, Series 500mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max10 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.60mm L x 36.50mm WHeight - Seated (Max)41.27mmVoltage - Isolation1500VrmsWeight0.563 lb (255.37g) | | Power Transformers |
| Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 10V, Series 20V Current - Output (Max) Parallel 1A, Series 500mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 36.50mm W Height - Seated (Max) 41.27mm Voltage - Isolation 1500Vrms Weight 0.563 lb (255.37g) | Package | - |
| Voltage - Primary Voltage - Secondary (Full Load) Parallel 10V, Series 20V Current - Output (Max) Parallel 1A, Series 500mA Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 36.50mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Weight | Series | PC |
| Voltage - Secondary (Full Load) Current - Output (Max) Parallel 1A, Series 500mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style Size / Dimension 47.60mm L x 36.50mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Weight Parallel 10V, Series 20V Parallel 1A, Series 500mA No Dual Center Tap No 10 VA Mounting Type Through Hole 15 Oomm L x 36.50mm W 15 Oovmm Voltage - Isolation 0.563 lb (255.37g) | Туре | Laminated Core |
| Current - Output (Max) Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style Size / Dimension Voltage - Isolation Voltage - Isolation Parallel 1A, Series 500mA Single Single No Pual No Powal No Powal No Powal No No Powal No | Voltage - Primary | 115V |
| Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Signer Winding(s) Single Single Single Single No No No 10 VA 41 V | Voltage - Secondary (Full Load) | Parallel 10V, Series 20V |
| Secondary Winding(s)DualCenter TapNoPower - Max10 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.60mm L x 36.50mm WHeight - Seated (Max)41.27mmVoltage - Isolation1500VrmsWeight0.563 lb (255.37g) | Current - Output (Max) | Parallel 1A, Series 500mA |
| Center Tap Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 36.50mm W Height - Seated (Max) Voltage - Isolation 1500Vrms Weight No 10 VA Through Hole PC Pin 47.60mm L x 36.50mm W 41.27mm 41.27mm 0.563 lb (255.37g) | Primary Winding(s) | Single |
| Power - Max Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 36.50mm W Height - Seated (Max) Voltage - Isolation 1500Vrms Weight 0.563 lb (255.37g) | Secondary Winding(s) | Dual |
| Mounting Type Through Hole PC Pin Size / Dimension 47.60mm L x 36.50mm W Height - Seated (Max) 41.27mm Voltage - Isolation 1500Vrms Weight 0.563 lb (255.37g) | Center Tap | No |
| Termination Style PC Pin Size / Dimension 47.60mm L x 36.50mm W Height - Seated (Max) 41.27mm Voltage - Isolation 1500Vrms Weight 0.563 lb (255.37g) | Power - Max | 10 VA |
| Size / Dimension 47.60mm L x 36.50mm W Height - Seated (Max) 41.27mm Voltage - Isolation 1500Vrms Weight 0.563 lb (255.37g) | Mounting Type | Through Hole |
| Height - Seated (Max) Voltage - Isolation 1500Vrms Weight 0.563 lb (255.37g) | Termination Style | PC Pin |
| Voltage - Isolation 1500Vrms Weight 0.563 lb (255.37g) | Size / Dimension | 47.60mm L x 36.50mm W |
| Weight 0.563 lb (255.37g) | Height - Seated (Max) | 41.27mm |
| | Voltage - Isolation | 1500Vrms |
| Report errors? | Weight | 0.563 lb (255.37g) |
| | | Report errors? |

PC-20-500 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PC-20-500 Payment Methods





















PC-20-500 Shipping Methods













If you have any question about PC-20-500, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com