

PC-28-800B52 Information

Heisener.com

Part Number PC-28-800B52

Manufacturer Pulse Electronics Power

Category Transformers

Power Transformers

Description XFRMR LAMINATED 24VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PC-28-800B52 Specifications

Manufacturer Part Number PC-28-800B52 Manufacturer Pulse Electronics Power Category Transformers Package - Series PC Plug-In Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 14V, Series 28V Current - Output (Max) Parallel 1.6A, Series 800mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 24 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 57.15mm W Height - Seated (Max) 34.93mm Voltage - Isolation 1500Vrms Weight 0.75 lb (340.19g)		
CategoryTransformersPackage-SeriesPC Plug-InTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 14V, Series 28VCurrent - Output (Max)Parallel 1.6A, Series 800mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max24 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 57.15mm WHeight - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)	Manufacturer Part Number	PC-28-800B52
Package Package PC Plug-In Type Laminated Core Voltage - Primary Voltage - Secondary (Full Load) Parallel 14V, Series 28V Current - Output (Max) Parallel 1.6A, Series 800mA Primary Winding(s) Secondary Winding(s) Sungle Secondary Winding(s) Dual Center Tap No Power - Max Augusta 24 VA Mounting Type Through Hole Termination Style Size / Dimension 41.28mm L x 57.15mm W Height - Seated (Max) Voltage - Isolation PC Pin Size / Dimension Voltage - Isolation Voltage -	Manufacturer	Pulse Electronics Power
Package-SeriesPC Plug-InTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 14V, Series 28VCurrent - Output (Max)Parallel 1.6A, Series 800mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max24 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 57.15mm WHeight - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)	Category	Transformers
SeriesPC Plug-InTypeLaminated CoreVoltage - Primary115 VVoltage - Secondary (Full Load)Parallel 14V, Series 28 VCurrent - Output (Max)Parallel 1.6A, Series 800mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max24 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 57.15mm WHeight - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)		Power Transformers
Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 14V, Series 28V Current - Output (Max) Parallel 1.6A, Series 800mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 24 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 57.15mm W Height - Seated (Max) 34.93mm Voltage - Isolation 1500Vrms Weight 0.75 lb (340.19g)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 14V, Series 28V Current - Output (Max) Parallel 1.6A, Series 800mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 24 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 57.15mm W Height - Seated (Max) Voltage - Isolation 0.75 lb (340.19g)	Series	PC Plug-In
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 1.6A, Series 800mA Primary Winding(s) Secondary Winding(s) Center Tap No Power - Max Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Parallel 1.4V, Series 28V Parallel 1.6A, Series 800mA Single No Dual No Powal Popual No 24 VA Mounting Type Through Hole PC Pin 31.28mm L x 57.15mm W 34.93mm Voltage - Isolation 1500Vrms Weight	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 24 VA Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Voltage - Isolation Parallel 1.6A, Series 800mA Single Dual Pull No Pull No Pull No Pthole PC Pin PC Pin Size / Dimension 41.28mm L x 57.15mm W 34.93mm Voltage - Isolation 1500Vrms Voltage - Isolation 0.75 lb (340.19g)	Voltage - Primary	115V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 24 VA Mounting Type Through Hole Termination Style Size / Dimension 41.28mm L x 57.15mm W Height - Seated (Max) Voltage - Isolation 1500Vrms Weight Onto the Management of the	Voltage - Secondary (Full Load)	Parallel 14V, Series 28V
Secondary Winding(s)DualCenter TapNoPower - Max24 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 57.15mm WHeight - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)	Current - Output (Max)	Parallel 1.6A, Series 800mA
Center TapNoPower - Max24 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 57.15mm WHeight - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)	Primary Winding(s)	Single
Power - Max Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 57.15mm W Height - Seated (Max) Voltage - Isolation 1500Vrms Weight 0.75 lb (340.19g)	Secondary Winding(s)	Dual
Mounting Type Through Hole PC Pin Size / Dimension 41.28mm L x 57.15mm W Height - Seated (Max) 34.93mm Voltage - Isolation 1500Vrms Weight 0.75 lb (340.19g)	Center Tap	No
Termination Style PC Pin Size / Dimension 41.28mm L x 57.15mm W Height - Seated (Max) 34.93mm Voltage - Isolation 1500Vrms Weight 0.75 lb (340.19g)	Power - Max	24 VA
Size / Dimension 41.28mm L x 57.15mm W Height - Seated (Max) 34.93mm Voltage - Isolation 1500Vrms Weight 0.75 lb (340.19g)	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation 1500Vrms Weight 0.75 lb (340.19g)	Termination Style	PC Pin
Voltage - Isolation 1500Vrms Weight 0.75 lb (340.19g)	Size / Dimension	41.28mm L x 57.15mm W
Weight 0.75 lb (340.19g)	Height - Seated (Max)	34.93mm
	Voltage - Isolation	1500Vrms
Report errors?	Weight	0.75 lb (340.19g)
		Report errors?

PC-28-800B52 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PC-28-800B52 Payment Methods



















PC-28-800B52 Shipping Methods













If you have any question about PC-28-800B52, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com