

## PC-34-700B24

#### PC-34-700B24 Information

Heisener.com	PC-34-700B24 Pulse Electronics Power Transformers Power Transformers XFRMR LAMINATED 24VA THRU HOLE - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### PC-34-700B24 Specifications

ManufacturerPulse Electronics PowerCategoryTransformersPackage-Package-SeriesPC Plug-InTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 17V, Series 34VCurrent - Output (Max)Parallel 1.4A, Series 700mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max24 VAMounting TypeFrinough HoleTermination StylePC PinSize / Dimension41.28mm Lx 57.15mm WHeight - Seated (Max)34.93mmVoltage - Isolation1500Vrms		
CategoryTransformersPackage-Package-SeriesPC Plug-InTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 17V, Series 34VCurrent - Output (Max)Parallel 1.4A, Series 700mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max4VAMounting TypeThrough HoleSize / Dimension41.28mm L x 57.15mm WHeight - Seated (Max)34.93mmVoltage - Isolation500VrmsWeight0.75 lb (340.19g)	Manufacturer Part Number	PC-34-700B24
PackagePower TransformersPackage-SeriesPC Plug-InTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 17V, Series 34VCurrent - Output (Max)Parallel 1.4A, Series 700mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max24 VAMounting TypeThrough HoleSize / Dimension41.28mm L x 57.15mm WHeight - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)	Manufacturer	Pulse Electronics Power
Package-SeriesPC Pug-InTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 17V, Series 34VCurrent - Output (Max)Parallel 1.4A, Series 700mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max24 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension34.93mm L x 57.15mm WVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)	Category	Transformers
SeriesPC Plug-InTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 17V, Series 34VCurrent - Output (Max)Parallel 1.4A, Series 700mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max24 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension34.93mmHeight - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)		Power Transformers
TypeLaminded CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 17V, Series 34VCurrent - Output (Max)Parallel 1.4A, Series 700mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max24 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 57.15mm WHeight - Seated (Max)34.93mmWoltage - Isolation1500VrmsWeight0.75 lb (340.19g)	Package	-
AVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 17V, Series 34VCurrent - Output (Max)Parallel 1.4A, Series 700mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max24 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension34.93mmHeight - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 Ib (340.19g)	Series	PC Plug-In
Voltage - Secondary (Full Load)Parallel 17V, Series 34VCurrent - Output (Max)Parallel 1.4A, Series 700mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max24 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 57.15mm WHeight - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)	Туре	Laminated Core
Current - Output (Max)Parallel 1.4A, Series 700mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max24 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 57.15mm WHeight - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)	Voltage - Primary	115V
Primary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max24 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 57.15mm WHeight - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)	Voltage - Secondary (Full Load)	Parallel 17V, Series 34V
Secondary Winding(s)DualCenter TapNoPower - Max24 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 57.15mm WHeight - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)	Current - Output (Max)	Parallel 1.4A, Series 700mA
Center TapNoPower - Max24 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 57.15mm WHeight - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)	Primary Winding(s)	Single
Power - Max24 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 57.15mm WHeight - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)	Secondary Winding(s)	Dual
Mounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 57.15mm WHeight - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)	Center Tap	No
Termination StylePC PinSize / Dimension41.28mm L x 57.15mm WHeight - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)	Power - Max	24 VA
Size / Dimension 41.28mm L x 57.15mm W   Height - Seated (Max) 34.93mm   Voltage - Isolation 1500Vrms   Weight 0.75 lb (340.19g)	Mounting Type	Through Hole
Height - Seated (Max)34.93mmVoltage - Isolation1500VrmsWeight0.75 lb (340.19g)	Termination Style	PC Pin
Voltage - Isolation1500VrmsWeight0.75 lb (340.19g)	Size / Dimension	41.28mm L x 57.15mm W
Weight 0.75 lb (340.19g)	Height - Seated (Max)	34.93mm
	Voltage - Isolation	1500Vrms
Report errors?	Weight	0.75 lb (340.19g)
		Report errors?

#### PC-34-700B24 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE GUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

# PC-34-700B24 Payment Methods WIRE transfer PayPal Wish MoneyGram Alipay: VISA PC-34-700B24 Shipping Methods



If you have any question about PC-34-700B24, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com