



# PC00SE-18-32P Information

Heisener.com

Part Number PC00SE-18-32P

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

**Description** CONN RCPT 32POS WALL MNT PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **PC00SE-18-32P Specifications**

Manufacturer Part Number       PC00SE-18-32P         Manufacturer       Amphenol Industrial Operations         Category       Connectors, Interconnects         Package       -         Series       MIL-DTL-26482 Series I, PC         Connector Type       Receptacle, Male Pins         Number of Positions       32         Shell Size - Insert       18-32         Shell Size, MIL       -         Mounting Type       Panel Mount, Flange         Termination       Crimp         Fastening Type       Threaded         Orientation       N (Normal)         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum, Clear Chromate over Bright Cadmium         Contact Finish       Gold         Features       -         Voltage - Rated       600VAC         Current Rating       7.5A		
Category Connectors, Interconnects Circular Connectors  Package - Series MIL-DTL-26482 Series I, PC Connector Type Receptacle, Male Pins Number of Positions 32 Shell Size - Insert 18-32 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Manufacturer Part Number	PC00SE-18-32P
Circular Connectors  Package - Series MIL-DTL-26482 Series I, PC Connector Type Receptacle, Male Pins Number of Positions 32 Shell Size - Insert 18-32 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features Voltage - Rated 600VAC Current Rating 7.5A	Manufacturer	Amphenol Industrial Operations
Package - Series MIL-DTL-26482 Series I, PC Connector Type Receptacle, Male Pins Number of Positions 32 Shell Size - Insert 18-32 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features Voltage - Rated 600VAC Current Rating 7.5A	Category	Connectors, Interconnects
Series MIL-DTL-26482 Series I, PC Connector Type Receptacle, Male Pins Number of Positions 32 Shell Size - Insert 18-32 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A		Circular Connectors
Connector Type Receptacle, Male Pins Number of Positions 32 Shell Size - Insert 18-32 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Package	-
Number of Positions  Shell Size - Insert  18-32  Shell Size, MIL  Mounting Type  Panel Mount, Flange  Termination  Crimp  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum, Clear Chromate over Bright Cadmium  Contact Finish  Features  Voltage - Rated  Current Rating  7.5A	Series	MIL-DTL-26482 Series I, PC
Shell Size - Insert  Shell Size, MIL  Mounting Type  Panel Mount, Flange  Termination  Crimp  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Clear Chromate over Bright Cadmium  Contact Finish  Gold  Features  Voltage - Rated  Current Rating  7.5A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features Voltage - Rated OOVAC Current Rating 7.5A	Number of Positions	32
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A	Shell Size - Insert	18-32
Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Shell Size, MIL	-
Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Termination	Crimp
Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium  Contact Finish Gold  Features -  Voltage - Rated 600VAC  Current Rating 7.5A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Clear Chromate over Bright Cadmium Gold Contact Finish Gold	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 600VAC Current Rating 7.5A	Shell Material, Finish	Aluminum, Clear Chromate over Bright Cadmium
Voltage - Rated 600VAC Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	-
	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A
		Report errors?

#### PC00SE-18-32P Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### PC00SE-18-32P Payment Methods

































If you have any question about PC00SE-18-32P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com