

PC01E-12-8P Information

Heisener.com

Part Number PC01E-12-8P

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 8POS INLINE PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PC01E-12-8P Specifications

Manufacturer Part NumberPC01E-12-8PManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, PCConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert12-8Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5AReport errors?		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, PCConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert12-8Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A	Manufacturer Part Number	PC01E-12-8P
Package-SeriesMIL-DTL-26482 Series I, PCConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert12-8Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A	Manufacturer	Amphenol Industrial Operations
Package - MIL-DTL-26482 Series I, PC Connector Type Receptacle, Male Pins Number of Positions 8 Shell Size - Insert 12-8 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features Voltage - Rated Current Rating 7,5A	Category	Connectors, Interconnects
SeriesMIL-DTL-26482 Series I, PCConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert12-8Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert12-8Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A	Package	-
Number of Positions8Shell Size - Insert12-8Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A	Series	MIL-DTL-26482 Series I, PC
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Features - Voltage - Rated 600VAC Current Rating 7.5A	Number of Positions	8
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A	Shell Size - Insert	12-8
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Shell Size, MIL	-
Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Clear Chromate over Bright Cadmium Gold - Voltage - Rated 600VAC 7.5A	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 600VAC Current Rating 7.5A	Shell Material, Finish	Aluminum, Clear Chromate over Bright Cadmium
Voltage - Rated 600VAC Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	-
	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A
		Report errors?

PC01E-12-8P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PC01E-12-8P Payment Methods





















PC01E-12-8P Shipping Methods













If you have any question about PC01E-12-8P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com