



PC06E-14-15P(SR) Information

Heisener.com

Part Number PC06E-14-15P(SR)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects **Circular Connectors**

Description CONN PLUG 15POS INLINE PIN

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PC06E-14-15P(SR) Specifications

Manufacturer Part NumberPC06E-14-15P(SR)ManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, PCConnector TypePlug, Male PinsNumber of Positions15Shell Size - Insert14-15Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A, 13A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, PCConnector TypePlug, Male PinsNumber of Positions15Shell Size - Insert14-15Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A, 13A	Manufacturer Part Number	PC06E-14-15P(SR)
Package-SeriesMIL-DTL-26482 Series I, PCConnector TypePlug, Male PinsNumber of Positions15Shell Size - Insert14-15Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A, 13A	Manufacturer	Amphenol Industrial Operations
Package - MIL-DTL-26482 Series I, PC Connector Type Plug, Male Pins Number of Positions 15 Shell Size - Insert 14-15 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7, 7.5A, 13A	Category	Connectors, Interconnects
Series MIL-DTL-26482 Series I, PC Connector Type Plug, Male Pins Number of Positions 15 Shell Size - Insert 14-15 Shell Size, MIL		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions15Shell Size - Insert14-15Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A, 13A	Package	-
Number of Positions15Shell Size - Insert14-15Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A, 13A	Series	MIL-DTL-26482 Series I, PC
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A, 13A	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A, 13A	Number of Positions	15
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A, 13A	Shell Size - Insert	14-15
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A, 13A	Shell Size, MIL	-
Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A, 13A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A, 13A	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A, 13A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating Aluminum, Clear Chromate over Bright Cadmium Gold Current Rating Aluminum, Clear Chromate over Bright Cadmium Gold Current Rating Strain Relief 7.5A, 13A	Orientation	N (Normal)
Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A, 13A	Ingress Protection	Environment Resistant
Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A, 13A	Shell Material, Finish	Aluminum, Clear Chromate over Bright Cadmium
Voltage - Rated 600VAC Current Rating 7.5A, 13A	Contact Finish	Gold
Current Rating 7.5A, 13A	Features	Strain Relief
	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A, 13A
		Report errors?

PC06E-14-15P(SR) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PC06E-14-15P(SR) Payment Methods





















PC06E-14-15P(SR) Shipping Methods













If you have any question about PC06E-14-15P(SR), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com