

### PC06E-8-3S Information

Heisener.com

Part Number PC06E-8-3S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 3POS INLINE SKT

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **PC06E-8-3S Specifications**

Manufacturer Part Number     PC06E-8-3S       Manufacturer     Amphenol Industrial Operations       Category     Connectors, Interconnects       Package     -       Series     MIL-DTL-26482 Series I, PC       Connector Type     Plug, Female Sockets       Number of Positions     3       Shell Size - Insert     8-3       Shell Size, MIL     -       Mounting Type     Free Hanging (In-Line)       Termination     Solder Cup       Fastening Type     Threaded       Orientation     N (Normal)       Ingress Protection     Environment Resistant       Shell Material, Finish     Aluminum, Clear Chromate over Bright Cadmium       Contact Finish     Gold       Features     -       Voltage - Rated     600VAC       Current Rating     7.5A		
Category Connectors, Interconnects Circular Connectors  Package - Series MIL-DTL-26482 Series I, PC Connector Type Plug, Female Sockets Number of Positions 3 Shell Size - Insert 8-3 Shell Size, MIL - Mounting Type Free Hanging (In-Line)  Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features Voltage - Rated Current Rating 7.5A	Manufacturer Part Number	PC06E-8-3S
Circular Connectors  Package Series MIL-DTL-26482 Series I, PC Connector Type Plug, Female Sockets Number of Positions 3 Shell Size - Insert 8-3 Shell Size, MIL	Manufacturer	Amphenol Industrial Operations
Package - MIL-DTL-26482 Series I, PC Connector Type Plug, Female Sockets Number of Positions 3 Shell Size - Insert 8-3 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Category	Connectors, Interconnects
Series MIL-DTL-26482 Series I, PC Connector Type Plug, Female Sockets Number of Positions 3 Shell Size - Insert 8-3 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert8-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A	Package	-
Number of Positions  Shell Size - Insert  8-3  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Clear Chromate over Bright Cadmium  Contact Finish  Gold  Features  Voltage - Rated  600VAC  Current Rating  7.5A	Series	MIL-DTL-26482 Series I, PC
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Connector Type	Plug, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Number of Positions	3
Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium  Contact Finish Gold  Features -  Voltage - Rated 600VAC  Current Rating 7.5A	Shell Size - Insert	8-3
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Shell Size, MIL	-
Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Termination	Solder Cup
Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium  Contact Finish Gold  Features -  Voltage - Rated 600VAC  Current Rating 7.5A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating 7.5A	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 600VAC Current Rating 7.5A	Shell Material, Finish	Aluminum, Clear Chromate over Bright Cadmium
Voltage - Rated 600VAC Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	-
-	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A
		Report errors?

#### PC06E-8-3S Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **PC06E-8-3S Payment Methods**



















# **PC06E-8-3S Shipping Methods**













If you have any question about PC06E-8-3S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com