

PC07A-8-4S(SR)

Quote

PC07A-8-4S(SR) Information

Part Number	PC07A-8-4S(SR)	
Manufacturer	Amphenol Industrial Operations	
Category	Connectors, Interconnects Circular Connectors	
Description	CONN RCPT 4POS JAM NUT SKT	- 300 E
Package	-	
	For the pricing/inventory/lead time, please contact	L AP
For Reference Only	E-mail: salesdept@heisener.com	Request a (
	Manufacturer Category Description	ManufacturerAmphenol Industrial OperationsCategoryConnectors, Interconnects Circular ConnectorsDescriptionCONN RCPT 4POS JAM NUT SKTPackage-For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



PC07A-8-4S(SR) Specifications

ManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsCircular ConnectorsCircular ConnectorsPackage-SeriesMIL-DTL-26482 Series I, PCConnector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert8-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VAC		
CategoryConnectors, Interconnects Circular ConnectorsPackage-SeriesMIL-DTL-26482 Series I, PCConnector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert8-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeaturesStrain ReliefVoltage - Rated7.5A	Manufacturer Part Number	PC07A-8-4S(SR)
Circular ConnectorsPackage-SeriesMIL-DTL-26482 Series I, PCConnector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert8-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeaturesStrain ReliefVoltage - Rated0.5A	Manufacturer	Amphenol Industrial Operations
Package-SeriesMIL-DTL-26482 Series I, PCConnector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert8-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Clear Chromate over Bright CadmiumFeaturesGoldVoltage - Rated600VACCurrent Rating7.5A	Category	Connectors, Interconnects
SeriesMIL-DTL-26482 Series I, PCConnector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert8-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishGoldContact FinishGoldFeaturesStrain ReliefVoltage - Rated7.5A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert8-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishGoldContact FinishGoldFeaturesStrain ReliefVoltage - Rated7.5A	Package	-
Number of Positions4Shell Size - Insert8-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeaturesStrain ReliefVoltage - Rated7.5A	Series	MIL-DTL-26482 Series I, PC
Shell Size - Insert8-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeaturesStrain ReliefVoltage - Rated7.5A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeaturesStrain ReliefVoltage - Rated00VACKent Rating7.5A	Number of Positions	4
Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACGurrent Rating7.5A	Shell Size - Insert	8-4
TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A	Shell Size, MIL	-
Fastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
OrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A	Termination	Solder Cup
Ingress Protection-Shell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A	Fastening Type	Threaded
Shell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A	Orientation	N (Normal)
Contact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A	Ingress Protection	-
FeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A	Shell Material, Finish	Aluminum, Clear Chromate over Bright Cadmium
Voltage - Rated600VACCurrent Rating7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	Strain Relief
-	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A
		Report errors?

PC07A-8-4S(SR) Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

PC07A-8-4S(SR) Payment Methods



PC07A-8-4S(SR) Shipping Methods



If you have any question about PC07A-8-4S(SR), please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com