

PC08P-18-30P Information

Heisener.com

Part Number PC08P-18-30P

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects
Circular Connectors

Circular Connectors

Description CONN PLUG 30POS INLINE PIN RA

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PC08P-18-30P Specifications

Manufacturer Part NumberPC08P-18-30PManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, PCConnector TypePlug, Male PinsNumber of Positions30Shell Size - Insert18-30Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeaturesPottedVoltage - Rated600VACCurrent Rating7.5A, 13AReport errors?	_	
Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-26482 Series I, PC Connector Type Plug, Male Pins Number of Positions 30 Shell Size - Insert 18-30 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features Potted Voltage - Rated Current Rating 7.5A, 13A	Manufacturer Part Number	PC08P-18-30P
Package-SeriesMIL-DTL-26482 Series I, PCConnector TypePlug, Male PinsNumber of Positions30Shell Size - Insert18-30Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeaturesPottedVoltage - Rated600VACCurrent Rating7.5A, 13A	Manufacturer	Amphenol Industrial Operations
Package-SeriesMIL-DTL-26482 Series I, PCConnector TypePlug, Male PinsNumber of Positions30Shell Size - Insert18-30Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeaturesPottedVoltage - Rated600VACCurrent Rating7.5A, 13A	Category	Connectors, Interconnects
SeriesMIL-DTL-26482 Series I, PCConnector TypePlug, Male PinsNumber of Positions30Shell Size - Insert18-30Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeaturesPottedVoltage - Rated600VACCurrent Rating7.5A, 13A		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions30Shell Size - Insert18-30Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeaturesPottedVoltage - Rated600VACCurrent Rating7.5A, 13A	Package	-
Number of Positions30Shell Size - Insert18-30Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Clear Chromate over Bright CadmiumContact FinishGoldFeaturesPottedVoltage - Rated600VACCurrent Rating7.5A, 13A	Series	MIL-DTL-26482 Series I, PC
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features Potted Voltage - Rated 600VAC Current Rating 7.5A, 13A	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features Potted Voltage - Rated 600VAC Current Rating 7.5A, 13A	Number of Positions	30
Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features Potted Voltage - Rated 600VAC Current Rating 7.5A, 13A	Shell Size - Insert	18-30
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features Potted Voltage - Rated 600VAC Current Rating 7.5A, 13A	Shell Size, MIL	-
Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features Potted Voltage - Rated 600VAC Current Rating 7.5A, 13A	Mounting Type	Free Hanging (In-Line), Right Angle
Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features Potted Voltage - Rated 600VAC Current Rating 7.5A, 13A	Termination	Solder Cup
Ingress Protection - Shell Material, Finish Aluminum, Clear Chromate over Bright Cadmium Contact Finish Gold Features Potted Voltage - Rated 600VAC Current Rating 7.5A, 13A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Gold Features Potted Voltage - Rated Current Rating 7.5A, 13A	Orientation	N (Normal)
Contact Finish Gold Features Potted Voltage - Rated 600VAC Current Rating 7.5A, 13A	Ingress Protection	-
Features Potted Voltage - Rated 600VAC Current Rating 7.5A, 13A	Shell Material, Finish	Aluminum, Clear Chromate over Bright Cadmium
Voltage - Rated 600VAC Current Rating 7.5A, 13A	Contact Finish	Gold
Current Rating 7.5A, 13A	Features	Potted
·	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A, 13A
		Report errors?

PC08P-18-30P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PC08P-18-30P Payment Methods



















PC08P-18-30P Shipping Methods













If you have any question about PC08P-18-30P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com