



### PC364N1T000F Information

Heisener.com

Part Number PC364N1T000F

Manufacturer Sharp Microelectronics

Category **Isolators** 

Optoisolators - Transistor, Photovoltaic Output

**Description** OPTOISO 3.75KV TRANS 4-MINI-FLAT

**Package** 4-SMD, Gull Wing

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **PC364N1T000F Specifications**

Manufacturer Part Number         PC364N1T000F           Manufacturer         Sharp Microelectronics           Category         Isolators           Optoisolators - Transistor, Photovoltaic Output           Package         4-SMD, Gull Wing           Series         -           Number of Channels         1           Voltage - Isolation         3750Vrms           Current Transfer Ratio (Min)         10% @ 500μA           Current Transfer Ratio (Max)         300% @ 500μA           Turn On / Turn Off Time (Typ)         -           Rise / Fall Time (Typ)         4μs, 3μs           Input Type         AC, DC           Output Type         Transistor           Voltage - Output (Max)         80V           Current - Output / Channel         50mA           Voltage - Forward (Vf) (Typ)         1.2V           Current - DC Forward (If) (Max)         10mA           Vec Saturation (Max)         200mV           Operating Temperature         -30°C ~ 100°C           Mounting Type         Surface Mount           Package / Case         4-SMD, Gull Wing           Supplier Device Package         4-Mini-Flat	•	
Category         Isolators           Optoisolators - Transistor, Photovoltaic Output           Package         4-SMD, Gull Wing           Series         -           Number of Channels         1           Voltage - Isolation         3750Vrms           Current Transfer Ratio (Min)         100% @ 500μA           Current Transfer Ratio (Max)         300% @ 500μA           Turn On / Turn Off Time (Typ)         -           Rise / Fall Time (Typ)         4μs, 3μs           Input Type         AC, DC           Output Type         Transistor           Voltage - Output (Max)         80V           Current - Output / Channel         50mA           Voltage - Forward (Vf) (Typ)         1.2V           Current - DC Forward (If) (Max)         10mA           Vce Saturation (Max)         200mV           Operating Temperature         -30°C ~ 100°C           Mounting Type         Surface Mount           Package / Case         4-SMD, Gull Wing           Supplier Device Package         4-Mini-Flat	Manufacturer Part Number	PC364N1T000F
Package         4-SMD, Gull Wing           Series         -           Number of Channels         1           Voltage - Isolation         3750Vrms           Current Transfer Ratio (Min)         100% @ 500μA           Current Transfer Ratio (Max)         300% @ 500μA           Turn On / Turn Off Time (Typ)         -           Rise / Fall Time (Typ)         4μs, 3μs           Input Type         AC, DC           Output Type         Transistor           Voltage - Output (Max)         80V           Current - Output / Channel         50mA           Voltage - Forward (Vf) (Typ)         1.2V           Current - DC Forward (If) (Max)         10mA           Vec Saturation (Max)         200mV           Operating Temperature         -30°C ~ 100°C           Mounting Type         Surface Mount           Package / Case         4-SMD, Gull Wing           Supplier Device Package         4-Mini-Flat	Manufacturer	Sharp Microelectronics
Package         4-SMD, Gull Wing           Series         -           Number of Channels         1           Voltage - Isolation         3750 Vrms           Current Transfer Ratio (Min)         100% @ 500μA           Current Transfer Ratio (Max)         300% @ 500μA           Turn On / Turn Off Time (Typ)         -           Rise / Fall Time (Typ)         4μs, 3μs           Input Type         AC, DC           Output Type         Transistor           Voltage - Output (Max)         80V           Current - Output / Channel         50mA           Voltage - Forward (Vf) (Typ)         1.2V           Current - DC Forward (If) (Max)         10mA           Vec Saturation (Max)         200mV           Operating Temperature         -30°C ~ 100°C           Mounting Type         Surface Mount           Package / Case         4-SMD, Gull Wing           Supplier Device Package         4-Mini-Flat	Category	Isolators
Series         -           Number of Channels         1           Voltage - Isolation         3750Vrms           Current Transfer Ratio (Min)         100% @ 500μA           Current Transfer Ratio (Max)         300% @ 500μA           Turn On / Turn Off Time (Typ)         -           Rise / Fall Time (Typ)         4μs, 3μs           Input Type         AC, DC           Output Type         Transistor           Voltage - Output (Max)         80V           Current - Output / Channel         50mA           Voltage - Forward (Vf) (Typ)         1.2V           Current - DC Forward (If) (Max)         10mA           Vce Saturation (Max)         200mV           Operating Temperature         -30°C ~ 100°C           Mounting Type         Surface Mount           Package / Case         4-SMD, Gull Wing           Supplier Device Package         4-Mini-Flat		Optoisolators - Transistor, Photovoltaic Output
Number of Channels1Voltage - Isolation3750VrmsCurrent Transfer Ratio (Min)100% @ 500μACurrent Transfer Ratio (Max)300% @ 500μATurn On / Turn Off Time (Typ)-Rise / Fall Time (Typ)4μs, 3μsInput TypeAC, DCOutput TypeTransistorVoltage - Output (Max)80VCurrent - Output / Channel50mAVoltage - Forward (Vf) (Typ)1.2VCurrent - DC Forward (If) (Max)10mAVec Saturation (Max)200mVOperating Temperature-30°C ~ 100°CMounting TypeSurface MountPackage / Case4-SMD, Gull WingSupplier Device Package4-Mini-Flat	Package	4-SMD, Gull Wing
Voltage - Isolation3750VrmsCurrent Transfer Ratio (Min)100% @ 500μACurrent Transfer Ratio (Max)300% @ 500μATurn On / Turn Off Time (Typ)-Rise / Fall Time (Typ)4μs, 3μsInput TypeAC, DCOutput TypeTransistorVoltage - Output (Max)80VCurrent - Output / Channel50mAVoltage - Forward (Vf) (Typ)1.2VCurrent - DC Forward (If) (Max)10mAVce Saturation (Max)200mVOperating Temperature-30°C ~ 100°CMounting TypeSurface MountPackage / Case4-SMD, Gull WingSupplier Device Package4-Mini-Flat	Series	-
Current Transfer Ratio (Min)  Current Transfer Ratio (Max)  300% © 500µA  Turn On / Turn Off Time (Typ)  - Rise / Fall Time (Typ)  4µs, 3µs  Input Type  AC, DC  Output Type  Transistor  Voltage - Output (Max)  80V  Current - Output / Channel  Voltage - Forward (Vf) (Typ)  1.2V  Current - DC Forward (If) (Max)  Vee Saturation (Max)  Operating Temperature  -30°C ~ 100°C  Mounting Type  Surface Mount  Package / Case  4-SMD, Gull Wing  Supplier Device Package	Number of Channels	1
Current Transfer Ratio (Max)300% @ 500μATurn On / Turn Off Time (Typ)-Rise / Fall Time (Typ)4μs, 3μsInput TypeAC, DCOutput TypeTransistorVoltage - Output (Max)80VCurrent - Output / Channel50mAVoltage - Forward (Vf) (Typ)1.2VCurrent - DC Forward (If) (Max)10mAVce Saturation (Max)200mVOperating Temperature-30°C ~ 100°CMounting TypeSurface MountPackage / Case4-SMD, Gull WingSupplier Device Package4-Mini-Flat	Voltage - Isolation	3750Vrms
Turn On / Turn Off Time (Typ)-Rise / Fall Time (Typ)4μs, 3μsInput TypeAC, DCOutput TypeTransistorVoltage - Output (Max)80VCurrent - Output / Channel50mAVoltage - Forward (Vf) (Typ)1.2VCurrent - DC Forward (If) (Max)10mAVce Saturation (Max)200mVOperating Temperature-30°C ~ 100°CMounting TypeSurface MountPackage / Case4-SMD, Gull WingSupplier Device Package4-Mini-Flat	Current Transfer Ratio (Min)	100% @ 500μA
Rise / Fall Time (Typ)4μs, 3μsInput TypeAC, DCOutput TypeTransistorVoltage - Output (Max)80VCurrent - Output / Channel50mAVoltage - Forward (Vf) (Typ)1.2VCurrent - DC Forward (If) (Max)10mAVce Saturation (Max)200mVOperating Temperature-30°C ~ 100°CMounting TypeSurface MountPackage / Case4-SMD, Gull WingSupplier Device Package4-Mini-Flat	Current Transfer Ratio (Max)	300% @ 500μA
Input Type AC, DC Output Type Transistor  Voltage - Output (Max) 80V Current - Output / Channel 50mA  Voltage - Forward (Vf) (Typ) 1.2V Current - DC Forward (If) (Max) 10mA  Vce Saturation (Max) 200mV Operating Temperature -30°C ~ 100°C Mounting Type Surface Mount Package / Case 4-SMD, Gull Wing Supplier Device Package 4-Mini-Flat	Turn On / Turn Off Time (Typ)	-
Output Type  Voltage - Output (Max)  80V  Current - Output / Channel  50mA  Voltage - Forward (Vf) (Typ)  1.2V  Current - DC Forward (If) (Max)  10mA  Vce Saturation (Max)  Operating Temperature  -30°C ~ 100°C  Mounting Type  Surface Mount  Package / Case  4-SMD, Gull Wing  Supplier Device Package	Rise / Fall Time (Typ)	4μs, 3μs
Voltage - Output (Max)  Current - Output / Channel  Voltage - Forward (Vf) (Typ)  1.2V  Current - DC Forward (If) (Max)  Vce Saturation (Max)  Operating Temperature  Mounting Type  Surface Mount  Package / Case  4-SMD, Gull Wing  Supplier Device Package  4-Mini-Flat	Input Type	AC, DC
Current - Output / Channel 50mA  Voltage - Forward (Vf) (Typ) 1.2V  Current - DC Forward (If) (Max) 10mA  Vce Saturation (Max) 200mV  Operating Temperature -30°C ~ 100°C  Mounting Type Surface Mount  Package / Case 4-SMD, Gull Wing  Supplier Device Package 4-Mini-Flat	Output Type	Transistor
Voltage - Forward (Vf) (Typ)  1.2V  Current - DC Forward (If) (Max)  10mA  Vce Saturation (Max)  Operating Temperature  -30°C ~ 100°C  Mounting Type  Surface Mount  Package / Case  4-SMD, Gull Wing  Supplier Device Package  4-Mini-Flat	Voltage - Output (Max)	80V
Current - DC Forward (If) (Max)  Vce Saturation (Max)  Operating Temperature  -30°C ~ 100°C  Mounting Type  Surface Mount  Package / Case  4-SMD, Gull Wing  Supplier Device Package  4-Mini-Flat	Current - Output / Channel	50mA
Vce Saturation (Max)200mVOperating Temperature-30°C ~ 100°CMounting TypeSurface MountPackage / Case4-SMD, Gull WingSupplier Device Package4-Mini-Flat	Voltage - Forward (Vf) (Typ)	1.2V
Operating Temperature  -30°C ~ 100°C  Mounting Type  Surface Mount  Package / Case  4-SMD, Gull Wing  Supplier Device Package  4-Mini-Flat	Current - DC Forward (If) (Max)	10mA
Mounting Type Surface Mount Package / Case 4-SMD, Gull Wing Supplier Device Package 4-Mini-Flat	Vce Saturation (Max)	200mV
Package / Case 4-SMD, Gull Wing Supplier Device Package 4-Mini-Flat	Operating Temperature	-30°C ~ 100°C
Supplier Device Package 4-Mini-Flat	Mounting Type	Surface Mount
	Package / Case	4-SMD, Gull Wing
Report errors?	Supplier Device Package	4-Mini-Flat
		Report errors?

### PC364N1T000F Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### PC364N1T000F Payment Methods



















## **PC364N1T000F Shipping Methods**













If you have any question about PC364N1T000F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com