



### PCA.3S.415.CTLC11 Information

Heisener.com

Part Number PCA.3S.415.CTLC11

Manufacturer LEMO

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN INLINE RCPT 1HV(15KV) SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## PCA.3S.415.CTLC11 Specifications

| Manufacturer Part NumberPCA.3S.415.CTLC11ManufacturerLEMOCategoryConnectors, InterconnectsPackage-Series3SConnector TypeReceptacle, Female SocketsNumber of Positions1Shell Size - Insert415Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-Pull, Detent LockOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating8A |                          |                            |
|--|--------------------------|----------------------------|
| CategoryConnectors, Interconnects<br>Circular ConnectorsPackage-Series3SConnector TypeReceptacle, Female SocketsNumber of Positions1Shell Size - Insert415Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-Pull, Detent LockOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-   | Manufacturer Part Number | PCA.3S.415.CTLC11          |
| Package-Series3SConnector TypeReceptacle, Female SocketsNumber of Positions1Shell Size - Insert415Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-Pull, Detent LockOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-   | Manufacturer             | LEMO                       |
| Package-Series3SConnector TypeReceptacle, Female SocketsNumber of Positions1Shell Size - Insert415Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-Pull, Detent LockOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-   | Category                 | Connectors, Interconnects  |
| Series 3S Connector Type Receptacle, Female Sockets Number of Positions 1 Shell Size - Insert 415 Shell Size, MIL  |                          | Circular Connectors        |
| Connector Type Receptacle, Female Sockets Number of Positions 1 Shell Size - Insert 415 Shell Size, MIL  | Package                  | -                          |
| Number of Positions  Shell Size - Insert  415  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Push-Pull, Detent Lock  Orientation  Keyed  Ingress Protection  IP50 - Dust Protected  Shell Material, Finish  Brass, Chrome Plated  Contact Finish  Gold  Features  Backshell, Shielded  Voltage - Rated  -   | Series                   | 3S                         |
| Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Push-Pull, Detent Lock  Orientation  Keyed  Ingress Protection  IP50 - Dust Protected  Shell Material, Finish  Brass, Chrome Plated  Contact Finish  Gold  Features  Backshell, Shielded  Voltage - Rated  -   | Connector Type           | Receptacle, Female Sockets |
| Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Push-Pull, Detent Lock Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated -   | Number of Positions      | 1                          |
| Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-Pull, Detent LockOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-   | Shell Size - Insert      | 415                        |
| Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated -   | Shell Size, MIL          | -                          |
| Fastening Type Push-Pull, Detent Lock Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated -  | Mounting Type            | Free Hanging (In-Line)     |
| Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated -  | Termination              | Solder Cup                 |
| Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated -  | Fastening Type           | Push-Pull, Detent Lock     |
| Shell Material, Finish  Contact Finish  Gold  Features  Backshell, Shielded  Voltage - Rated   | Orientation              | Keyed                      |
| Contact Finish Gold Features Backshell, Shielded Voltage - Rated -   | Ingress Protection       | IP50 - Dust Protected      |
| Features Backshell, Shielded Voltage - Rated -   | Shell Material, Finish   | Brass, Chrome Plated       |
| Voltage - Rated -  | Contact Finish           | Gold                       |
| -  | Features                 | Backshell, Shielded        |
| Current Rating 8A  | Voltage - Rated          | -                          |
|  | Current Rating           | 8A                         |
| Report errors?   |                          | Report errors?             |

#### PCA.3S.415.CTLC11 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### PCA.3S.415.CTLC11 Payment Methods



















# PCA.3S.415.CTLC11 Shipping Methods













If you have any question about PCA.3S.415.CTLC11, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com