

PCLH-106A1S,000 Information



For Reference Only

Part Number PCLH-106A1S,000

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPDT 15A 110V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PCLH-106A1S,000 Specifications

Manufacturer Part NumberPCLH-106A1S,000ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPackage-SeriesPCLH, OEGRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage110VACContact FormSPDT (1 Form C)Contact Rating (Current)15ASwitching Voltage250VAC, 24VDC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)33 VACOperate Time20msRelease Time20msFeaturesInsulation - Class FMounting TypeSocketable		
Category Relays Power Relays, Over 2 Amps Package - Series PCLH, OEG Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 110VAC Contact Form SPDT (1 Form C) Contact Rating (Current) 15A Switching Voltage 250VAC, 24VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 20ms Release Time 20ms Features Insulation - Class F	Manufacturer Part Number	PCLH-106A1S,000
Package - Series PCLH, OEG Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 110VAC Contact Form SPDT (1 Form C) Contact Rating (Current) 15A Switching Voltage 250VAC, 24VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 20ms Release Time 20ms Features Insulation - Class F	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series PCLH, OEG Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 110VAC Contact Form SPDT (1 Form C) Contact Rating (Current) 15A Switching Voltage 250VAC, 24VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 20ms Release Time 20ms Features Insulation - Class F	Category	Relays
Series PCLH, OEG Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 110VAC Contact Form SPDT (1 Form C) Contact Rating (Current) 15A Switching Voltage 250VAC, 24VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 20ms Release Time 20ms Features Insulation - Class F		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage110VACContact FormSPDT (1 Form C)Contact Rating (Current)15ASwitching Voltage250VAC, 24VDC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)33 VACOperate Time20msRelease Time20msFeaturesInsulation - Class F	Package	-
Coil Type Non Latching Coil Current - Coil Voltage 110VAC Contact Form SPDT (1 Form C) Contact Rating (Current) 15A Switching Voltage 250VAC, 24VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 20ms Release Time 20ms Features Insulation - Class F	Series	PCLH, OEG
Coil Current Coil Voltage 110VAC Contact Form SPDT (1 Form C) Contact Rating (Current) 15A Switching Voltage 250VAC, 24VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 20ms Release Time 20ms Features Insulation - Class F	Relay Type	General Purpose
Coil Voltage 110VAC Contact Form SPDT (1 Form C) Contact Rating (Current) 15A Switching Voltage 250VAC, 24VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 20ms Release Time 20ms Features Insulation - Class F	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage 250VAC, 24VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 20ms Release Time 20ms Features Insulation - Class F	Coil Current	-
Contact Rating (Current) Switching Voltage 250VAC, 24VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 20ms Release Time 20ms Features Insulation - Class F	Coil Voltage	110VAC
Switching Voltage 250VAC, 24VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 20ms Release Time 20ms Features Insulation - Class F	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features Insulation - Class F	Contact Rating (Current)	15A
Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features Insulation - Class F	Switching Voltage	250VAC, 24VDC - Max
Operate Time20msRelease Time20msFeaturesInsulation - Class F	Turn On Voltage (Max)	88 VAC
Release Time 20ms Features Insulation - Class F	Turn Off Voltage (Min)	33 VAC
Features Insulation - Class F	Operate Time	20ms
	Release Time	20ms
Mounting Type Socketable	Features	Insulation - Class F
	Mounting Type	Socketable
Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Termination Style	Plug In, Quick Connect - 0.187" (4.7mm)
Report errors?		Report errors?

PCLH-106A1S,000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PCLH-106A1S,000 Payment Methods



















PCLH-106A1S,000 Shipping Methods













If you have any question about PCLH-106A1S,000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com