

## PCLH-203A1SP,000 Information



For Reference Only

Part Number PCLH-203A1SP,000

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE DPDT 15A 24V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## PCLH-203A1SP,000 Specifications

Manufacturer Part Number         PCLH-203AISP,000           Manufacturer         TE Connectivity Potter & Brumfield Relays           Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         PCLH, OEG           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         -           Coil Voltage         24VAC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         15A           Switching Voltage         120VAC - Max           Turn On Voltage (Max)         19.2 VAC           Turn Off Voltage (Min)         7.2 VAC           Operate Time         20ms           Release Time         20ms           Features         Insulation - Class F           Mounting Type         Through Hole           Termination Style         PC Pin		
Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         PCLH, OEG           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         -           Coil Voltage         24VAC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         15A           Switching Voltage         120VAC - Max           Turn On Voltage (Max)         19.2 VAC           Turn Off Voltage (Min)         7.2 VAC           Operate Time         20ms           Release Time         20ms           Features         Insulation - Class F           Mounting Type         Through Hole           Termination Style         PC Pin	Manufacturer Part Number	PCLH-203A1SP,000
Package         -           Series         PCLH, OEG           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         -           Coil Voltage         24VAC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         15A           Switching Voltage         120VAC - Max           Turn On Voltage (Max)         19.2 VAC           Turn Off Voltage (Min)         7.2 VAC           Operate Time         20ms           Release Time         20ms           Features         Insulation - Class F           Mounting Type         Through Hole           Termination Style         PC Pin	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package         -           Series         PCLH, OEG           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         -           Coil Voltage         24VAC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         15A           Switching Voltage         120VAC - Max           Turn On Voltage (Max)         19.2 VAC           Turn Off Voltage (Min)         7.2 VAC           Operate Time         20ms           Release Time         20ms           Features         Insulation - Class F           Mounting Type         Through Hole           Termination Style         PC Pin	Category	Relays
SeriesPCLH, OEGRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage24VACContact FormDPDT (2 Form C)Contact Rating (Current)15ASwitching Voltage120VAC - MaxTurn On Voltage (Max)19.2 VACTurn Off Voltage (Min)7.2 VACOperate Time20msRelease Time20msFeaturesInsulation - Class FMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage24VACContact FormDPDT (2 Form C)Contact Rating (Current)15ASwitching Voltage120VAC - MaxTurn On Voltage (Max)19.2 VACTurn Off Voltage (Min)7.2 VACOperate Time20msRelease Time20msFeaturesInsulation - Class FMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type Non Latching Coil Current - Coil Voltage 24VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 15A Switching Voltage 120VAC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time 20ms Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin	Series	PCLH, OEG
Coil Current Coil Voltage 24VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 15A Switching Voltage 120VAC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time 20ms Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage24VACContact FormDPDT (2 Form C)Contact Rating (Current)15ASwitching Voltage120VAC - MaxTurn On Voltage (Max)19.2 VACTurn Off Voltage (Min)7.2 VACOperate Time20msRelease Time20msFeaturesInsulation - Class FMounting TypeThrough HoleTermination StylePC Pin	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current)  15A  Switching Voltage  120VAC - Max  Turn On Voltage (Max)  19.2 VAC  Turn Off Voltage (Min)  7.2 VAC  Operate Time  20ms  Release Time  20ms  Release Time  Insulation - Class F  Mounting Type  Through Hole  Termination Style	Coil Current	-
Contact Rating (Current)  Switching Voltage  120VAC - Max  19.2 VAC  Turn On Voltage (Max)  7.2 VAC  Operate Time  20ms  Release Time  20ms  Features  Insulation - Class F  Mounting Type  Through Hole  Termination Style	Coil Voltage	24VAC
Switching Voltage 120VAC - Max  Turn On Voltage (Max) 19.2 VAC  Turn Off Voltage (Min) 7.2 VAC  Operate Time 20ms  Release Time 20ms  Features Insulation - Class F  Mounting Type Through Hole  Termination Style PC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  19.2 VAC  Turn Off Voltage (Min)  7.2 VAC  Operate Time  20ms  Release Time  20ms  Features  Insulation - Class F  Mounting Type  Through Hole  Termination Style  PC Pin	Contact Rating (Current)	15A
Turn Off Voltage (Min) 7.2 VAC  Operate Time 20ms  Release Time 20ms  Features Insulation - Class F  Mounting Type Through Hole  Termination Style PC Pin	Switching Voltage	120VAC - Max
Operate Time20msRelease Time20msFeaturesInsulation - Class FMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	19.2 VAC
Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	7.2 VAC
Features Insulation - Class F  Mounting Type Through Hole  Termination Style PC Pin	Operate Time	20ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	20ms
Termination Style PC Pin	Features	Insulation - Class F
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

### PCLH-203A1SP,000 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### PCLH-203A1SP,000 Payment Methods



















### PCLH-203A1SP,000 Shipping Methods













If you have any question about PCLH-203A1SP,000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com