



### PDA040B-48VB Information

Heisener.com

Part Number PDA040B-48VB Manufacturer Phihong USA

Category Power Supplies - External/Internal (Off-Board)

**LED Drivers** 

**Description** LED DRIVER CV AC/DC 48V 830MA

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## PDA040B-48VB Specifications

Manufacturer Phihong USA Category Power Supplies - External/Internal (Off-Board) LED Drivers  Package - Series PDA Type Constant Voltage Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 120VAC Voltage - Input (Max) 277VAC Voltage - Output 48V Current - Output (Max) 830mA Power (Watts) 40W Voltage - Isolation 3kV (3000V) Dimming - Features OCP, OVP, SCP Ratings IP67 Operating Temperature 40°C ~ 70°C Efficiency 87% Termination Style Wire Leads		
Category         Power Supplies - External/Internal (Off-Board)           LED Drivers           Package         -           Series         PDA           Type         Constant Voltage           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         120VAC           Voltage - Input (Max)         277VAC           Voltage - Output         48V           Current - Output (Max)         830mA           Power (Watts)         40W           Voltage - Isolation         3kV (3000V)           Dimming         -           Features         OCP, OVP, SCP           Ratings         IP67           Operating Temperature         -40°C ~ 70°C           Efficiency         87%           Termination Style         Wire Leads           Size / Dimension         6.48" L x 1.69" W x 1.26" H (164.5mm x 43.0mm x 32.0mm)	Manufacturer Part Number	PDA040B-48VB
LED Drivers           Package         -           Series         PDA           Type         Constant Voltage           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         120VAC           Voltage - Input (Max)         277VAC           Voltage - Output         48V           Current - Output (Max)         830mA           Power (Watts)         40W           Voltage - Isolation         3kV (3000V)           Dimming         -           Features         OCP, OVP, SCP           Ratings         IP67           Operating Temperature         -40°C ~ 70°C           Efficiency         87%           Termination Style         Wire Leads           Size / Dimension         6.48" L x 1.69" W x 1.26" H (164.5mm x 43.0mm x 32.0mm)	Manufacturer	Phihong USA
Package         -           Series         PDA           Type         Constant Voltage           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         120VAC           Voltage - Input (Max)         277VAC           Voltage - Output         48V           Current - Output (Max)         830mA           Power (Watts)         40W           Voltage - Isolation         3kV (3000V)           Dimming         -           Features         OCP, OVP, SCP           Ratings         IP67           Operating Temperature         -40°C ~ 70°C           Efficiency         87%           Termination Style         Wire Leads           Size / Dimension         6.48" L x 1.69" W x 1.26" H (164.5mm x 43.0mm x 32.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         PDA           Type         Constant Voltage           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         120VAC           Voltage - Output (Max)         277VAC           Voltage - Output (Max)         830mA           Power (Watts)         40W           Voltage - Isolation         3kV (3000V)           Dimming         -           Features         OCP, OVP, SCP           Ratings         IP67           Operating Temperature         -40°C ~ 70°C           Efficiency         87%           Termination Style         Wire Leads           Size / Dimension         6.48" L x 1.69" W x 1.26" H (164.5mm x 43.0mm x 32.0mm)		LED Drivers
Type         Constant Voltage           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         120VAC           Voltage - Output (Max)         277VAC           Voltage - Output (Max)         830mA           Power (Watts)         40W           Voltage - Isolation         3kV (3000V)           Dimming         -           Features         OCP, OVP, SCP           Ratings         IP67           Operating Temperature         -40°C ~ 70°C           Efficiency         87%           Termination Style         Wire Leads           Size / Dimension         6.48" L x 1.69" W x 1.26" H (164.5mm x 43.0mm x 32.0mm)	Package	-
Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         120VAC           Voltage - Input (Max)         277VAC           Voltage - Output         48V           Current - Output (Max)         830mA           Power (Watts)         40W           Voltage - Isolation         3kV (3000V)           Dimming         -           Features         OCP, OVP, SCP           Ratings         IP67           Operating Temperature         -40°C ~ 70°C           Efficiency         87%           Termination Style         Wire Leads           Size / Dimension         6.48" L x 1.69" W x 1.26" H (164.5mm x 43.0mm x 32.0mm)	Series	PDA
Number of Outputs       1         Voltage - Input (Min)       120VAC         Voltage - Input (Max)       277VAC         Voltage - Output       48V         Current - Output (Max)       830mA         Power (Watts)       40W         Voltage - Isolation       3kV (3000V)         Dimming       -         Features       OCP, OVP, SCP         Ratings       IP67         Operating Temperature       -40°C ~ 70°C         Efficiency       87%         Termination Style       Wire Leads         Size / Dimension       6.48" L x 1.69" W x 1.26" H (164.5mm x 43.0mm x 32.0mm)	Туре	Constant Voltage
Voltage - Input (Min)       120VAC         Voltage - Output       48V         Current - Output (Max)       830mA         Power (Watts)       40W         Voltage - Isolation       3kV (3000V)         Dimming       -         Features       OCP, OVP, SCP         Ratings       IP67         Operating Temperature       -40°C ~ 70°C         Efficiency       87%         Termination Style       Wire Leads         Size / Dimension       6.48" L x 1.69" W x 1.26" H (164.5mm x 43.0mm x 32.0mm)	Topology	AC DC Converter
Voltage - Input (Max)       277VAC         Voltage - Output       48V         Current - Output (Max)       830mA         Power (Watts)       40W         Voltage - Isolation       3kV (3000V)         Dimming       -         Features       OCP, OVP, SCP         Ratings       IP67         Operating Temperature       -40°C ~ 70°C         Efficiency       87%         Termination Style       Wire Leads         Size / Dimension       6.48" L x 1.69" W x 1.26" H (164.5mm x 43.0mm x 32.0mm)	Number of Outputs	1
Voltage - Output       48V         Current - Output (Max)       830mA         Power (Watts)       40W         Voltage - Isolation       3kV (3000V)         Dimming       -         Features       OCP, OVP, SCP         Ratings       IP67         Operating Temperature       -40°C ~ 70°C         Efficiency       87%         Termination Style       Wire Leads         Size / Dimension       6.48" L x 1.69" W x 1.26" H (164.5mm x 43.0mm x 32.0mm)	Voltage - Input (Min)	120VAC
Current - Output (Max)       830mA         Power (Watts)       40W         Voltage - Isolation       3kV (3000V)         Dimming       -         Features       OCP, OVP, SCP         Ratings       IP67         Operating Temperature       -40°C ~ 70°C         Efficiency       87%         Termination Style       Wire Leads         Size / Dimension       6.48" L x 1.69" W x 1.26" H (164.5mm x 43.0mm x 32.0mm)	Voltage - Input (Max)	277VAC
Power (Watts)       40W         Voltage - Isolation       3kV (3000V)         Dimming       -         Features       OCP, OVP, SCP         Ratings       IP67         Operating Temperature       -40°C ~ 70°C         Efficiency       87%         Termination Style       Wire Leads         Size / Dimension       6.48" L x 1.69" W x 1.26" H (164.5mm x 43.0mm x 32.0mm)	Voltage - Output	48V
Voltage - Isolation 3kV (3000V)  Dimming -  Features OCP, OVP, SCP  Ratings IP67 Operating Temperature -40°C ~ 70°C  Efficiency 87%  Termination Style Wire Leads  Size / Dimension 6.48" L x 1.69" W x 1.26" H (164.5mm x 43.0mm x 32.0mm)	Current - Output (Max)	830mA
Dimming  Features  OCP, OVP, SCP  Ratings  IP67  Operating Temperature  -40°C ~ 70°C  Efficiency  87%  Termination Style  Size / Dimension  -48" L x 1.69" W x 1.26" H (164.5mm x 43.0mm x 32.0mm)	Power (Watts)	40W
Features OCP, OVP, SCP  Ratings IP67  Operating Temperature -40°C ~ 70°C  Efficiency 87%  Termination Style Wire Leads  Size / Dimension 6.48" L x 1.69" W x 1.26" H (164.5mm x 43.0mm x 32.0mm)	Voltage - Isolation	3kV (3000V)
Ratings IP67 Operating Temperature -40°C ~ 70°C Efficiency 87% Termination Style Wire Leads Size / Dimension 6.48" L x 1.69" W x 1.26" H (164.5mm x 43.0mm x 32.0mm)	Dimming	-
Operating Temperature -40°C ~ 70°C  Efficiency 87%  Termination Style Wire Leads  Size / Dimension 6.48" L x 1.69" W x 1.26" H (164.5mm x 43.0mm x 32.0mm)	Features	OCP, OVP, SCP
Efficiency 87% Termination Style Wire Leads Size / Dimension 6.48" L x 1.69" W x 1.26" H (164.5mm x 43.0mm x 32.0mm)	Ratings	IP67
Termination Style Wire Leads Size / Dimension 6.48" L x 1.69" W x 1.26" H (164.5mm x 43.0mm x 32.0mm)	Operating Temperature	-40°C ~ 70°C
Size / Dimension 6.48" L x 1.69" W x 1.26" H (164.5mm x 43.0mm x 32.0mm)	Efficiency	87%
· · · · · · · · · · · · · · · · · · ·	Termination Style	Wire Leads
Report errors?	Size / Dimension	6.48" L x 1.69" W x 1.26" H (164.5mm x 43.0mm x 32.0mm)
		Report errors?

#### PDA040B-48VB Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### PDA040B-48VB Payment Methods



















### PDA040B-48VB Shipping Methods













If you have any question about PDA040B-48VB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com