

## PDA080W-1A0G Information

Heisener.com

Part Number PDA080W-1A0G Manufacturer Phihong USA

Category Power Supplies - External/Internal (Off-Board)

**LED Drivers** 

**Description** LED DRIVER CC AC/DC 50-76V 1A

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# PDA080W-1A0G Specifications

Manufacturer Part Number         PDA080W-1A0G           Manufacturer         Phihong USA           Category         Power Supplies - External/Internal (Off-Board)           LED Drivers           Package         -           Series         PDA           Type         Constant Current           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Input (Max)         304VAC           Voltage - Output         50 ~ 76 V           Current - Output (Max)         1A           Power (Watts)         80W           Voltage - Isolation         4.242kV (4242V)           Dimming         Analog           Features         OCP, OVP, SCP           Ratings         IP67           Operating Temperature         40°C ~ 60°C           Efficiency         85%           Termination Style         Wire Leads           Size / Dimension         8.39" L x 1.71" W x 1.20" H (213.2mm x 43.5mm x 30.5mm)			
Category         Power Supplies - External/Internal (Off-Board)           LED Drivers           Package         -           Series         PDA           Type         Constant Current           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Output (Max)         304VAC           Voltage - Output (Max)         1A           Power (Watts)         80W           Voltage - Isolation         4.242kV (4242V)           Dimming         Analog           Features         OCP, OVP, SCP           Ratings         IP67           Operating Temperature         -40°C ~ 60°C           Efficiency         85%           Termination Style         Wire Leads           Size / Dimension         8.39" L x 1.71" W x 1.20" H (213.2mm x 43.5mm x 30.5mm)	Manufacturer Part Number	PDA080W-1A0G	
Package         -           Series         PDA           Type         Constant Current           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Output (Max)         304VAC           Voltage - Output (Max)         1A           Power (Watts)         80W           Voltage - Isolation         4.242kV (4242V)           Dimming         Analog           Features         OCP, OVP, SCP           Ratings         IP67           Operating Temperature         -40°C ~ 60°C           Efficiency         85%           Termination Style         Wire Leads           Size / Dimension         8.39" L x 1.71" W x 1.20" H (213.2mm x 43.5mm x 30.5mm)	Manufacturer	Phihong USA	
Package         -           Series         PDA           Type         Constant Current           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Input (Max)         304VAC           Voltage - Output         50 ~ 76 V           Current - Output (Max)         1A           Power (Watts)         80W           Voltage - Isolation         4.242kV (4242V)           Dimming         Analog           Features         OCP, OVP, SCP           Ratings         IP67           Operating Temperature         -40°C ~ 60°C           Efficiency         85%           Termination Style         Wire Leads           Size / Dimension         8.39" L x 1.71" W x 1.20" H (213.2mm x 43.5mm x 30.5mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series         PDA           Type         Constant Current           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Input (Max)         304VAC           Voltage - Output         50 ~ 76 V           Current - Output (Max)         1A           Power (Watts)         80W           Voltage - Isolation         4.242kV (4242V)           Dimming         Analog           Features         OCP, OVP, SCP           Ratings         IP67           Operating Temperature         -40°C ~ 60°C           Efficiency         85%           Termination Style         Wire Leads           Size / Dimension         8.39" L x 1.71" W x 1.20" H (213.2mm x 43.5mm x 30.5mm)		LED Drivers	
Type         Constant Current           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Input (Max)         304VAC           Voltage - Output         50 ~ 76 V           Current - Output (Max)         1A           Power (Watts)         80W           Voltage - Isolation         4.242kV (4242V)           Dimming         Analog           Features         OCP, OVP, SCP           Ratings         IP67           Operating Temperature         -40°C ~ 60°C           Efficiency         85%           Termination Style         Wire Leads           Size / Dimension         8.39" L x 1.71" W x 1.20" H (213.2mm x 43.5mm x 30.5mm)	Package	-	
Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Output         50 ~ 76 V           Current - Output (Max)         1A           Power (Watts)         80W           Voltage - Isolation         4.242kV (4242V)           Dimming         Analog           Features         OCP, OVP, SCP           Ratings         IP67           Operating Temperature         -40°C ~ 60°C           Efficiency         85%           Termination Style         Wire Leads           Size / Dimension         8.39" L x 1.71" W x 1.20" H (213.2mm x 43.5mm x 30.5mm)	Series	PDA	
Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Input (Max)         304VAC           Voltage - Output         50 ~ 76 V           Current - Output (Max)         1A           Power (Watts)         80W           Voltage - Isolation         4.242kV (4242V)           Dimming         Analog           Features         OCP, OVP, SCP           Ratings         IP67           Operating Temperature         -40°C ~ 60°C           Efficiency         85%           Termination Style         Wire Leads           Size / Dimension         8.39" L x 1.71" W x 1.20" H (213.2mm x 43.5mm x 30.5mm)	Туре	Constant Current	
Voltage - Input (Min)         90VAC           Voltage - Input (Max)         304VAC           Voltage - Output         50 ~ 76 V           Current - Output (Max)         1A           Power (Watts)         80W           Voltage - Isolation         4.242kV (4242V)           Dimming         Analog           Features         OCP, OVP, SCP           Ratings         IP67           Operating Temperature         -40°C ~ 60°C           Efficiency         85%           Termination Style         Wire Leads           Size / Dimension         8.39" L x 1.71" W x 1.20" H (213.2mm x 43.5mm x 30.5mm)	Topology	AC DC Converter	
Voltage - Input (Max) $304\text{VAC}$ Voltage - Output $50 \sim 76 \text{ V}$ Current - Output (Max) $1A$ Power (Watts) $80\text{W}$ Voltage - Isolation $4.242\text{kV} (4242\text{V})$ DimmingAnalogFeaturesOCP, OVP, SCPRatingsIP67Operating Temperature $-40^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Efficiency $85\%$ Termination StyleWire LeadsSize / Dimension $8.39^{\circ}\text{L} \times 1.71^{\circ}\text{W} \times 1.20^{\circ}\text{H} (213.2\text{mm} \times 43.5\text{mm} \times 30.5\text{mm})$	Number of Outputs	1	
Voltage - Output       50 ~ 76 V         Current - Output (Max)       1A         Power (Watts)       80W         Voltage - Isolation       4.242kV (4242V)         Dimming       Analog         Features       OCP, OVP, SCP         Ratings       IP67         Operating Temperature       -40°C ~ 60°C         Efficiency       85%         Termination Style       Wire Leads         Size / Dimension       8.39" L x 1.71" W x 1.20" H (213.2mm x 43.5mm x 30.5mm)	Voltage - Input (Min)	90VAC	
Current - Output (Max)  Power (Watts)  80W  Voltage - Isolation  4.242kV (4242V)  Dimming  Analog  Features  OCP, OVP, SCP  Ratings  IP67  Operating Temperature  -40°C ~ 60°C  Efficiency  85%  Termination Style  Wire Leads  Size / Dimension  1A  80W	Voltage - Input (Max)	304VAC	
Power (Watts) $80W$ Voltage - Isolation $4.242kV$ ( $4242V$ )DimmingAnalogFeaturesOCP, OVP, SCPRatingsIP67Operating Temperature $-40^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Efficiency $85\%$ Termination StyleWire LeadsSize / Dimension $8.39$ " L x $1.71$ " W x $1.20$ " H ( $213.2\text{mm}$ x $43.5\text{mm}$ x $30.5\text{mm}$ )	Voltage - Output	50 ~ 76 V	
Voltage - Isolation4.242kV (4242V)DimmingAnalogFeaturesOCP, OVP, SCPRatingsIP67Operating Temperature-40°C ~ 60°CEfficiency85%Termination StyleWire LeadsSize / Dimension8.39" L x 1.71" W x 1.20" H (213.2mm x 43.5mm x 30.5mm)	Current - Output (Max)	1A	
$\begin{array}{llllllllllllllllllllllllllllllllllll$	Power (Watts)	80W	
FeaturesOCP, OVP, SCPRatingsIP67Operating Temperature $-40^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Efficiency $85\%$ Termination StyleWire LeadsSize / Dimension $8.39^{\circ}\text{L x 1.71^{\circ} W x 1.20^{\circ} H (213.2mm x 43.5mm x 30.5mm)}$	Voltage - Isolation	4.242kV (4242V)	
Ratings IP67  Operating Temperature $-40^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Efficiency 85%  Termination Style Wire Leads  Size / Dimension 8.39" L x 1.71" W x 1.20" H (213.2mm x 43.5mm x 30.5mm)	Dimming	Analog	
Operating Temperature $-40^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Efficiency 85%  Termination Style Wire Leads  Size / Dimension 8.39" L x 1.71" W x 1.20" H (213.2mm x 43.5mm x 30.5mm)	Features	OCP, OVP, SCP	
Efficiency 85% Termination Style Wire Leads Size / Dimension 8.39" L x 1.71" W x 1.20" H (213.2mm x 43.5mm x 30.5mm)	Ratings	IP67	
Termination Style Wire Leads Size / Dimension 8.39" L x 1.71" W x 1.20" H (213.2mm x 43.5mm x 30.5mm)	Operating Temperature	-40°C ~ 60°C	
Size / Dimension 8.39" L x 1.71" W x 1.20" H (213.2mm x 43.5mm x 30.5mm)	Efficiency	85%	
	Termination Style	Wire Leads	
Report errors?	Size / Dimension	8.39" L x 1.71" W x 1.20" H (213.2mm x 43.5mm x 30.5mm)	
			Report errors?

#### PDA080W-1A0G Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### PDA080W-1A0G Payment Methods



















## PDA080W-1A0G Shipping Methods













If you have any question about PDA080W-1A0G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com