

PDC500-1024F Information

Heisener.com

Part Number PDC500-1024F
Manufacturer Bel Power Solutions

Category Power Supplies - External/Internal (Off-Board)

DC DC Converters

Description DC/DC CONVERT 24V 21A

Package Module

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PDC500-1024F Specifications

Manufacturer Part Number PDC500-1024F Manufacturer Bel Power Solutions Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series PDC500 Type Isolated Voltage - Input (Min) 36V Voltage - Input (Max) 75V Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 21A Power (Watts) 500W Applications ITE (Commercial) Operating Temperature 0°C ~ 50°C Efficiency 75% Mounting Type Rack Mount Package / Case Module Size / Dimension 9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm) Report errors?		
Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series PDC500 Type Isolated Voltage - Input (Min) 36V Voltage - Input (Max) 75V Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 21A Power (Watts) 500W Applications ITE (Commercial) Operating Temperature 0°C ~ 50°C Efficiency 75% Mounting Type Rack Mount Package / Case Module Size / Dimension 9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Manufacturer Part Number	PDC500-1024F
Package Module Series PDC500 Type Isolated Voltage - Input (Min) 36V Voltage - Input (Max) 75V Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 21A Power (Watts) 500W Applications ITE (Commercial) Operating Temperature 0°C ~ 50°C Efficiency 75% Mounting Type Rack Mount Package / Case Module Size / Dimension 9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Manufacturer	Bel Power Solutions
Package Module Series PDC500 Type Isolated Voltage - Input (Min) 36V Voltage - Input (Max) 75V Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 21A Power (Watts) 500W Applications ITE (Commercial) Operating Temperature 0°C ~ 50°C Efficiency 75% Mounting Type Rack Mount Package / Case Module Size / Dimension 9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Category	Power Supplies - External/Internal (Off-Board)
Series PDC500 Type Isolated Voltage - Input (Min) 36V Voltage - Input (Max) 75V Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 21A Power (Watts) 500W Applications ITE (Commercial) Operating Temperature 0°C ~ 50°C Efficiency 75% Mounting Type Rack Mount Package / Case Module Size / Dimension 9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)		DC DC Converters
Type Isolated Voltage - Input (Min) 36V Voltage - Input (Max) 75V Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 21A Power (Watts) 500W Applications ITE (Commercial) Operating Temperature 0°C ~ 50°C Efficiency 75% Mounting Type Rack Mount Package / Case Module Size / Dimension 9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Package	Module
Voltage - Input (Min) 36V Voltage - Input (Max) 75V Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 21A Power (Watts) 500W Applications ITE (Commercial) Operating Temperature 0°C ~ 50°C Efficiency 75% Mounting Type Rack Mount Package / Case Module Size / Dimension 9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Series	PDC500
Voltage - Input (Max) 75 V Number of Outputs 1 Voltage - Output 1 24 V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 21 A Power (Watts) 500 W Applications ITE (Commercial) Operating Temperature 0°C ~ 50°C Efficiency 75% Mounting Type Rack Mount Package / Case Module Size / Dimension 9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Туре	Isolated
Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 21A Power (Watts) 500W Applications ITE (Commercial) Operating Temperature 0°C ~ 50°C Efficiency 75% Mounting Type Rack Mount Package / Case Module Size / Dimension 9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Voltage - Input (Min)	36V
Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 21A Power (Watts) 500W Applications ITE (Commercial) Operating Temperature 0°C ~ 50°C Efficiency 75% Mounting Type Rack Mount Package / Case Module Size / Dimension 9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Voltage - Input (Max)	75V
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 21A Power (Watts) 500W Applications ITE (Commercial) Operating Temperature 0°C ~ 50°C Efficiency 75% Mounting Type Rack Mount Package / Case Module Size / Dimension 9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Number of Outputs	1
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications Operating Temperature Efficiency Mounting Type Rack Mount Package / Case Module Size / Dimension - Output (Max) - Current -	Voltage - Output 1	24V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Operating Temperature 0°C ~ 50°C Efficiency 75% Mounting Type Rack Mount Package / Case Module Size / Dimension - Output (Max) 21A - Output (Max) 500W Rack Mount - Output (Max) 500W Rack Mount - Output (Max) 500W Rack Mount - Output (Max) 500W - Output (Max) - Output (Max) 500W - Output (Max) - Output (M	Voltage - Output 2	-
Current - Output (Max) Power (Watts) Applications Operating Temperature O°C ~ 50°C Efficiency Mounting Type Rack Mount Package / Case Module Size / Dimension 21A 20W Mounting Type Rack Mount 9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Voltage - Output 3	-
Power (Watts) 500W Applications ITE (Commercial) Operating Temperature 0°C ~ 50°C Efficiency 75% Mounting Type Rack Mount Package / Case Module Size / Dimension 9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Voltage - Output 4	-
Applications ITE (Commercial) Operating Temperature 0°C ~ 50°C Efficiency 75% Mounting Type Rack Mount Package / Case Module Size / Dimension 9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Current - Output (Max)	21A
Operating Temperature 0°C ~ 50°C Efficiency 75% Mounting Type Rack Mount Package / Case Module Size / Dimension 9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Power (Watts)	500W
Efficiency 75% Mounting Type Rack Mount Package / Case Module Size / Dimension 9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Applications	
Mounting Type Rack Mount Package / Case Module Size / Dimension 9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Operating Temperature	0°C ~ 50°C
Package / Case Module Size / Dimension 9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Efficiency	75%
Size / Dimension 9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Mounting Type	Rack Mount
	Package / Case	Module
Report errors?	Size / Dimension	9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)
		Report errors?

PDC500-1024F Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PDC500-1024F Payment Methods



















PDC500-1024F Shipping Methods













If you have any question about PDC500-1024F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com