



### PES.1F.308.XLC Information

Heisener.com

Part Number PES.1F.308.XLC

Manufacturer LEMO

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PNL MNT RCPT 8PIN CRIMP

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# PES.1F.308.XLC Specifications

Manufacturer Part Number       PES.1F.308.XLC         Manufacturer       LEMO         Category       Connectors, Interconnects         Package       -         Series       1F         Connector Type       Receptacle, Male Pins         Number of Positions       8         Shell Size - Insert       308         Shell Size, MIL       -         Mounting Type       Panel Mount, Flange - Front Side Nut         Termination       Crimp         Fastening Type       Push-Pull, Detent Lock         Orientation       S         Ingress Protection       IP67 - Dust Tight, Waterproof         Shell Material, Finish       Aluminum Alloy, Nickel Plated         Contact Finish       Gold         Features       Backshell, Shielded         Voltage - Rated       -         Current Rating       5A		
CategoryConnectors, InterconnectsPackage-Series1FConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert308Shell Size, MIL-Mounting TypePanel Mount, Flange - Front Side NutTerminationCrimpFastening TypePush-Pull, Detent LockOrientationSIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating5A	Manufacturer Part Number	PES.1F.308.XLC
Package-Series1FConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert308Shell Size, MIL-Mounting TypePanel Mount, Flange - Front Side NutTerminationCrimpFastening TypePush-Pull, Detent LockOrientationSIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating5A	Manufacturer	LEMO
Package-Series1FConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert308Shell Size, MIL-Mounting TypePanel Mount, Flange - Front Side NutTerminationCrimpFastening TypePush-Pull, Detent LockOrientationSIngress Protection1P67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating5A	Category	Connectors, Interconnects
Series1FConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert308Shell Size, MIL-Mounting TypePanel Mount, Flange - Front Side NutTerminationCrimpFastening TypePush-Pull, Detent LockOrientationSIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating5A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert308Shell Size, MIL-Mounting TypePanel Mount, Flange - Front Side NutTerminationCrimpFastening TypePush-Pull, Detent LockOrientationSIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating5A	Package	-
Number of Positions8Shell Size - Insert308Shell Size, MIL-Mounting TypePanel Mount, Flange - Front Side NutTerminationCrimpFastening TypePush-Pull, Detent LockOrientationSIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating5A	Series	1F
Shell Size - Insert308Shell Size, MIL-Mounting TypePanel Mount, Flange - Front Side NutTerminationCrimpFastening TypePush-Pull, Detent LockOrientationSIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating5A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Flange - Front Side Nut  Termination Crimp Fastening Type Push-Pull, Detent Lock Orientation S Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Gold Features Backshell, Shielded  Voltage - Rated Current Rating 5A	Number of Positions	8
Mounting TypePanel Mount, Flange - Front Side NutTerminationCrimpFastening TypePush-Pull, Detent LockOrientationSIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating5A	Shell Size - Insert	308
Termination Crimp Fastening Type Push-Pull, Detent Lock Orientation S Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated Current Rating 5A	Shell Size, MIL	-
Fastening Type Push-Pull, Detent Lock Orientation S Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated - Current Rating 5A	Mounting Type	Panel Mount, Flange - Front Side Nut
Orientation S Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated Current Rating 5A	Termination	Crimp
Ingress Protection  IP67 - Dust Tight, Waterproof  Shell Material, Finish  Aluminum Alloy, Nickel Plated  Contact Finish  Gold  Features  Backshell, Shielded  Voltage - Rated  - Current Rating  5A	Fastening Type	Push-Pull, Detent Lock
Shell Material, Finish  Contact Finish  Gold  Features  Backshell, Shielded  Voltage - Rated  Current Rating  5A	Orientation	S
Contact Finish Gold Features Backshell, Shielded  Voltage - Rated - Current Rating 5A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Backshell, Shielded  Voltage - Rated - Current Rating 5A	Shell Material, Finish	Aluminum Alloy, Nickel Plated
Voltage - Rated - Current Rating 5A	Contact Finish	Gold
Current Rating 5A	Features	Backshell, Shielded
	Voltage - Rated	-
Report errors?	Current Rating	5A
		Report errors?

#### PES.1F.308.XLC Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### PES.1F.308.XLC Payment Methods



















## PES.1F.308.XLC Shipping Methods













If you have any question about PES.1F.308.XLC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com