

## PF1000A-360 Information



For Reference Only

Part Number PF1000A-360

Manufacturer TDK-Lambda Americas Inc.

Category Power Supplies - Board Mount

AC DC Converters

**Description** PWR CORRECTION MOD 360VDC

Package 10-DIP Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# PF1000A-360 Specifications

Manufacturer Part Number         PF1000A-360           Manufacturer         TDK-Lambda Americas Inc.           Category         Power Supplies - Board Mount           AC DC Converters           Package         10-DIP Module           Series         PF           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         360V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         2.8A           Power (Watts)         1000W           Applications         ITE (Commercial)           Features         OCP, OTP, OVP           Operating Temperature         -40°C ~ 100°C (With Derating)           Efficiency         95%           Mounting Type         Through Hole           Package / Case         10-DIP Module           Size / Dimension         4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)           Report errors?			
Category         Power Supplies - Board Mount           AC DC Converters           Package         10-DIP Module           Series         PF           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         360V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output (Max)         2.8A           Power (Watts)         1000W           Applications         ITE (Commercial)           Features         OCP, OTP, OVP           Operating Temperature         -40°C ~ 100°C (With Derating)           Efficiency         95%           Mounting Type         Through Hole           Package / Case         10-DIP Module           Size / Dimension         4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	Manufacturer Part Number	PF1000A-360	
Package         10-DIP Module           Series         PF           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         360V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         2.8A           Power (Watts)         1000W           Applications         ITE (Commercial)           Features         OCP, OTP, OVP           Operating Temperature         -40°C ~ 100°C (With Derating)           Efficiency         95%           Mounting Type         Through Hole           Package / Case         10-DIP Module           Size / Dimension         4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	Manufacturer	TDK-Lambda Americas Inc.	
Package         10-DIP Module           Series         PF           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         360V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         2.8A           Power (Watts)         1000W           Applications         ITE (Commercial)           Features         OCP, OTP, OVP           Operating Temperature         -40°C ~ 100°C (With Derating)           Efficiency         95%           Mounting Type         Through Hole           Package / Case         10-DIP Module           Size / Dimension         4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	Category	Power Supplies - Board Mount	
Series         PF           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         360V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         2.8A           Power (Watts)         1000W           Applications         ITE (Commercial)           Features         OCP, OTP, OVP           Operating Temperature         -40°C ~ 100°C (With Derating)           Efficiency         95%           Mounting Type         Through Hole           Package / Case         10-DIP Module           Size / Dimension         4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)		AC DC Converters	
Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         360V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         2.8A           Power (Watts)         1000W           Applications         ITE (Commercial)           Features         OCP, OTP, OVP           Operating Temperature         -40°C ~ 100°C (With Derating)           Efficiency         95%           Mounting Type         Through Hole           Package / Case         10-DIP Module           Size / Dimension         4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	Package	10-DIP Module	
Number of Outputs       1         Voltage - Input       85 ~ 265 VAC         Voltage - Output 1       360V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       2.8A         Power (Watts)       1000W         Applications       ITE (Commercial)         Features       OCP, OTP, OVP         Operating Temperature       -40°C ~ 100°C (With Derating)         Efficiency       95%         Mounting Type       Through Hole         Package / Case       10-DIP Module         Size / Dimension       4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	Series	PF	
Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         360V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         2.8A           Power (Watts)         1000W           Applications         ITE (Commercial)           Features         OCP, OTP, OVP           Operating Temperature         -40°C ~ 100°C (With Derating)           Efficiency         95%           Mounting Type         Through Hole           Package / Case         10-DIP Module           Size / Dimension         4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	Type	Enclosed	
Voltage - Output 1         360V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         2.8A           Power (Watts)         1000W           Applications         ITE (Commercial)           Features         OCP, OTP, OVP           Operating Temperature         -40°C ~ 100°C (With Derating)           Efficiency         95%           Mounting Type         Through Hole           Package / Case         10-DIP Module           Size / Dimension         4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	Number of Outputs	1	
Voltage - Output 2  Voltage - Output 3  - Voltage - Output 4  - Current - Output (Max)  Applications  Features  OCP, OTP, OVP  Operating Temperature  Efficiency  Mounting Type  Through Hole  Package / Case  Size / Dimension  - Voltage - Output 2  - Current - Output (Max)  - Cur	Voltage - Input	85 ~ 265 VAC	
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Features  OCP, OTP, OVP  Operating Temperature  -40°C ~ 100°C (With Derating)  Efficiency  Mounting Type  Through Hole  Package / Case  10-DIP Module  Size / Dimension  - Output 4  - Case  - Case  10-DIP Module  4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	Voltage - Output 1	360V	
Voltage - Output 4  Current - Output (Max)  2.8A  Power (Watts)  Applications  ITE (Commercial)  Features  OCP, OTP, OVP  Operating Temperature  -40°C ~ 100°C (With Derating)  Efficiency  95%  Mounting Type  Through Hole  Package / Case  10-DIP Module  Size / Dimension  -4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	Voltage - Output 2	-	
Current - Output (Max)  2.8A  Power (Watts)  1000W  Applications  ITE (Commercial)  Features  OCP, OTP, OVP  Operating Temperature  -40°C ~ 100°C (With Derating)  Efficiency  95%  Mounting Type  Through Hole  Package / Case  10-DIP Module  Size / Dimension  2.8A  2.8A  1000W  THE (Commercial)  1000W  1000 C (With Derating)	Voltage - Output 3	-	
Power (Watts)  Applications  ITE (Commercial)  Features  OCP, OTP, OVP  Operating Temperature  -40°C ~ 100°C (With Derating)  Efficiency  95%  Mounting Type  Through Hole  Package / Case  10-DIP Module  Size / Dimension  1000W  ITE (Commercial)  OCP, OTP, OVP  -40°C ~ 100°C (With Derating)	Voltage - Output 4	-	
Applications ITE (Commercial)  Features OCP, OTP, OVP  Operating Temperature -40°C ~ 100°C (With Derating)  Efficiency 95%  Mounting Type Through Hole  Package / Case 10-DIP Module  Size / Dimension 4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	Current - Output (Max)	2.8A	
Features OCP, OTP, OVP Operating Temperature -40°C ~ 100°C (With Derating)  Efficiency 95%  Mounting Type Through Hole Package / Case 10-DIP Module  Size / Dimension 4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	Power (Watts)	1000W	
Operating Temperature -40°C ~ 100°C (With Derating)  Efficiency 95%  Mounting Type Through Hole  Package / Case 10-DIP Module  Size / Dimension 4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	Applications	ITE (Commercial)	
Efficiency 95%  Mounting Type Through Hole  Package / Case 10-DIP Module  Size / Dimension 4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	Features	OCP, OTP, OVP	
Mounting Type Through Hole Package / Case 10-DIP Module Size / Dimension 4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	Operating Temperature	$-40^{\circ}$ C ~ $100^{\circ}$ C (With Derating)	
Package / Case         10-DIP Module           Size / Dimension         4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	Efficiency	95%	
Size / Dimension 4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	Mounting Type	Through Hole	
	Package / Case	10-DIP Module	
Report errors?	Size / Dimension	4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	
			Report errors?

### PF1000A-360 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### PF1000A-360 Payment Methods



















### PF1000A-360 Shipping Methods













If you have any question about PF1000A-360, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com