



PF175B480T033FP-00 Information



For Reference Only

Part Number PF175B480T033FP-00 **Manufacturer** Vicor Corporation

Category Power Supplies - Board Mount

AC DC Converters

Description AC/DC CONVERT 48V 10.2A

Package 14-DIP Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PF175B480T033FP-00 Specifications

| Manufacturer Part Number PF175B480T033FP-00 Manufacturer Vicor Corporation Category Power Supplies - Board Mount AC DC Converters Package 14-DIP Module Series VI Brick? PFM? Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10.2A Power (Watts) 330W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP, UVLO Operating Temperature -40°C ~ 100°C Efficiency 93.5% Mounting Type Through Hole Package / Case 14-DIP Module Size / Dimension 15.92" L x 1.91" W x 0.37" H (48.7mm x 48.6mm x 9.5mm) Report errors? | | | |
|--|--------------------------|---|------|
| Category Power Supplies - Board Mount AC DC Converters Package 14-DIP Module Series VI Brick? PFM? Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10.2A Power (Watts) 330W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP, UVLO Operating Temperature -40°C ~ 100°C Efficiency 93.5% Mounting Type Through Hole Package / Case 14-DIP Module Size / Dimension 1.92" L x 1.91" W x 0.37" H (48.7mm x 48.6mm x 9.5mm) | Manufacturer Part Number | PF175B480T033FP-00 | |
| AC DC Converters Package 14-DIP Module Series VI Brick? PFM? Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10.2A Power (Watts) 330W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP, UVLO Operating Temperature -40°C ~ 100°C Efficiency 93.5% Mounting Type Through Hole Package / Case 14-DIP Module Size / Dimension 1.92" L x 1.91" W x 0.37" H (48.7mm x 48.6mm x 9.5mm) | Manufacturer | Vicor Corporation | |
| Package 14-DIP Module Series VI Brick? PFM? Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10.2A Power (Watts) 330W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP, UVLO Operating Temperature -40°C ~ 100°C Efficiency 93.5% Mounting Type Through Hole Package / Case 14-DIP Module Size / Dimension 1.92" L x 1.91" W x 0.37" H (48.7mm x 48.6mm x 9.5mm) | Category | Power Supplies - Board Mount | |
| Series VI Brick? PFM? Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10.2A Power (Watts) 330W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP, UVLO Operating Temperature -40°C ~ 100°C Efficiency 93.5% Mounting Type Through Hole Package / Case 14-DIP Module Size / Dimension 1.92" L x 1.91" W x 0.37" H (48.7mm x 48.6mm x 9.5mm) | | AC DC Converters | |
| Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10.2A Power (Watts) 330W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP, UVLO Operating Temperature -40°C ~ 100°C Efficiency 93.5% Mounting Type Through Hole Package / Case 14-DIP Module Size / Dimension 1.92" L x 1.91" W x 0.37" H (48.7mm x 48.6mm x 9.5mm) | Package | 14-DIP Module | |
| Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10.2A Power (Watts) 330W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP, UVLO Operating Temperature -40°C ~ 100°C Efficiency 93.5% Mounting Type Through Hole Package / Case 14-DIP Module Size / Dimension 1.92" L x 1.91" W x 0.37" H (48.7mm x 48.6mm x 9.5mm) | Series | VI Brick? PFM? | |
| Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10.2A Power (Watts) 330W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP, UVLO Operating Temperature -40°C ~ 100°C Efficiency 93.5% Mounting Type Through Hole Package / Case 14-DIP Module Size / Dimension 1.92" L x 1.91" W x 0.37" H (48.7mm x 48.6mm x 9.5mm) | Туре | Enclosed | |
| Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10.2A Power (Watts) 330W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP, UVLO Operating Temperature -40°C ~ 100°C Efficiency 93.5% Mounting Type Through Hole Package / Case 14-DIP Module Size / Dimension 1.92" L x 1.91" W x 0.37" H (48.7mm x 48.6mm x 9.5mm) | Number of Outputs | 1 | |
| Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10.2A Power (Watts) 330W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP, UVLO Operating Temperature -40°C ~ 100°C Efficiency 93.5% Mounting Type Through Hole Package / Case 14-DIP Module Size / Dimension 1.92" L x 1.91" W x 0.37" H (48.7mm x 48.6mm x 9.5mm) | Voltage - Input | 85 ~ 264 VAC | |
| Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP, UVLO Operating Temperature Efficiency Mounting Type Through Hole Package / Case 14-DIP Module Size / Dimension | Voltage - Output 1 | 48V | |
| Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP, UVLO Operating Temperature -40°C ~ 100°C Efficiency 93.5% Mounting Type Through Hole Package / Case 14-DIP Module Size / Dimension 1.92" L x 1.91" W x 0.37" H (48.7mm x 48.6mm x 9.5mm) | Voltage - Output 2 | - | |
| Current - Output (Max) Power (Watts) 330W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP, UVLO Operating Temperature -40°C ~ 100°C Efficiency 93.5% Mounting Type Through Hole Package / Case 14-DIP Module Size / Dimension 1.92" L x 1.91" W x 0.37" H (48.7mm x 48.6mm x 9.5mm) | Voltage - Output 3 | - | |
| Power (Watts) Applications ITE (Commercial) OCP, OTP, OVP, SCP, UVLO Operating Temperature -40°C ~ 100°C Efficiency 93.5% Mounting Type Through Hole Package / Case 14-DIP Module Size / Dimension 1.92" L x 1.91" W x 0.37" H (48.7mm x 48.6mm x 9.5mm) | Voltage - Output 4 | - | |
| Applications ITE (Commercial) Features OCP, OTP, OVP, SCP, UVLO Operating Temperature -40°C ~ 100°C Efficiency 93.5% Mounting Type Through Hole Package / Case 14-DIP Module Size / Dimension 1.92" L x 1.91" W x 0.37" H (48.7mm x 48.6mm x 9.5mm) | Current - Output (Max) | 10.2A | |
| Features OCP, OTP, OVP, SCP, UVLO Operating Temperature -40°C ~ 100°C Efficiency 93.5% Mounting Type Through Hole Package / Case 14-DIP Module Size / Dimension 1.92" L x 1.91" W x 0.37" H (48.7mm x 48.6mm x 9.5mm) | Power (Watts) | 330W | |
| Operating Temperature -40°C ~ 100°C Efficiency 93.5% Mounting Type Through Hole Package / Case 14-DIP Module Size / Dimension 1.92" L x 1.91" W x 0.37" H (48.7mm x 48.6mm x 9.5mm) | Applications | ITE (Commercial) | |
| Efficiency 93.5% Mounting Type Through Hole Package / Case 14-DIP Module Size / Dimension 1.92" L x 1.91" W x 0.37" H (48.7mm x 48.6mm x 9.5mm) | Features | OCP, OTP, OVP, SCP, UVLO | |
| Mounting Type Through Hole Package / Case 14-DIP Module Size / Dimension 1.92" L x 1.91" W x 0.37" H (48.7mm x 48.6mm x 9.5mm) | Operating Temperature | -40°C ~ 100°C | |
| Package / Case 14-DIP Module Size / Dimension 1.92" L x 1.91" W x 0.37" H (48.7mm x 48.6mm x 9.5mm) | Efficiency | 93.5% | |
| Size / Dimension 1.92" L x 1.91" W x 0.37" H (48.7mm x 48.6mm x 9.5mm) | Mounting Type | Through Hole | |
| | Package / Case | 14-DIP Module | |
| Report errors? | Size / Dimension | 1.92" L x 1.91" W x 0.37" H (48.7mm x 48.6mm x 9.5mm) | |
| | | Report error | ors? |

PF175B480T033FP-00 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PF175B480T033FP-00 Payment Methods



















PF175B480T033FP-00 Shipping Methods













If you have any question about PF175B480T033FP-00, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com