



PFE300SA12 Information

Part Number PFE300SA12

Manufacturer TDK-Lambda Americas Inc.

Category Power Supplies - Board Mount

AC DC Converters

Description AC/DC CONVERTER 12V 300W

Package 11-DIP Module, Full Brick

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PFE300SA12 Specifications

Manufacturer Part Number PFE300SA12 Manufacturer TDK-Lambda Americas Inc. Category Power Supplies - Board Mount AC DC Converters Package 11-DIP Module, Full Brick Series PFE300SA Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 25A Power (Watts) 300W Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -40°C ~ 100°C (With Derating) Efficiency 85% Mounting Type Through Hole Package / Case 11-DIP Module, Full Brick Size / Dimension 4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm) Report errors?	-	
Category Power Supplies - Board Mount AC DC Converters Package 11-DIP Module, Full Brick Series PFE300SA Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 25A Power (Watts) 300W Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -40°C ~ 100°C (With Derating) Efficiency 85% Mounting Type Through Hole Package / Case 11-DIP Module, Full Brick Size / Dimension 4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	Manufacturer Part Number	PFE300SA12
Package 11-DIP Module, Full Brick Series PFE300SA Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 25A Power (Watts) 300W Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -40°C ~ 100°C (With Derating) Efficiency 85% Mounting Type Through Hole Package / Case 11-DIP Module, Full Brick Size / Dimension 4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	Manufacturer	TDK-Lambda Americas Inc.
Package 11-DIP Module, Full Brick Series PFE300SA Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 25A Power (Watts) 300W Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -40°C ~ 100°C (With Derating) Efficiency 85% Mounting Type Through Hole Package / Case 11-DIP Module, Full Brick Size / Dimension 4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	Category	Power Supplies - Board Mount
Series PFE300SA Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 25A Power (Watts) 300W Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -40°C ~ 100°C (With Derating) Efficiency 85% Mounting Type Through Hole Package / Case 11-DIP Module, Full Brick Size / Dimension 4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)		AC DC Converters
Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 25A Power (Watts) 300W Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -40°C ~ 100°C (With Derating) Efficiency 85% Mounting Type Through Hole Package / Case 11-DIP Module, Full Brick Size / Dimension 4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	Package	11-DIP Module, Full Brick
Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 25A Power (Watts) 300W Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -40°C ~ 100°C (With Derating) Efficiency 85% Mounting Type Through Hole Package / Case 11-DIP Module, Full Brick Size / Dimension 4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	Series	PFE300SA
Voltage - Input 85 ~ 265 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 25A Power (Watts) 300W Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -40°C ~ 100°C (With Derating) Efficiency 85% Mounting Type Through Hole Package / Case 11-DIP Module, Full Brick Size / Dimension 4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	Туре	Enclosed
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications Features Remote On/Off, OCP, OTP, OVP Operating Temperature Efficiency Mounting Type Through Hole Package / Case Size / Dimension 12V 12V 12V 12V 12V 12V 12V 12	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications Features Remote On/Off, OCP, OTP, OVP Operating Temperature Efficiency Mounting Type Through Hole Package / Case Size / Dimension Output (Max) Current - Output (Max) Size / Dimension Current - Output (Max) Size / Output 4	Voltage - Input	85 ~ 265 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -40°C ~ 100°C (With Derating) Efficiency 85% Mounting Type Through Hole Package / Case 11-DIP Module, Full Brick Size / Dimension - Use X 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	Voltage - Output 1	12V
Voltage - Output 4 Current - Output (Max) 25A Power (Watts) 300W Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -40°C ~ 100°C (With Derating) Efficiency 85% Mounting Type Through Hole Package / Case 11-DIP Module, Full Brick Size / Dimension 4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	Voltage - Output 2	-
Current - Output (Max) 25A Power (Watts) 300W Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -40°C ~ 100°C (With Derating) Efficiency 85% Mounting Type Through Hole Package / Case 11-DIP Module, Full Brick Size / Dimension 25A Mounting Type Through Hole 11-DIP Module, Full Brick Size / Dimension 4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Remote On/Off, OCP, OTP, OVP Operating Temperature -40°C ~ 100°C (With Derating) Efficiency 85% Mounting Type Through Hole Package / Case 11-DIP Module, Full Brick Size / Dimension 300W Remote On/Off, OCP, OTP, OVP -40°C ~ 100°C (With Derating) 1-00°C (With Derating)	Voltage - Output 4	-
Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -40°C ~ 100°C (With Derating) Efficiency 85% Mounting Type Through Hole Package / Case 11-DIP Module, Full Brick Size / Dimension 4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	Current - Output (Max)	25A
FeaturesRemote On/Off, OCP, OTP, OVPOperating Temperature-40°C ~ 100°C (With Derating)Efficiency85%Mounting TypeThrough HolePackage / Case11-DIP Module, Full BrickSize / Dimension4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	Power (Watts)	300W
Operating Temperature -40°C ~ 100°C (With Derating) Efficiency 85% Mounting Type Through Hole Package / Case 11-DIP Module, Full Brick Size / Dimension 4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	Applications	ITE (Commercial)
Efficiency 85% Mounting Type Through Hole Package / Case 11-DIP Module, Full Brick Size / Dimension 4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	Features	Remote On/Off, OCP, OTP, OVP
Mounting Type Through Hole Package / Case 11-DIP Module, Full Brick Size / Dimension 4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	Operating Temperature	-40°C ~ 100 °C (With Derating)
Package / Case 11-DIP Module, Full Brick Size / Dimension 4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	Efficiency	85%
Size / Dimension 4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	Mounting Type	Through Hole
	Package / Case	11-DIP Module, Full Brick
Report errors?	Size / Dimension	4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)
		Report errors?

PFE300SA12 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PFE300SA12 Payment Methods



















PFE300SA12 Shipping Methods













If you have any question about PFE300SA12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com