



PFE5K1R60E Information

Heisener.com

For Reference Only

Part Number PFE5K1R60E

Manufacturer Ohmite
Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 1.6 OHM 10% 1082W

Package Radial, Tubular

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PFE5K1R60E Specifications

Manufacturer Part NumberPFE5K1R60EManufacturerOhmiteCategoryResistorsPackageRadial, TubularSeriesPowr-Rib?PFEResistance1.6 OhmsTolerance±10%Power (Watts)1082WCompositionWirewoundTemperature Coefficient±500ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeCeramicMounting FeatureBracketsSize / Dimension-Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-Report errors?		
CategoryResistorsPackageRadial, TubularSeriesPowr-Rib?PFEResistance1.6 OhmsTolerance±10%Power (Watts)1082WCompositionWirewoundTemperature Coefficient±500ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeCeramicMounting FeatureBracketsSize / Dimension-Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Manufacturer Part Number	PFE5K1R60E
Chassis Mount Resistors Package Radial, Tubular Series Powr-Rib?PFE Resistance 1.6 Ohms Tolerance ±10% Power (Watts) 1082W Composition Wirewound Temperature Coefficient ±500ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Ceramic Mounting Feature Brackets Size / Dimension - Height - Seated (Max) Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate	Manufacturer	Ohmite
PackageRadial, TubularSeriesPowr-Rib?PFEResistance1.6 OhmsTolerance±10%Power (Watts)1082WCompositionWirewoundTemperature Coefficient±500ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeCeramicMounting FeatureBracketsSize / Dimension-Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Category	Resistors
SeriesPowr-Rib?PFEResistance1.6 OhmsTolerance±10%Power (Watts)1082WCompositionWirewoundTemperature Coefficient±500ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeCeramicMounting FeatureBracketsSize / Dimension-Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-		Chassis Mount Resistors
Resistance1.6 OhmsTolerance±10%Power (Watts)1082WCompositionWirewoundTemperature Coefficient±500ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeCeramicMounting FeatureBracketsSize / Dimension-Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Package	Radial, Tubular
Tolerance ±10% Power (Watts) 1082W Composition Wirewound Temperature Coefficient ±500ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Ceramic Mounting Feature Brackets Size / Dimension - Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Series	Powr-Rib?PFE
Power (Watts) Composition Wirewound Temperature Coefficient ±500ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Mounting Feature Brackets Size / Dimension - Height - Seated (Max) Lead Style Package / Case Package / Case Failure Rate 1082W Wirewound ±500ppm/°C -55°C ~ 350°C Ceramic Brackets - Solder Lugs Radial, Tubular Failure Rate	Resistance	1.6 Ohms
Composition Wirewound Temperature Coefficient ±500ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Ceramic Mounting Feature Brackets Size / Dimension - Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate	Tolerance	±10%
Temperature Coefficient ±500ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Ceramic Mounting Feature Brackets Size / Dimension - Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Power (Watts)	1082W
Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Ceramic Mounting Feature Brackets Size / Dimension - Height - Seated (Max) Lead Style Package / Case Radial, Tubular Failure Rate - Solve C ~ 350°C Ceramic Solve C ~ 350°C Ceramic Solve Sates Brackets - Solve Sates Radial, Tubular Failure Rate - Solve Sates Failure Rate	Composition	Wirewound
Features - Coating, Housing Type Ceramic Mounting Feature Brackets Size / Dimension - Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate	Temperature Coefficient	±500ppm/°C
Coating, Housing Type Mounting Feature Brackets Size / Dimension - Height - Seated (Max) Lead Style Package / Case Radial, Tubular Failure Rate Ceramic Brackets Solder Lugs Radial, Tubular -	Operating Temperature	-55°C ~ 350°C
Mounting Feature Brackets Size / Dimension - Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Features	-
Size / Dimension - Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Coating, Housing Type	Ceramic
Height - Seated (Max) Lead Style Package / Case Radial, Tubular Failure Rate -	Mounting Feature	Brackets
Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Size / Dimension	-
Package / Case Radial, Tubular Failure Rate -	Height - Seated (Max)	-
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Radial, Tubular
Report errors?	Failure Rate	-
		Report errors?

PFE5K1R60E Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PFE5K1R60E Payment Methods



















PFE5K1R60E Shipping Methods













If you have any question about PFE5K1R60E, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com