



### PFG.2B.306.CLLD52 Information

Heisener.com

Part Number PFG.2B.306.CLLD52

Manufacturer LEMO

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PNL MNT RCPT 6SKT SLD CUP

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# PFG.2B.306.CLLD52 Specifications

| Manufacturer Part NumberPFG.2B.306.CLLD52ManufacturerLEMOCategoryConnectors, InterconnectsPackage-Series2BConnector TypeReceptacle, Female SocketsNumber of Positions6Shell Size - Insert306Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel MountTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP50 - Dust ProtectedShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated- |                          |                                     |
|--|--------------------------|-------------------------------------|
| Category Circular Connectors  Package - Series 2B Connector Type Receptacle, Female Sockets Number of Positions 6 Shell Size - Insert 306 Shell Size, MIL - Mounting Type Free Hanging (In-Line); Panel Mount Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated -  | Manufacturer Part Number | PFG.2B.306.CLLD52                   |
| Circular Connectors  Package Series 2B Connector Type Receptacle, Female Sockets Number of Positions 6 Shell Size - Insert 306 Shell Size, MIL - Mounting Type Free Hanging (In-Line); Panel Mount Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated -   | Manufacturer             | LEMO                                |
| Package - Series 2B Connector Type Receptacle, Female Sockets Number of Positions 6 Shell Size - Insert 306 Shell Size, MIL - Series Hanging (In-Line); Panel Mount Type Free Hanging (In-Line); Panel Mount Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated                                   | Category                 | Connectors, Interconnects           |
| Series 2B Connector Type Receptacle, Female Sockets Number of Positions 6 Shell Size - Insert 306 Shell Size, MIL  |                          | Circular Connectors                 |
| Connector Type Receptacle, Female Sockets  Number of Positions 6  Shell Size - Insert 306  Shell Size, MIL -  Mounting Type Free Hanging (In-Line); Panel Mount  Termination Solder Cup  Fastening Type Push-Pull, Detent Lock  Orientation G  Ingress Protection IP50 - Dust Protected  Shell Material, Finish Brass, Chrome Plated  Contact Finish Gold  Features Shielded  Voltage - Rated -  | Package                  | -                                   |
| Number of Positions Shell Size - Insert 306 Shell Size, MIL - Mounting Type Free Hanging (In-Line); Panel Mount Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated -  | Series                   | 2B                                  |
| Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line); Panel Mount  Termination  Solder Cup  Fastening Type  Push-Pull, Detent Lock  Orientation  G  Ingress Protection  IP50 - Dust Protected  Shell Material, Finish  Brass, Chrome Plated  Contact Finish  Gold  Features  Shielded  Voltage - Rated  -   | Connector Type           | Receptacle, Female Sockets          |
| Shell Size, MIL  Mounting Type Free Hanging (In-Line); Panel Mount  Termination Solder Cup  Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated -   | Number of Positions      | 6                                   |
| Mounting TypeFree Hanging (In-Line); Panel MountTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP50 - Dust ProtectedShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-   | Shell Size - Insert      | 306                                 |
| Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated -  | Shell Size, MIL          | -                                   |
| Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated -   | Mounting Type            | Free Hanging (In-Line); Panel Mount |
| Orientation G Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated -   | Termination              | Solder Cup                          |
| Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated -   | Fastening Type           | Push-Pull, Detent Lock              |
| Shell Material, Finish  Contact Finish  Gold  Features  Shielded  Voltage - Rated  | Orientation              | G                                   |
| Contact Finish Gold Features Shielded Voltage - Rated -  | Ingress Protection       | IP50 - Dust Protected               |
| Features Shielded Voltage - Rated -  | Shell Material, Finish   | Brass, Chrome Plated                |
| Voltage - Rated -  | Contact Finish           | Gold                                |
|  | Features                 | Shielded                            |
|  | Voltage - Rated          | -                                   |
| Current Rating 12A   | Current Rating           | 12A                                 |
| Report errors?   |                          | Report errors?                      |

### PFG.2B.306.CLLD52 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# PFG.2B.306.CLLD52 Payment Methods



















## PFG.2B.306.CLLD52 Shipping Methods













If you have any question about PFG.2B.306.CLLD52, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com