



Heisener.com

#### PHG.0T.307.CLLC50Z Information

Part Number PHG.0T.307.CLLC50Z

Manufacturer LEMO

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 7POS INLNE SKT SLD CUP

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# PHG.0T.307.CLLC50Z Specifications

Manufacturer Part Number     PHG.0T.307.CLLC50Z       Manufacturer     LEMO       Category     Connectors, Interconnects       Package     -       Series     0T       Connector Type     Receptacle, Female Sockets       Number of Positions     7       Shell Size - Insert     307       Shell Size, MIL     -       Mounting Type     Free Hanging (In-Line)       Termination     Solder Cup       Fastening Type     Push-Pull, Detent Lock       Orientation     G       Ingress Protection     IP68 - Dust Tight, Waterproof       Shell Material, Finish     Brass, Chrome Plated       Contact Finish     Gold       Features     Backshell, Shielded       Voltage - Rated     -       Current Rating     2.5A		
CategoryConnectors, Interconnects Circular ConnectorsPackage-Series0TConnector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert307Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating2.5A	Manufacturer Part Number	PHG.0T.307.CLLC50Z
Package-Series0TConnector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert307Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating2.5A	Manufacturer	LEMO
Package-Series0TConnector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert307Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating2.5A	Category	Connectors, Interconnects
SeriesOTConnector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert307Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating2.5A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert307Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating2.5A	Package	-
Number of Positions7Shell Size - Insert307Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating2.5A	Series	OT
Shell Size - Insert Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP68 - Dust Tight, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Backshell, Shielded  Voltage - Rated Current Rating 2.5A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP68 - Dust Tight, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Backshell, Shielded  Voltage - Rated - Current Rating 2.5A	Number of Positions	7
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesBackshell, ShieldedVoltage - Rated-Current Rating2.5A	Shell Size - Insert	307
Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP68 - Dust Tight, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated Current Rating 2.5A	Shell Size, MIL	-
Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP68 - Dust Tight, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated Current Rating 2.5A	Mounting Type	Free Hanging (In-Line)
Orientation G Ingress Protection IP68 - Dust Tight, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated - Current Rating 2.5A	Termination	Solder Cup
Ingress Protection IP68 - Dust Tight, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Backshell, Shielded Voltage - Rated - Current Rating 2.5A	Fastening Type	Push-Pull, Detent Lock
Shell Material, Finish  Contact Finish  Gold  Features  Backshell, Shielded  Voltage - Rated  Current Rating  2.5A	Orientation	G
Contact Finish Gold Features Backshell, Shielded  Voltage - Rated - Current Rating 2.5A	Ingress Protection	IP68 - Dust Tight, Waterproof
Features Backshell, Shielded  Voltage - Rated - Current Rating 2.5A	Shell Material, Finish	Brass, Chrome Plated
Voltage - Rated - Current Rating 2.5A	Contact Finish	Gold
Current Rating 2.5A	Features	Backshell, Shielded
-	Voltage - Rated	-
Report errors?	Current Rating	2.5A
		Report errors?

#### PHG.0T.307.CLLC50Z Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### PHG.0T.307.CLLC50Z Payment Methods



















# PHG.0T.307.CLLC50Z Shipping Methods













If you have any question about PHG.0T.307.CLLC50Z, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com