

PIC12F1822-I/P

PIC12F1822-I/P Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



PIC12F1822-I/P Specifications

Manufacturer Part NumberPIC12F1822-I/PManufacturerMicrochip GenhologyCategoryIntegrated Circuits (ICs)CategoryEmbedded - MicrocontrollersPackage8-DIP (0.300", 7.62mm)PackagePIC? XLP? 12FCore ProcessorPICCore Size8-BitSpeed32MHzConnectivityICc, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, POR, PWM, WDTNumber of I/O6Program Memory SizeSIXB (2K x 14)Program Memory TypeFLASH
CategoryIntegrated Circuits (ICs)Embedded - MicrocontrollersPackage8-DIP (0.300", 7.62mm)Package8-DIP (0.300", 7.62mm)SeriesPIC? XLP? 12FCore ProcessorPICCore Size8-BitSpeed32MHzConnectivityI2C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, POR, PWM, WDTNumber of I/O6Program Memory Size3.5KB (2K x 14)Program Memory TypeFLASH
ImageEmbedded - MicrocontrollersPackage8-DIP (0.300", 7.62mm)SeriesPIC (0.300", 7.62mm)Core ProcessorPICCore Size8-BitSpeed32MHzConnectivityI2C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, POR, PWM, WDTNumber of I/O6Program Memory Size3.5KB (2K x 14)Frogram Memory TypeFLASH
Package8-DIP (0.300", 7.62mm)SeriesPIC? XLP? 12FCore ProcessorPICCore Size8-BitSpeed32MHzConnectivityI2C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, POR, PWM, WDTNumber of I/O6Program Memory Size3.5KB (2K x 14)Program Memory TypeFLASH
SeriesPIC? XLP? 12FCore ProcessorPICCore Size8-BitSpeed32MHzConnectivityI2C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, POR, PWM, WDTNumber of I/O6Program Memory Size3.5KB (2K x 14)Program Memory TypeFLASH
Core ProcessorPICCore Size8-BitSpeed32MHzConnectivityI2C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, POR, PWM, WDTNumber of I/O6Program Memory Size3.5KB (2K x 14)Program Memory TypeFLASH
Core Size8-BitSpeed32MHzConnectivityI2C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, POR, PWM, WDTNumber of I/O6Program Memory Size3.5KB (2K x 14)Program Memory TypeFLASH
Speed32MHzConnectivityI2C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, POR, PWM, WDTNumber of I/O6Program Memory Size3.5KB (2K x 14)Program Memory TypeFLASH
Image: ConnectivityI2C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, POR, PWM, WDTNumber of I/O6Program Memory Size3.5KB (2K x 14)Program Memory TypeFLASH
PeripheralsBrown-out Detect/Reset, POR, PWM, WDTNumber of I/O6Program Memory Size3.5KB (2K x 14)Program Memory TypeFLASH
Number of I/O6Program Memory Size3.5KB (2K x 14)Program Memory TypeFLASH
Program Memory Size3.5KB (2K x 14)Program Memory TypeFLASH
Program Memory Type FLASH
EEPROM Size 256 x 8
RAM Size 128 x 8
Voltage - Supply (Vcc/Vdd)1.8 V ~ 5.5 V
Data ConvertersA/D 4x10b, D/A 1x5b
Oscillator Type Internal
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ (TA)
Mounting Type -
Package / Case 8-DIP (0.300", 7.62mm)
Supplier Device Package 8-PDIP
Report errors ⁴

PIC12F1822-I/P Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

PIC12F1822-I/P Payment Methods



PIC12F1822-I/P Shipping Methods



If you have any question about PIC12F1822-I/P, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com