



PIC16C58B-20I/SS Information



For Reference Only

Part Number PIC16C58B-20I/SS

Manufacturer Microchip Technology

Category Integrated Circuits (ICs)
Embedded - Microcontrollers

Description IC MCU 8BIT 3KB OTP 20SSOP

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com

20-SSOP (0.209", 5.30mm Width)



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.

Package









PIC16C58B-20I/SS Specifications

Manufacturer Part Number PIC16C58B-20I/SS Manufacturer Microchip Technology Category Integrated Circuits (ICs) Embedded - Microcontrollers Package 20-SSOP (0.209", 5.30mm Width) Series PIC? 16C Core Processor PIC Core Size 8-Bit Speed 20MHz Connectivity - Peripherals POR, WDT Number of I/O 12 Program Memory Size 3KB (2K x 12) Program Memory Type OTP EEPROM Size - RAM Size 73 x 8 Voltage - Supply (Vcc/Vdd) 3 V ~ 5.5 V Data Converters - Oscillator Type External Operating Temperature -40°C ~ 85°C (TA) Mounting Type - Package / Case 20-SSOP (0.209", 5.30mm Width) Supplier Device Package 20-SSOP	*	
Category Integrated Circuits (ICs) Embedded - Microcontrollers Package 20-SSOP (0.209", 5.30mm Width) Series PIC? 16C Core Processor PIC Core Size 8-Bit Speed 20MHz Connectivity - Peripherals POR, WDT Number of I/O 12 Program Memory Size 3KB (2K x 12) Program Memory Type OTP EEPROM Size - RAM Size 73 x 8 Voltage - Supply (Vcc/Vdd) 3 V ~ 5.5 V Data Converters - Oscillator Type External Operating Temperature -40°C ~ 85°C (TA) Mounting Type - Package / Case 20-SSOP (0.209", 5.30mm Width)	Manufacturer Part Number	PIC16C58B-20I/SS
Backage 20-SSOP (0.209", 5.30mm Width) Series PIC? 16C Core Processor PIC Core Size 8-Bit Speed 20MHz Connectivity - Peripherals POR, WDT Number of I/O 12 Program Memory Size 3KB (2K x 12) Program Memory Type OTP EEPROM Size - RAM Size 73 x 8 Voltage - Supply (Vcc/Vdd) 3 V ~ 5.5 V Data Converters - Oscillator Type External Operating Temperature -40°C ~ 85°C (TA) Mounting Type - Package / Case 20-SSOP (0.209", 5.30mm Width)	Manufacturer	Microchip Technology
Package 20-SSOP (0.209", 5.30mm Width) Series PIC? 16C Core Processor PIC Core Size 8-Bit Speed 20MHz Connectivity - Peripherals POR, WDT Number of I/O 12 Program Memory Size 3KB (2K x 12) Program Memory Type OTP EEPROM Size - RAM Size 73 x 8 Voltage - Supply (Vcc/Vdd) 3 V ~ 5.5 V Data Converters - Oscillator Type External Operating Temperature -40°C ~ 85°C (TA) Mounting Type - Package / Case 20-SSOP (0.209", 5.30mm Width)	Category	Integrated Circuits (ICs)
Series PIC? 16C Core Processor PIC Core Size 8-Bit Speed 20MHz Connectivity - Peripherals POR, WDT Number of I/O 12 Program Memory Size 3KB (2K x 12) Program Memory Type OTP EEPROM Size - RAM Size 73 x 8 Voltage - Supply (Vcc/Vdd) 3 V ~ 5.5 V Data Converters - Oscillator Type External Operating Temperature -40°C ~ 85°C (TA) Mounting Type - Package / Case 20-SSOP (0.209", 5.30mm Width)		Embedded - Microcontrollers
Core Processor PIC Core Size 8-Bit Speed 20MHz Connectivity - Peripherals POR, WDT Number of I/O 12 Program Memory Size 3KB (2K x 12) Program Memory Type OTP EEPROM Size - RAM Size 73 x 8 Voltage - Supply (Vcc/Vdd) 3 V ~ 5.5 V Data Converters - Oscillator Type External Operating Temperature -40°C ~ 85°C (TA) Mounting Type - Package / Case 20-SSOP (0.209", 5.30mm Width)	Package	20-SSOP (0.209", 5.30mm Width)
Core Size 8-Bit Speed 20MHz Connectivity - Peripherals POR, WDT Number of I/O 12 Program Memory Size 3KB (2K x 12) Program Memory Type OTP EEPROM Size - RAM Size 73 x 8 Voltage - Supply (Vcc/Vdd) 3 V ~ 5.5 V Data Converters - Oscillator Type External Operating Temperature -40°C ~ 85°C (TA) Mounting Type - Package / Case 20-SSOP (0.209", 5.30mm Width)	Series	PIC? 16C
Speed 20MHz Connectivity - Peripherals POR, WDT Number of I/O 12 Program Memory Size 3KB (2K x 12) Program Memory Type OTP EEPROM Size - RAM Size 73 x 8 Voltage - Supply (Vcc/Vdd) 3 V ~ 5.5 V Data Converters - Oscillator Type External Operating Temperature -40°C ~ 85°C (TA) Mounting Type - Package / Case 20-SSOP (0.209", 5.30mm Width)	Core Processor	PIC
Connectivity Peripherals POR, WDT Number of I/O 12 Program Memory Size 3KB (2K x 12) Program Memory Type OTP EEPROM Size RAM Size 73 x 8 Voltage - Supply (Vcc/Vdd) 3 V ~ 5.5 V Data Converters - Oscillator Type External Operating Temperature -40°C ~ 85°C (TA) Mounting Type POR, WDT ARD ARD ARD ARD ARD ARD ARD ARD ARD AR	Core Size	8-Bit
PeripheralsPOR, WDTNumber of I/O12Program Memory Size3KB (2K x 12)Program Memory TypeOTPEEPROM Size-RAM Size73 x 8Voltage - Supply (Vcc/Vdd)3 V ~ 5.5 VData Converters-Oscillator TypeExternalOperating Temperature-40°C ~ 85°C (TA)Mounting Type-Package / Case20-SSOP (0.209", 5.30mm Width)	Speed	20MHz
Number of I/O Program Memory Size 3KB (2K x 12) Program Memory Type OTP EEPROM Size - RAM Size 73 x 8 Voltage - Supply (Vcc/Vdd) 3 V ~ 5.5 V Data Converters - Oscillator Type External Operating Temperature 4-40°C ~ 85°C (TA) Mounting Type Package / Case 12 3KB (2K x 12) ARB (2K x 12) ARB (2K x 12) ARB (2K x 12) External - COTP External - COPERATION OF TABLE (TABLE) - COPERATION OF TABLE) - COPE	Connectivity	-
Program Memory Size 3KB (2K x 12) Program Memory Type OTP EEPROM Size RAM Size 73 x 8 Voltage - Supply (Vcc/Vdd) 3 V ~ 5.5 V Data Converters Oscillator Type External Operating Temperature -40°C ~ 85°C (TA) Mounting Type Package / Case 20-SSOP (0.209", 5.30mm Width)	Peripherals	POR, WDT
Program Memory Type EEPROM Size - RAM Size 73 x 8 Voltage - Supply (Vcc/Vdd) 3 V ~ 5.5 V Data Converters - Oscillator Type External Operating Temperature -40°C ~ 85°C (TA) Mounting Type - Package / Case OTP OTP - OTP - A OTP - OT - OT	Number of I/O	12
EEPROM Size - RAM Size 73 x 8 Voltage - Supply (Vcc/Vdd) 3 V ~ 5.5 V Data Converters - Coscillator Type External Operating Temperature -40°C ~ 85°C (TA) Mounting Type - Package / Case 20-SSOP (0.209", 5.30mm Width)	Program Memory Size	3KB (2K x 12)
RAM Size 73 x 8 Voltage - Supply (Vcc/Vdd) 3 V ~ 5.5 V Data Converters - Oscillator Type External Operating Temperature -40°C ~ 85°C (TA) Mounting Type - Package / Case 20-SSOP (0.209", 5.30mm Width)	Program Memory Type	OTP
Voltage - Supply (Vcc/Vdd) Data Converters Oscillator Type External Operating Temperature -40°C ~ 85°C (TA) Mounting Type - Package / Case 20-SSOP (0.209", 5.30mm Width)	EEPROM Size	-
Data Converters Oscillator Type External Operating Temperature -40°C ~ 85°C (TA) Mounting Type - Package / Case 20-SSOP (0.209", 5.30mm Width)	RAM Size	73 x 8
Oscillator Type External $ -40^{\circ}\text{C} \sim 85^{\circ}\text{C (TA)} $ Mounting Type $ - $ Package / Case $ 20\text{-SSOP } (0.209^{\circ}, 5.30 \text{mm Width)} $	Voltage - Supply (Vcc/Vdd)	3 V ~ 5.5 V
Operating Temperature -40°C ~ 85°C (TA) Mounting Type - Package / Case 20-SSOP (0.209", 5.30mm Width)	Data Converters	-
Mounting Type - Package / Case - 20-SSOP (0.209", 5.30mm Width)	Oscillator Type	External
Package / Case 20-SSOP (0.209", 5.30mm Width)	Operating Temperature	-40°C ~ 85°C (TA)
	Mounting Type	-
Supplier Device Package 20-SSOP	Package / Case	20-SSOP (0.209", 5.30mm Width)
	Supplier Device Package	20-SSOP
Report errors?		Report errors?

PIC16C58B-20I/SS Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PIC16C58B-20I/SS Payment Methods

































If you have any question about PIC16C58B-20I/SS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com