



### PIC16F685T-I/SS Information



For Reference Only

Part Number PIC16F685T-I/SS

Manufacturer Microchip Technology

Category Integrated Circuits (ICs)
Embedded - Microcontrollers

**Description**IC MCU 8BIT 7KB FLASH 20SSOP**Package**20-SSOP (0.209", 5.30mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## PIC16F685T-I/SS Specifications

Manufacturer Part NumberPIC16F685T-I/SSManufacturerMicrochip TechnologyCategoryIntegrated Circuits (ICs)Embedded - MicrocontrollersPackage20-SSOP (0.209", 5.30mm Width)SeriesPIC? 16FCore ProcessorPICCore Size8-BitSpeed20MHzConnectivity-	•	
Category         Integrated Circuits (ICs)           Embedded - Microcontrollers           Package         20-SSOP (0.209", 5.30mm Width)           Series         PIC? 16F           Core Processor         PIC           Core Size         8-Bit           Speed         20MHz	Manufacturer Part Number	PIC16F685T-I/SS
Embedded - Microcontrollers  Package 20-SSOP (0.209", 5.30mm Width)  Series PIC? 16F  Core Processor PIC  Core Size 8-Bit  Speed 20MHz	Manufacturer	Microchip Technology
Package 20-SSOP (0.209", 5.30mm Width)  Series PIC? 16F  Core Processor PIC  Core Size 8-Bit  Speed 20MHz	Category	Integrated Circuits (ICs)
Series PIC? 16F  Core Processor PIC  Core Size 8-Bit  Speed 20MHz		Embedded - Microcontrollers
Core Processor PIC Core Size 8-Bit Speed 20MHz	Package	20-SSOP (0.209", 5.30mm Width)
Core Size 8-Bit Speed 20MHz	Series	PIC? 16F
Speed 20MHz	Core Processor	PIC
•	Core Size	8-Bit
Connectivity -	Speed	20MHz
	Connectivity	-
Peripherals Brown-out Detect/Reset, POR, PWM, WDT	Peripherals	Brown-out Detect/Reset, POR, PWM, WDT
Number of I/O 18	Number of I/O	18
Program Memory Size 7KB (4K x 14)	Program Memory Size	7KB (4K x 14)
Program Memory Type FLASH	Program Memory Type	FLASH
EEPROM Size 256 x 8	EEPROM Size	256 x 8
RAM Size 256 x 8	RAM Size	256 x 8
Voltage - Supply (Vcc/Vdd) $2 \text{ V} \sim 5.5 \text{ V}$	Voltage - Supply (Vcc/Vdd)	2 V ~ 5.5 V
Data Converters A/D 12x10b	Data Converters	A/D 12x10b
Oscillator Type Internal	Oscillator Type	Internal
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C} \text{ (TA)}$	Operating Temperature	$-40^{\circ}\text{C} \sim 85^{\circ}\text{C} \text{ (TA)}$
Mounting Type -	Mounting Type	-
Package / Case 20-SSOP (0.209", 5.30mm Width)	Package / Case	20-SSOP (0.209", 5.30mm Width)
Supplier Device Package 20-SSOP	Supplier Device Package	20-SSOP
Report error		Report errors?

#### PIC16F685T-I/SS Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# PIC16F685T-I/SS Payment Methods



















### PIC16F685T-I/SS Shipping Methods













If you have any question about PIC16F685T-I/SS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com