

# PIC16LF1938-I/SS

u Quote

#### PIC16LF1938-I/SS Information

	Part Number	PIC16LF1938-I/SS	
ANTONOODIN TO	Manufacturer	Microchip Technology	Tel North
www.heisener.com	Category	Integrated Circuits (ICs) Embedded - Microcontrollers	
line .	Description	IC MCU 8BIT 28KB FLASH 28SSOP	- 2566
	Package	28-SSOP (0.209", 5.30mm Width)	
-(III.		For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## PIC16LF1938-I/SS Specifications

Manufacturer Part NumberPIC16LF1938-I/SSManufacturerMicrochip TechnologyCategoryIntegrated Circuits (ICs)Embedded - MicrocontrollersPackage28-SSOP (0.209", 5.30mm Width)SeriesPIC? XLP? 16FCore ProcessorPICCore Size8-BitSpeed32MHzConnectivityI2C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, LCD, POR, PWM, WDTNumber of I/O25Program Memory Size28KB (16K x 14)
CategoryIntegrated Circuits (ICs)Embedded - MicrocontrollersPackage28-SSOP (0.209", 5.30mm Width)SeriesPIC? XLP? 16FCore ProcessorPICCore Size8-BitSpeed32MHzConnectivityI2C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, LCD, POR, PWM, WDTNumber of I/O25
Embedded - MicrocontrollersPackage28-SSOP (0.209", 5.30mm Width)SeriesPIC? XLP? 16FCore ProcessorPICCore Size8-BitSpeed32MHzConnectivityI2C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, LCD, POR, PWM, WDTNumber of I/O25
Package28-SSOP (0.209", 5.30mm Width)SeriesPIC? XLP? 16FCore ProcessorPICCore Size8-BitSpeed32MHzConnectivityI2C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, LCD, POR, PWM, WDTNumber of I/O25
SeriesPIC? XLP? 16FCore ProcessorPICCore Size8-BitSpeed32MHzConnectivityI2C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, LCD, POR, PWM, WDTNumber of I/O25
Core ProcessorPICCore Size8-BitSpeed32MHzConnectivityI2C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, LCD, POR, PWM, WDTNumber of I/O25
Core Size8-BitSpeed32MHzConnectivityI2C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, LCD, POR, PWM, WDTNumber of I/O25
Speed32MHzConnectivityI2C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, LCD, POR, PWM, WDTNumber of I/O25
ConnectivityI2C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, LCD, POR, PWM, WDTNumber of I/O25
Peripherals Brown-out Detect/Reset, LCD, POR, PWM, WDT   Number of I/O 25
Number of I/O 25
Program Memory Size 28KB (16K x 14)
Program Memory Type FLASH
EEPROM Size 256 x 8
RAM Size 1K x 8
Voltage - Supply (Vcc/Vdd)1.8 V ~ 3.6 V
Data Converters A/D 11x10b
Oscillator Type Internal
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ (TA)
Mounting Type -
Package / Case 28-SSOP (0.209", 5.30mm Width)
Supplier Device Package 28-SSOP
Report errors?

#### PIC16LF1938-I/SS Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### PIC16LF1938-I/SS Payment Methods



### PIC16LF1938-I/SS Shipping Methods



If you have any question about PIC16LF1938-I/SS, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com