



### PIC18F25K50-E/ML Information



For Reference Only

Part Number PIC18F25K50-E/ML

Manufacturer Microchip Technology

Category Integrated Circuits (ICs)
Embedded - Microcontrollers

**Description** IC MCU 8BIT 32KB FLASH 28QFN

Package 28-VQFN Exposed Pad

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## PIC18F25K50-E/ML Specifications

Manufacturer Part Number  Manufacturer  Microchip Technology  Category  Integrated Circuits (ICs)  Embedded - Microcontrollers  Package  28-VQFN Exposed Pad  Series  PIC? XLP? 18K  Core Processor  PIC  Core Size  8-Bit  Speed  48MHz  Connectivity  I2C, SPI, UART/USART, USB  Peripherals  Brown-out Detect/Reset, POR, PWM, WDT  Number of I/O  25
Category  Integrated Circuits (ICs)  Embedded - Microcontrollers  Package  28-VQFN Exposed Pad  Series  PIC? XLP? 18K  Core Processor  PIC  Core Size  8-Bit  Speed  48MHz  Connectivity  I2C, SPI, UART/USART, USB  Peripherals  Brown-out Detect/Reset, POR, PWM, WDT
Embedded - Microcontrollers  Package 28-VQFN Exposed Pad  Series PIC? XLP? 18K  Core Processor PIC  Core Size 8-Bit  Speed 48MHz  Connectivity I2C, SPI, UART/USART, USB  Peripherals Brown-out Detect/Reset, POR, PWM, WDT
Package 28-VQFN Exposed Pad  Series PIC? XLP? 18K  Core Processor PIC  Core Size 8-Bit  Speed 48MHz  Connectivity I2C, SPI, UART/USART, USB  Peripherals Brown-out Detect/Reset, POR, PWM, WDT
Series PIC? XLP? 18K  Core Processor PIC  Core Size 8-Bit  Speed 48MHz  Connectivity I2C, SPI, UART/USART, USB  Peripherals Brown-out Detect/Reset, POR, PWM, WDT
Core Processor  Core Size  8-Bit  Speed  48MHz  Connectivity  I2C, SPI, UART/USART, USB  Peripherals  Brown-out Detect/Reset, POR, PWM, WDT
Core Size 8-Bit  Speed 48MHz  Connectivity I2C, SPI, UART/USART, USB  Peripherals Brown-out Detect/Reset, POR, PWM, WDT
Speed 48MHz Connectivity I2C, SPI, UART/USART, USB Peripherals Brown-out Detect/Reset, POR, PWM, WDT
Connectivity I2C, SPI, UART/USART, USB Peripherals Brown-out Detect/Reset, POR, PWM, WDT
Peripherals Brown-out Detect/Reset, POR, PWM, WDT
Number of I/O 25
Program Memory Size 32KB (16K x 16)
Program Memory Type FLASH
EEPROM Size 256 x 8
RAM Size 2K x 8
Voltage - Supply (Vcc/Vdd) 2.3 V ~ 5.5 V
Data Converters A/D 14x10b
Oscillator Type Internal
Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C} \text{ (TA)}$
Mounting Type -
Package / Case 28-VQFN Exposed Pad
Supplier Device Package 28-QFN (6x6)
Report errors

### PIC18F25K50-E/ML Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## PIC18F25K50-E/ML Payment Methods



















## PIC18F25K50-E/ML Shipping Methods













If you have any question about PIC18F25K50-E/ML, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com