

PIC18F26K22-I/SS

Quote

PIC18F26K22-I/SS Information

Part Number	PIC18F26K22-I/SS	
Manufacturer	Microchip Technology	Tel North
Category	Integrated Circuits (ICs) Embedded - Microcontrollers	
Description	IC MCU 8BIT 64KB FLASH 28SSOP	- SEX 3
Package	28-SSOP (0.209", 5.30mm Width)	
	For the pricing/inventory/lead time, please contact us	
	Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a
	Manufacturer Category Description	Embedded - MicrocontrollersDescriptionIC MCU 8BIT 64KB FLASH 28SSOPPackage28-SSOP (0.209", 5.30mm Width)For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



PIC18F26K22-I/SS Specifications

Manufacturer Microchip Technology Integrated Circuits (ICs) Embedded - Microcontrollers Package 28-SSOP (0.209", 5.30mm Width) Series PIC? XLP? 18K Core Processor PIC Core Size 8-Bit Speed 64MHz Connectivity I2C, SPI, UART/USART Peripherals Brown-out Detect/Reset, HLVD, POR, PWM, WDT Number of I/O 24 Program Memory Size 64KB (32K x 16) Program Memory Type FLASH EEPROM Size 1K x 8 RAM Size 38K x 8 Voltage - Supply (Vcc/Vdd) 2.3 V ~ 5.5 V Data Converters A/D 19x10b Operating Temperature -40°C ~ 85°C (TA) Operating Temperature 2.8SOP (0.209", 5.30mm Width) Supplier Device Package 28-SSOP (0.209", 5.30mm Width)			
Integrated Circuits (ICs) Embedded - Microcontrollers Package 28-SSOP (0.209", 5.30mm Width) Series PIC? XLP? 18K Core Processor PIC Core Size 8-Bit Speed 64MHz Connectivity I2C, SPI, UART/USART Peripherals Brown-out Detect/Reset, HLVD, POR, PWM, WDT Number of I/O 24 Program Memory Size 64KB (32K x 16) Program Memory Type FLASH EEPROM Size 1K x 8 RAM Size 3.8K x 8 Voltage - Supply (Vcc/Vdd) 2.3 V ~ 5.5 V Data Converters A/D 19x10b Operating Temperature -40°C ~ 85°C (TA) Mounting Type - Package / Case 28-SSOP (0.209", 5.30mm Width)	Manufacturer Part Number	PIC18F26K22-I/SS	
Embedded - Microcontrollers Package 28-SSOP (0.209", 5.30mm Width) Series PIC? XLP? 18K Core Processor PIC Core Size 8-Bit Speed 64MHz Connectivity I2C, SPI, UART/USART Peripherals Brown-out Detect/Reset, HLVD, POR, PWM, WDT Number of I/O 24 Program Memory Size 64KB (32K x 16) Program Memory Type FLASH EEPROM Size 3.8K x 8 Voltage - Supply (Vcc/Vdd) 2.3 V ~ 5.5 V Data Converters A/D 19x10b Operating Temperature 40°C ~ 85°C (TA) Mounting Type - Package / Case 28-SSOP	Manufacturer	Microchip Technology	
Package 28-SSOP (0.209", 5.30mm Width) Series PIC XLP? 18K Core Processor PIC Core Size 8-Bit Speed 64MHz Connectivity I2C, SPI, UART/USART Peripherals Brown-out Detect/Reset, HLVD, POR, PWM, WDT Program Memory Size 64KB (32K x 16) Program Memory Type FLASH EEPROM Size 1K x 8 RAM Size 3.8K x 8 Voltage - Supply (Vcc/Vdd) 2.3 V ~ 5.5 V Data Converters A/D 19x10b Operating Temperature -40°C ~ 85°C (TA) Mounting Type - Package / Case 28-SSOP (0.209", 5.30mm Width)	Category	Integrated Circuits (ICs)	
SeriesPIC? XLP? 18KCore ProcessorPICCore Size8-BitSpeed64MHzConnectivity12C, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, HLVD, POR, PWM, WDTNumber of I/O24Program Memory Size64KB (32K x 16)Program Memory TypeFLASHEEPROM Size3.8K x 8Voltage - Supply (Vcc/Vdd)2.3 V ~ 5.5 VData ConvertersAD 19x10bOperating Temperature4.0°C ~ 85°C (TA)Package / Case28-SSOP (0.209°, 5.30mm Width)Supplier Device Package88-SSOP		Embedded - Microcontrollers	
Core ProcessorPICCore Size8-BitSpeed64MHzConnectivityI2C, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, HLVD, POR, PWM, WDTNumber of I/O24Program Memory Size64KB (32K x 16)Program Memory TypeFLASHEEPROM Size3.8K x 8Nutage - Supply (Vcc/Vdd)2.3 V ~ 5.5 VData ConvertersA/D 19x10bOperating Temperature-40°C ~ 85°C (TA)Program Gype-Package / Case88SOP (0.209", 5.30mm Width)	Package	28-SSOP (0.209", 5.30mm Width)	
Core Size8-BitSpeed64MHzConnectivityI2C, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, HLVD, POR, PWM, WDTNumber of I/O24Program Memory Size64KB (32K x 16)Program Memory TypeFLASHEEPROM Size1K x 8RAM Size3.8K x 8Voltage - Supply (Vcc/Vdd)2.3 V ~ 5.5 VData ConvertersInternalOperating Temperature-40°C ~ 85°C (TA)Program Grape-8SSOP (0.209", 5.30mm Width)Supplier Device Package8-SSOP	Series	PIC? XLP? 18K	
Speed64MHzConnectivityI2C, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, HLVD, POR, PWM, WDTNumber of I/O24Program Memory Size64KB (32K x 16)Program Memory TypeFLASHEEPROM Size1K x 8RAM Size3.8K x 8Voltage - Supply (Vcc/Vdd)2.3 V ~ 5.5 VData ConvertersA/D 19x10bOscillator Type-40°C ~ 85°C (TA)Mounting Type-Package / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOP	Core Processor	PIC	
IConnectivityI2C, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, HLVD, POR, PWM, WDTNumber of I/O24Program Memory Size64KB (32K x 16)Program Memory TypeFLASHEEPROM Size1K x 8RAM Size3.8K x 8Voltage - Supply (Vcc/Vdd)2.3 V ~ 5.5 VData ConvertersA/D 19x10bOperating Temperature-40°C ~ 85°C (TA)Operating Temperature28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOP	Core Size	8-Bit	
PeripheralsBrown-out Detect/Reset, HLVD, POR, PWM, WDTNumber of I/O24Program Memory Size64KB (32K x 16)Program Memory TypeFLASHEEPROM Size1K x 8RAM Size3.8K x 8Voltage - Supply (Vcc/Vdd)2.3 V ~ 5.5 VData ConvertersA/D 19x10bOperating Temperature-40°C ~ 85°C (TA)Mounting Type-Package / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOP	Speed	64MHz	
Number of I/O 24 Program Memory Size 64KB (32K x 16) Program Memory Type FLASH EEPROM Size 1K x 8 RAM Size 3.8K x 8 Voltage - Supply (Vcc/Vdd) 2.3 V ~ 5.5 V Data Converters A/D 19x10b Oscillator Type Internal Operating Temperature -40°C ~ 85°C (TA) Mounting Type - Package / Case 28-SSOP (0.209", 5.30mm Width)	Connectivity	I2C, SPI, UART/USART	
Program Memory Size64KB (32K x 16)Program Memory TypeFLASHEEPROM Size1K x 8RAM Size3.8K x 8Voltage - Supply (Vcc/Vdd)2.3 V ~ 5.5 VData ConvertersA/D 19x10bOscillator TypeInternalOperating Temperature-40°C ~ 85°C (TA)Mounting Type-Package / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOP	Peripherals	Brown-out Detect/Reset, HLVD, POR, PWM, WDT	
Program Memory TypeFLASHEEPROM Size1K x 8RAM Size3.8K x 8Voltage - Supply (Vcc/Vdd)2.3 V ~ 5.5 VData ConvertersA/D 19x10bOscillator TypeInternalOperating Temperature-40°C ~ 85°C (TA)Mounting Type-Package / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOP	Number of I/O	24	
EEPROM SizeIK x 8RAM Size3.8K x 8Voltage - Supply (Vcc/Vdd)2.3 V ~ 5.5 VData ConvertersA/D 19x10bOscillator TypeInternalOperating Temperature-40°C ~ 85°C (TA)Mounting Type-Package / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOP	Program Memory Size	64KB (32K x 16)	
RAM Size3.8K x 8Voltage - Supply (Vcc/Vdd)2.3 V ~ 5.5 VData ConvertersA/D 19x10bOscillator TypeInternalOperating Temperature-40°C ~ 85°C (TA)Mounting Type-Package / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOP	Program Memory Type	FLASH	
Voltage - Supply (Vcc/Vdd)2.3 V ~ 5.5 VData ConvertersA/D 19x10bOscillator TypeInternalOperating Temperature-40°C ~ 85°C (TA)Mounting Type-Package / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOP	EEPROM Size	1K x 8	
Data ConvertersA/D 19x10bOscillator TypeInternalOperating Temperature-40°C ~ 85°C (TA)Mounting Type-Package / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOP	RAM Size	3.8K x 8	
Oscillator TypeInternalOperating Temperature-40°C ~ 85°C (TA)Mounting Type-Package / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOP	Voltage - Supply (Vcc/Vdd)	2.3 V ~ 5.5 V	
Operating Temperature-40°C ~ 85°C (TA)Mounting Type-Package / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOP	Data Converters	A/D 19x10b	
Mounting Type-Package / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOP	Oscillator Type	Internal	
Package / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOP	Operating Temperature	-40°C ~ 85°C (TA)	
Supplier Device Package 28-SSOP	Mounting Type	-	
	Package / Case	28-SSOP (0.209", 5.30mm Width)	
Report errors?	Supplier Device Package	28-SSOP	
			Report errors?

PIC18F26K22-I/SS Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

PIC18F26K22-I/SS Payment Methods



PIC18F26K22-I/SS Shipping Methods



If you have any question about PIC18F26K22-I/SS, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com