



PIC18F4480-E/ML Information



For Reference Only

Part Number PIC18F4480-E/ML

Manufacturer Microchip Technology

Category Integrated Circuits (ICs)
Embedded - Microcontrollers

Description IC MCU 8BIT 16KB FLASH 44QFN

Package 44-VQFN Exposed Pad

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PIC18F4480-E/ML Specifications

Manufacturer Part Number Microchip Technology Category Integrated Circuits (ICs) Embedded - Microcontrollers Package 44-VQFN Exposed Pad Series PIC? 18F Core Processor PIC Core Size 8-Bit Speed 25MHz Connectivity CAN, I2C, SPI, UART/USART Peripherals Brown-out Detect/Reset, HLVD, POR, PWM, WDT Number of I/O Program Memory Size PiC18F4480-E/ML Microchip Technology Integrated Circuits (ICs) Embedded - Microcontrollers PERD	
Category Integrated Circuits (ICs) Embedded - Microcontrollers Package 44-VQFN Exposed Pad Series PIC? 18F Core Processor PIC Core Size 8-Bit Speed 25MHz Connectivity CAN, I2C, SPI, UART/USART Peripherals Brown-out Detect/Reset, HLVD, POR, PWM, WDT Number of I/O 36	
Embedded - Microcontrollers Package 44-VQFN Exposed Pad Series PIC? 18F Core Processor PIC Core Size 8-Bit Speed 25MHz Connectivity CAN, I2C, SPI, UART/USART Peripherals Brown-out Detect/Reset, HLVD, POR, PWM, WDT Number of I/O 36	
Package 44-VQFN Exposed Pad Series PIC? 18F Core Processor PIC Core Size 8-Bit Speed 25MHz Connectivity CAN, I2C, SPI, UART/USART Peripherals Brown-out Detect/Reset, HLVD, POR, PWM, WDT Number of I/O 36	
Series PIC? 18F Core Processor PIC Core Size 8-Bit Speed 25MHz Connectivity CAN, I2C, SPI, UART/USART Peripherals Brown-out Detect/Reset, HLVD, POR, PWM, WDT Number of I/O 36	
Core Processor PIC Speed Speed 25MHz Connectivity CAN, I2C, SPI, UART/USART Peripherals Brown-out Detect/Reset, HLVD, POR, PWM, WDT Number of I/O 36	
Core Size 8-Bit Speed 25MHz Connectivity CAN, I2C, SPI, UART/USART Peripherals Brown-out Detect/Reset, HLVD, POR, PWM, WDT Number of I/O 36	
Speed 25MHz Connectivity CAN, I2C, SPI, UART/USART Peripherals Brown-out Detect/Reset, HLVD, POR, PWM, WDT Number of I/O 36	
Connectivity CAN, I2C, SPI, UART/USART Peripherals Brown-out Detect/Reset, HLVD, POR, PWM, WDT Number of I/O 36	
Peripherals Brown-out Detect/Reset, HLVD, POR, PWM, WDT Number of I/O 36	
Number of I/O 36	
Program Memory Size 16KB (8K x 16)	
Program Memory Type FLASH	
EEPROM Size 256 x 8	
RAM Size 768 x 8	
Voltage - Supply (Vcc/Vdd) $4.2 \text{ V} \sim 5.5 \text{ V}$	
Data Converters A/D 11x10b	
Oscillator Type Internal	
Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C} \text{ (TA)}$	
Mounting Type -	
Package / Case 44-VQFN Exposed Pad	
Supplier Device Package 44-QFN (8x8)	
Report	

PIC18F4480-E/ML Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PIC18F4480-E/ML Payment Methods



















PIC18F4480-E/ML Shipping Methods













If you have any question about PIC18F4480-E/ML, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com