

# PIC18F45K80-H/ML

#### PIC18F45K80-H/ML Information

www.banwitchtem Filler Dununt	 PIC18F45K80-H/ML Microchip Technology Integrated Circuits (ICs) Embedded - Microcontrollers IC MCU 8BIT 32KB FLASH 44QFN 44-VQFN Exposed Pad For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### PIC18F45K80-H/ML Specifications

Manufacturer Part NumberPIC18F45K80-H/MLManufacturerMicrochip TechnologyCategoryIntegrated Circuits (ICs)CategoryEmbedded - MicrocontrollersPackage44-VQFN Exposed PadSeriesPIC? XLP? 18KCore ProcessorPICCore Size8-BitSpeed64MHzConnectivityECAN, 12C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, LVD, POR, PWM, WDTNumber of I/O35Program Memory Size32KB (16K x 16)
CategoryIntegrated Circuits (ICs)Embedded - MicrocontrollersPackage44-VQFN Exposed PadSeriesPIC? XLP? 18KCore ProcessorPICCore Size8-BitSpeed64MHzConnectivityECAN, 12C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, LVD, POR, PWM, WDTNumber of I/O35
FindEmbedded - MicrocontrollersPackage44-VQFN Exposed PadSeriesPIC? XLP? 18KCore ProcessorPICCore Size8-BitSpeed64MHzConnectivityECAN, 12C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, LVD, POR, PWM, WDTNumber of I/O35
Package44-VQFN Exposed PadSeriesPIC? XLP? 18KCore ProcessorPICCore Size8-BitSpeed64MHzConnectivityECAN, 12C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, LVD, POR, PWM, WDTNumber of I/O35
SeriesPIC? XLP? 18KCore ProcessorPICCore Size8-BitSpeed64MHzConnectivityECAN, 12C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, LVD, POR, PWM, WDTNumber of I/O35
Core ProcessorPICCore Size8-BitSpeed64MHzConnectivityECAN, 12C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, LVD, POR, PWM, WDTNumber of I/O35
Core Size8-BitSpeed64MHzConnectivityECAN, I2C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, LVD, POR, PWM, WDTNumber of I/O35
Speed64MHzConnectivityECAN, I2C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, LVD, POR, PWM, WDTNumber of I/O35
ConnectivityECAN, I2C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, LVD, POR, PWM, WDTNumber of I/O35
PeripheralsBrown-out Detect/Reset, LVD, POR, PWM, WDTNumber of I/O35
Number of I/O 35
Program Memory Size 32KB (16K x 16)
Program Memory Type FLASH
EEPROM Size 1K x 8
RAM Size 3.6K x 8
Voltage - Supply (Vcc/Vdd)4 V ~ 5.5 V
Data ConvertersA/D 11x12b
Oscillator Type Internal
Operating Temperature $-40^{\circ}\text{C} \sim 150^{\circ}\text{C}$ (TA)
Mounting Type -
Package / Case 44-VQFN Exposed Pad
Supplier Device Package44-QFN (8x8)
Report error

#### PIC18F45K80-H/ML Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### PIC18F45K80-H/ML Payment Methods





If you have any question about PIC18F45K80-H/ML, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com