

## PIC18LF24K40-E/SO

#### PIC18LF24K40-E/SO Information



For Reference Only

Part Number PIC18LF24K40-E/SO

Manufacturer Microchip Technology

Category Integrated Circuits (ICs)
Embedded - Microcontrollers

DescriptionIC MCU 8BIT 16KB FLASH 28SOICPackage28-SOIC (0.295", 7.50mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# PIC18LF24K40-E/SO Specifications

Manufacturer Part Number  Manufacturer  Microchip Technology  Integrated Circuits (ICs)  Embedded - Microcontrollers  Package  Package  28-SOIC (0.295", 7.50mm Width)  Series  PIC? XLP? 18K  Core Processor  PIC  Core Size  8-Bit  Speed  64MHz  Connectivity  I2C, LIN, SPI, UART/USART  Peripherals  Brown-out Detect/Reset, LVD, POR, PWM, WDT  Number of I/O  Program Memory Size  16KB (8K x 16)  Program Memory Type  FLASH  EEPROM Size  RAM Size  Voltage - Supply (Vcc/Vdd)  Integrated Circuits (ICs)  Microchip Technology  Integrated Circuits (ICs)  Embedded - Microcontrollers  28-SOIC (0.295", 7.50mm Width)  PIC? XLP? 18K  EBROM Size  IS SHE  Microchip Technology  Integrated Circuits (ICs)  Embedded - Microcontrollers  PIC (0.295", 7.50mm Width)  PIC? XLP? 18K  EBROM Size  IS SHE  I
Category         Integrated Circuits (ICs)           Embedded - Microcontrollers           Package         28-SOIC (0.295", 7.50mm Width)           Series         PIC? XLP? 18K           Core Processor         PIC           Core Size         8-Bit           Speed         64MHz           Connectivity         I2C, LIN, SPI, UART/USART           Peripherals         Brown-out Detect/Reset, LVD, POR, PWM, WDT           Number of I/O         25           Program Memory Size         16KB (8K x 16)           Program Memory Type         FLASH           EEPROM Size         256 x 8           RAM Size         1K x 8
Embedded - Microcontrollers  Package 28-SOIC (0.295", 7.50mm Width)  Series PIC? XLP? 18K  Core Processor PIC  Core Size 8-Bit  Speed 64MHz  Connectivity I2C, LIN, SPI, UART/USART  Peripherals Brown-out Detect/Reset, LVD, POR, PWM, WDT  Number of I/O 25  Program Memory Size 16KB (8K x 16)  Program Memory Type FLASH  EEPROM Size 256 x 8  RAM Size 1K x 8
Package         28-SOIC (0.295", 7.50mm Width)           Series         PIC? XLP? 18K           Core Processor         PIC           Core Size         8-Bit           Speed         64MHz           Connectivity         I2C, LIN, SPI, UART/USART           Peripherals         Brown-out Detect/Reset, LVD, POR, PWM, WDT           Number of I/O         25           Program Memory Size         16KB (8K x 16)           Program Memory Type         FLASH           EEPROM Size         256 x 8           RAM Size         1K x 8
Series         PIC? XLP? 18K           Core Processor         PIC           Core Size         8-Bit           Speed         64MHz           Connectivity         I2C, LIN, SPI, UART/USART           Peripherals         Brown-out Detect/Reset, LVD, POR, PWM, WDT           Number of I/O         25           Program Memory Size         16KB (8K x 16)           Program Memory Type         FLASH           EEPROM Size         256 x 8           RAM Size         1K x 8
Core Processor  Core Size  8-Bit  Speed  64MHz  Connectivity  I2C, LIN, SPI, UART/USART  Peripherals  Brown-out Detect/Reset, LVD, POR, PWM, WDT  Number of I/O  25  Program Memory Size  16KB (8K x 16)  Program Memory Type  FLASH  EEPROM Size  256 x 8  RAM Size  1K x 8
Core Size 8-Bit  Speed 64MHz  Connectivity I2C, LIN, SPI, UART/USART  Peripherals Brown-out Detect/Reset, LVD, POR, PWM, WDT  Number of I/O 25  Program Memory Size 16KB (8K x 16)  Program Memory Type FLASH  EEPROM Size 256 x 8  RAM Size 1K x 8
Speed 64MHz Connectivity I2C, LIN, SPI, UART/USART Peripherals Brown-out Detect/Reset, LVD, POR, PWM, WDT Number of I/O 25 Program Memory Size 16KB (8K x 16) Program Memory Type FLASH EEPROM Size 256 x 8 RAM Size 1K x 8
Connectivity  I2C, LIN, SPI, UART/USART  Peripherals  Brown-out Detect/Reset, LVD, POR, PWM, WDT  Number of I/O  25  Program Memory Size  16KB (8K x 16)  Program Memory Type  FLASH  EEPROM Size  256 x 8  RAM Size  1K x 8
Peripherals  Brown-out Detect/Reset, LVD, POR, PWM, WDT  Number of I/O  25  Program Memory Size  16KB (8K x 16)  Program Memory Type  FLASH  EEPROM Size  256 x 8  RAM Size  1K x 8
Number of I/O  Program Memory Size  16KB (8K x 16)  Program Memory Type  FLASH  EEPROM Size  256 x 8  RAM Size  1K x 8
Program Memory Size 16KB (8K x 16)  Program Memory Type FLASH  EEPROM Size 256 x 8  RAM Size 1K x 8
Program Memory Type FLASH  EEPROM Size 256 x 8  RAM Size 1K x 8
EEPROM Size 256 x 8  RAM Size 1K x 8
RAM Size 1K x 8
Voltage - Supply (Vcc/Vdd) 1.8 V ~ 3.6 V
Data Converters A/D 24x10b, D/A 1x5b
Oscillator Type Internal
Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C} \text{ (TA)}$
Mounting Type -
Package / Case 28-SOIC (0.295", 7.50mm Width)
Supplier Device Package 28-SOIC
Report error

#### PIC18LF24K40-E/SO Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### PIC18LF24K40-E/SO Payment Methods





















## PIC18LF24K40-E/SO Shipping Methods













If you have any question about PIC18LF24K40-E/SO, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com