

PIC18LF26K40-E/SS

PIC18LF26K40-E/SS Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



PIC18LF26K40-E/SS Specifications

Manufacturer Part NumberPIC18LF26K40-E/SSManufacturerMicrochip TechnologyCategoryIntegrated Circuits (ICs)Embedded - MicrocontrollersPackage28-SSOP (0.209", 5.30mm Width)Package28-SSOP (0.209", 5.30mm Width)SeriesPIC? XLP? 18KCore ProcessorPICCore Size8-BitSpeed64MHzConnectivityI2C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, LVD, POR, PWM, WDTNumber of I/O25Program Memory Size64KB (32K x 16)Program Memory TypeFLASHEEPROM SizeIK x 8
CategoryIntegrated Circuits (ICs)Embedded - MicrocontrollersPackage28-SSOP (0.209", 5.30mm Width)Package28-SSOP (0.209", 5.30mm Width)SeriesPIC? XLP? 18KCore ProcessorPICCore Size8-BitSpeed64MHzConnectivityI2C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, LVD, POR, PWM, WDTVumber of I/O25Program Memory Size64KB (32K x 16)Program Memory TypeFLASH
PackageEmbedded - MicrocontrollersPackage28-SSOP (0.209", 5.30mm Width)PackagePIC? XLP? 18KCore ProcessorPICCore Size8-BitSpeed64MHzConnectivity12C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, LVD, POR, PWM, WDTNumber of I/O25Program Memory Size64KB (32K x 16)Program Memory TypeFLASH
Package28-SSOP (0.209", 5.30mm Width)SeriesPIC? XLP? 18KCore ProcessorPICCore Size8-BitSpeed64MHzConnectivityI2C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, LVD, POR, PWM, WDTVumber of I/O25Program Memory Size64KB (32K x 16)Program Memory TypeFLASH
SeriesPIC? XLP? 18KCore ProcessorPICCore Size8-BitSpeed64MHzConnectivityI2C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, LVD, POR, PWM, WDTProgram Memory Size64KB (32K x 16)Program Memory TypeFLASH
Core ProcessorPICCore Size8-BitSpeed64MHzConnectivityI2C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, LVD, POR, PWM, WDTProgram Memory Size64KB (32K x 16)Program Memory TypeFLASH
Core Size8-BitSpeed64MHzConnectivityI2C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, LVD, POR, PWM, WDTNumber of I/O25Program Memory Size64KB (32K x 16)Program Memory TypeFLASH
Speed64MHzConnectivityI2C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, LVD, POR, PWM, WDTNumber of I/O25Program Memory Size64KB (32K x 16)Program Memory TypeFLASH
ConnectivityI2C, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, LVD, POR, PWM, WDTNumber of I/O25Program Memory Size64KB (32K x 16)Program Memory TypeFLASH
PeripheralsBrown-out Detect/Reset, LVD, POR, PWM, WDTNumber of I/O25Program Memory Size64KB (32K x 16)Program Memory TypeFLASH
Number of I/O25Program Memory Size64KB (32K x 16)Program Memory TypeFLASH
Program Memory Size64KB (32K x 16)Program Memory TypeFLASH
Program Memory Type FLASH
EPROM Size 1K x 8
RAM Size 3.6K x 8
Voltage - Supply (Vcc/Vdd) $1.8 \text{ V} \sim 3.6 \text{ V}$
Data ConvertersA/D 24x10b, D/A 1x5b
Dscillator Type Internal
Departing Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ (TA)
Mounting Type -
Package / Case 28-SSOP (0.209", 5.30mm Width)
Supplier Device Package 28-SSOP
Report errors?

PIC18LF26K40-E/SS Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

PIC18LF26K40-E/SS Payment Methods





If you have any question about PIC18LF26K40-E/SS, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com