

## **PJ-009A Information**



For Reference Only

Part Number PJ-009A Manufacturer CUI Inc.

Category Connectors, Interconnects Barrel - Power Connectors

**Description** CONN PWR JACK 2X5.5MM SOLDER

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **PJ-009A Specifications**

Manufacturer Part NumberPJ-009AManufacturerCUI Inc.CategoryConnectors, InterconnectsBarrel - Power ConnectorsPackage-Series-Connector TypeJackGenderMaleIndustry Recognized Mating Diameter2.00mm ID (0.079"), 5.50mm OD (0.217")Actual Diameter0.078" (2.00mm ID), 0.260" (6.60mm OD)Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypePanel MountMounting Feature-TerminationSolder Eyelet(s)ShieldingUnshieldedFeatures-Insulation Color-Voltage - Rated24VDCCurrent RatingEepert errors?		
CategoryConnectors, InterconnectsBarrel - Power ConnectorsPackage-Series-Connector TypeJackGenderMaleIndustry Recognized Mating Diameter2.00mm ID (0.079"), 5.50mm OD (0.217")Actual Diameter0.078" (2.00mm ID), 0.260" (6.60mm OD)Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypePanel MountMounting Feature-TerminationSolder Eyelet(s)ShieldingUnshieldedFeatures-Insulation Color-Voltage - Rated24VDCCurrent Rating2.5A	Manufacturer Part Number	PJ-009A
Package - Connector Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 2.00mm ID (0.079"), 5.50mm OD (0.217") Actual Diameter 0.078" (2.00mm ID), 0.260" (6.60mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Panel Mount Mounting Feature - Cermination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color - Voltage - Rated Current Rating 2.5A	Manufacturer	CUI Inc.
Package - Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 2.00mm ID (0.079"), 5.50mm OD (0.217") Actual Diameter 0.078" (2.00mm ID), 0.260" (6.60mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Panel Mount Mounting Feature - Cremination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color - Voltage - Rated Current Rating 2.5A	Category	Connectors, Interconnects
Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 2.00mm ID (0.079"), 5.50mm OD (0.217") Actual Diameter 0.078" (2.00mm ID), 0.260" (6.60mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Panel Mount Mounting Feature - Cermination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color - Voltage - Rated 24VDC Current Rating 2.5A		Barrel - Power Connectors
Connector TypeJackGenderMaleIndustry Recognized Mating Diameter2.00mm ID (0.079"), 5.50mm OD (0.217")Actual Diameter0.078" (2.00mm ID), 0.260" (6.60mm OD)Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypePanel MountMounting Feature-TerminationSolder Eyelet(s)ShieldingUnshieldedFeatures-Insulation Color-Voltage - Rated24VDCCurrent Rating2.5A	Package	-
Gender Male Industry Recognized Mating Diameter 2.00mm ID (0.079"), 5.50mm OD (0.217") Actual Diameter 0.078" (2.00mm ID), 0.260" (6.60mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Panel Mount Mounting Feature - Termination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color - Voltage - Rated 24VDC Current Rating 2.5A	Series	-
Industry Recognized Mating Diameter  2.00mm ID (0.079"), 5.50mm OD (0.217")  Actual Diameter  0.078" (2.00mm ID), 0.260" (6.60mm OD)  Number of Positions/Contacts  2 Conductors, 3 Contacts  Internal Switch(s)  Single Switch, Normally Closed  Mounting Type  Panel Mount  Mounting Feature  - Termination  Solder Eyelet(s)  Shielding  Unshielded  Features  - Insulation Color  Voltage - Rated  24VDC  Current Rating  2.00mm ID (0.079"), 5.50mm OD (0.217")  0.078" (2.00mm ID), 0.260" (6.60mm OD)  Unshielded  Single Switch, Normally Closed  Unshielded  -  -  -  Voltage - Rated  24VDC	Connector Type	Jack
Actual Diameter 0.078" (2.00mm ID), 0.260" (6.60mm OD)  Number of Positions/Contacts 2 Conductors, 3 Contacts  Internal Switch(s) Single Switch, Normally Closed  Mounting Type Panel Mount  Mounting Feature -  Termination Solder Eyelet(s)  Shielding Unshielded  Features -  Insulation Color -  Voltage - Rated 24VDC  Current Rating 2.5A	Gender	Male
Number of Positions/Contacts  Internal Switch(s)  Single Switch, Normally Closed  Mounting Type  Panel Mount  Mounting Feature  - Termination  Solder Eyelet(s)  Shielding  Unshielded  Features  - Insulation Color  Voltage - Rated  Current Rating  2 Conductors, 3 Contacts  Single Switch, Normally Closed  Panel Mount  -  Unshielded  -  2 Conductors, 3 Contacts  Single Switch, Normally Closed  Panel Mount  -  2 Conductors, 3 Contacts  Single Switch, Normally Closed  Panel Mount  -  2 Conductors, 3 Contacts  Single Switch, Normally Closed  Panel Mount  -  2 Conductors, 3 Contacts  Single Switch, Normally Closed  Panel Mount  -  2 Conductors, 3 Contacts  Single Switch, Normally Closed  Panel Mount  -  2 Conductors, 3 Contacts  Single Switch, Normally Closed  Panel Mount  -  2 Conductors, 3 Contacts  Single Switch, Normally Closed  Panel Mount  -  2 Conductors, 3 Contacts  Single Switch, Normally Closed  Panel Mount  -  2 Conductors, 3 Contacts  Single Switch, Normally Closed  Panel Mount  -  2 Conductors, 3 Contacts  Single Switch, Normally Closed  Panel Mount  -  2 Conductors, 3 Contacts  Single Switch, Normally Closed  Panel Mount  -  2 Conductors, 3 Contacts  Single Switch, Normally Closed  -  2 Current Rating Single Switch, Normally Closed  Panel Mount  -  2 Conductors, 3 Contacts  Single Switch, Normally Closed  -  2 Current Rating Single Switch, Normally Closed  Panel Mount  -  2 Current Rating Single Switch, Normally Closed  Single Switch, Normally Closed  -  2 Current Rating Single Switch, Normally Closed  Single Switch, Normally Closed  -  2 Current Rating Single Switch, Normally Closed  Single Switch, Normally Closed  -  2 Current Rating Single Switch, Normally Closed  Single Switch, Normally Closed  -  2 Current Rating Single Switch, Normally Closed  -  2 Current Rating Single Switch Switch Single Switch Switch Switch Single Switch S	Industry Recognized Mating Diameter	2.00mm ID (0.079"), 5.50mm OD (0.217")
Internal Switch(s)  Single Switch, Normally Closed  Mounting Type  Panel Mount  Mounting Feature  - Termination  Solder Eyelet(s)  Unshielded  Features  - Insulation Color  Voltage - Rated  Current Rating  Single Switch, Normally Closed  Panel Mount  -  24VDC  2.5A	Actual Diameter	0.078" (2.00mm ID), 0.260" (6.60mm OD)
Mounting Type Panel Mount  Mounting Feature -  Termination Solder Eyelet(s)  Shielding Unshielded  Features -  Insulation Color -  Voltage - Rated 24VDC  Current Rating 2.5A	Number of Positions/Contacts	2 Conductors, 3 Contacts
Mounting Feature  Termination Solder Eyelet(s) Unshielded  Features - Insulation Color Voltage - Rated Current Rating  -  Current Rating -  Color  -  24VDC  2.5A	Internal Switch(s)	Single Switch, Normally Closed
Termination Solder Eyelet(s)  Shielding Unshielded  Features - Insulation Color - Voltage - Rated 24VDC  Current Rating 2.5A	Mounting Type	Panel Mount
Shielding Unshielded  Features - Insulation Color - Voltage - Rated 24VDC Current Rating 2.5A	Mounting Feature	-
Features - Insulation Color - Voltage - Rated 24VDC Current Rating 2.5A	Termination	Solder Eyelet(s)
Insulation Color  Voltage - Rated  Current Rating  - 24VDC  2.5A	Shielding	Unshielded
Voltage - Rated 24VDC Current Rating 2.5A	Features	-
Current Rating 2.5A	Insulation Color	-
	Voltage - Rated	24VDC
Report errors?	Current Rating	2.5A
		Report errors?

#### **PJ-009A Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **PJ-009A Payment Methods**





















## **PJ-009A Shipping Methods**













If you have any question about PJ-009A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com