

PJ-038AH Information



Part Number PJ-038AH **Manufacturer** CUI Inc.

Category Connectors, Interconnects Barrel - Power Connectors

Description CONN PWR JACK 2X6.5MM SOLDER

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PJ-038AH Specifications

Manufacturer Part NumberPJ-038AHManufacturerCUI Inc.CategoryConnectors, InterconnectsBarrel - Power ConnectorsPackage-Series-Connector TypeJackGenderMaleIndustry Recognized Mating Diameter2.00mm ID (0.079"), 6.50mm OD (0.256")Actual Diameter0.078" (2.00mm ID), 0.244" (6.20mm OD)Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypePanel MountMounting FeatureFlangeTerminationSolder Eyelet(s)ShieldingUnshieldedFeatures-Insulation Color-Voltage - Rated24VDCCurrent Rating5A		
CategoryConnectors, InterconnectsBarrel - Power ConnectorsPackage-Series-Connector TypeJackGenderMaleIndustry Recognized Mating Diameter2.00mm ID (0.079"), 6.50mm OD (0.256")Actual Diameter0.078" (2.00mm ID), 0.244" (6.20mm OD)Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypePanel MountMounting FeatureFlangeTerminationSolder Eyelet(s)ShieldingUnshieldedFeatures-Insulation Color-Voltage - Rated24VDCCurrent Rating5A	Manufacturer Part Number	PJ-038AH
Package - Connector Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 2.00mm ID (0.079"), 6.50mm OD (0.256") Actual Diameter 0.078" (2.00mm ID), 0.244" (6.20mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Panel Mount Mounting Feature Flange Termination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color - Voltage - Rated Current Rating 5A	Manufacturer	CUI Inc.
Package-Series-Connector TypeJackGenderMaleIndustry Recognized Mating Diameter2.00mm ID (0.079"), 6.50mm OD (0.256")Actual Diameter0.078" (2.00mm ID), 0.244" (6.20mm OD)Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypePanel MountMounting FeatureFlangeTerminationSolder Eyelet(s)ShieldingUnshieldedFeatures-Insulation Color-Voltage - Rated24VDCCurrent Rating5A	Category	Connectors, Interconnects
Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 2.00mm ID (0.079"), 6.50mm OD (0.256") Actual Diameter 0.078" (2.00mm ID), 0.244" (6.20mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Panel Mount Mounting Feature Flange Termination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color - Voltage - Rated 24VDC Current Rating 5A		Barrel - Power Connectors
Connector Type Gender Male Industry Recognized Mating Diameter 2.00mm ID (0.079"), 6.50mm OD (0.256") Actual Diameter 0.078" (2.00mm ID), 0.244" (6.20mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Panel Mount Mounting Feature Flange Termination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color Voltage - Rated Current Rating Jack Male 2.00mm ID (0.079"), 6.50mm OD (0.256") 8.00mm ID (0.079"), 6.50mm OD (0.256") 9.00mm ID (0.0	Package	-
Gender Male Industry Recognized Mating Diameter 2.00mm ID (0.079"), 6.50mm OD (0.256") Actual Diameter 0.078" (2.00mm ID), 0.244" (6.20mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Panel Mount Mounting Feature Flange Termination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color - Voltage - Rated 24VDC Current Rating 5A	Series	-
Industry Recognized Mating Diameter 2.00mm ID (0.079"), 6.50mm OD (0.256") Actual Diameter 0.078" (2.00mm ID), 0.244" (6.20mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Panel Mount Mounting Feature Flange Termination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color Voltage - Rated 24VDC Current Rating 5 A	Connector Type	Jack
Actual Diameter 0.078" (2.00mm ID), 0.244" (6.20mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Panel Mount Mounting Feature Flange Termination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color - Voltage - Rated 24VDC Current Rating 5A	Gender	Male
Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypePanel MountMounting FeatureFlangeTerminationSolder Eyelet(s)ShieldingUnshieldedFeatures-Insulation Color-Voltage - Rated24VDCCurrent Rating5A	Industry Recognized Mating Diameter	2.00mm ID (0.079"), 6.50mm OD (0.256")
Internal Switch(s)Single Switch, Normally ClosedMounting TypePanel MountMounting FeatureFlangeTerminationSolder Eyelet(s)ShieldingUnshieldedFeatures-Insulation Color-Voltage - Rated24VDCCurrent Rating5A	Actual Diameter	0.078" (2.00mm ID), 0.244" (6.20mm OD)
Mounting TypePanel MountMounting FeatureFlangeTerminationSolder Eyelet(s)ShieldingUnshieldedFeatures-Insulation Color-Voltage - Rated24VDCCurrent Rating5A	Number of Positions/Contacts	2 Conductors, 3 Contacts
Mounting Feature Flange Termination Solder Eyelet(s) Unshielded Features - Insulation Color Voltage - Rated Current Rating Flange Flange 4 4 5 5 5 5 5 5 5 5 5 5 5	Internal Switch(s)	Single Switch, Normally Closed
Termination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color - Voltage - Rated 24VDC Current Rating 5A	Mounting Type	Panel Mount
Shielding Unshielded Features - Insulation Color - Voltage - Rated 24VDC Current Rating 5A	Mounting Feature	Flange
Features - Insulation Color - Voltage - Rated 24VDC Current Rating 5A	Termination	Solder Eyelet(s)
Insulation Color Voltage - Rated Current Rating	Shielding	Unshielded
Voltage - Rated 24VDC Current Rating 5A	Features	-
Current Rating 5A	Insulation Color	-
	Voltage - Rated	24VDC
Report errors?	Current Rating	5A
		Report errors

PJ-038AH Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PJ-038AH Payment Methods



















PJ-038AH Shipping Methods













If you have any question about PJ-038AH, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com