

### **PJ-055C Information**



Part Number PJ-055C Manufacturer CUI Inc.

Category Connectors, Interconnects Barrel - Power Connectors

**Description** CONN PWR JACK 1X3.4MM SOLDER

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **PJ-055C Specifications**

Manufacturer Part Number       PJ-055C         Manufacturer       CUI Inc.         Category       Connectors, Interconnects         Barrel - Power Connectors         Package       -         Series       -         Connector Type       Jack         Gender       Male         Industry Recognized Mating Diameter       1.00mm ID (0.039"), 3.40mm OD (0.134")         Actual Diameter       0.039" (1.00mm ID), 0.150" (3.80mm OD)         Number of Positions/Contacts       2 Conductors, 3 Contacts         Internal Switch(s)       Single Switch, Normally Closed         Mounting Type       Through Hole         Mounting Feature       -         Termination       Solder Eyelet(s)         Shielding       Unshielded         Features       -         Insulation Color       -         Voltage - Rated       24VDC         Current Rating       2A			
CategoryConnectors, InterconnectsBarrel - Power ConnectorsPackage-Series-Connector TypeJackGenderMaleIndustry Recognized Mating Diameter1.00mm ID (0.039"), 3.40mm OD (0.134")Actual Diameter0.039" (1.00mm ID), 0.150" (3.80mm OD)Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypeThrough HoleMounting Feature-TerminationSolder Eyelet(s)ShieldingUnshieldedFeatures-Insulation Color-Voltage - Rated24VDCCurrent Rating2A	Manufacturer Part Number	PJ-055C	
Package - Connector Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 1.00mm ID (0.039"), 3.40mm OD (0.134") Actual Diameter 0.039" (1.00mm ID), 0.150" (3.80mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Through Hole Mounting Feature - Contacts Colder Eyelet(s) Shielding Unshielded Features - Insulation Color - Voltage - Rated Current Rating 2A	Manufacturer	CUI Inc.	
Package - Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 1.00mm ID (0.039"), 3.40mm OD (0.134") Actual Diameter 0.039" (1.00mm ID), 0.150" (3.80mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Through Hole Mounting Feature - Cermination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color - Voltage - Rated Current Rating 2A	Category	Connectors, Interconnects	
Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 1.00mm ID (0.039"), 3.40mm OD (0.134") Actual Diameter 0.039" (1.00mm ID), 0.150" (3.80mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Through Hole Mounting Feature - Cermination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color - Voltage - Rated 24VDC Current Rating 2 2A		Barrel - Power Connectors	
Connector Type Gender Male Industry Recognized Mating Diameter 1.00mm ID (0.039"), 3.40mm OD (0.134") Actual Diameter 0.039" (1.00mm ID), 0.150" (3.80mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Through Hole Mounting Feature - Termination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color - Voltage - Rated Current Rating  Jack Male  1.00mm ID (0.039"), 3.40mm OD (0.134")  8.40mm OD  8.50mm OD  9.11mm ID  9.12mm ID  9.1	Package	-	
GenderMaleIndustry Recognized Mating Diameter1.00mm ID (0.039"), 3.40mm OD (0.134")Actual Diameter0.039" (1.00mm ID), 0.150" (3.80mm OD)Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypeThrough HoleMounting Feature-TerminationSolder Eyelet(s)ShieldingUnshieldedFeatures-Insulation Color-Voltage - Rated24VDCCurrent Rating2A	Series	-	
Industry Recognized Mating Diameter  1.00mm ID (0.039"), 3.40mm OD (0.134")  Actual Diameter  0.039" (1.00mm ID), 0.150" (3.80mm OD)  Number of Positions/Contacts  2 Conductors, 3 Contacts  Internal Switch(s)  Single Switch, Normally Closed  Mounting Type  Through Hole  Mounting Feature  - Termination  Solder Eyelet(s)  Shielding  Unshielded  Features  - Insulation Color  Voltage - Rated  24VDC  Current Rating  2.000mm ID (0.039"), 3.40mm OD (0.134")  0.039" (1.00mm ID), 0.150" (3.80mm OD)  0.150" (3.	Connector Type	Jack	
Actual Diameter 0.039" (1.00mm ID), 0.150" (3.80mm OD)  Number of Positions/Contacts 2 Conductors, 3 Contacts  Internal Switch(s) Single Switch, Normally Closed  Mounting Type Through Hole  Mounting Feature -  Termination Solder Eyelet(s)  Shielding Unshielded  Features -  Insulation Color -  Voltage - Rated 24VDC  Current Rating 2A	Gender	Male	
Number of Positions/Contacts  Internal Switch(s)  Single Switch, Normally Closed  Mounting Type  Through Hole  Mounting Feature  Termination  Solder Eyelet(s)  Shielding  Unshielded  Features  Insulation Color  Voltage - Rated  Current Rating  2 Conductors, 3 Contacts  Single Switch, Normally Closed  Through Hole	Industry Recognized Mating Diameter	1.00mm ID (0.039"), 3.40mm OD (0.134")	
Internal Switch(s)  Mounting Type  Through Hole  Mounting Feature  Termination  Solder Eyelet(s)  Unshielded  Features  -  Insulation Color  Voltage - Rated  Current Rating  Single Switch, Normally Closed  Through Hole  Unshielded  -  Unshielded  24VDC  24VDC	Actual Diameter	0.039" (1.00mm ID), 0.150" (3.80mm OD)	
Mounting Type  Mounting Feature  Termination  Solder Eyelet(s)  Shielding  Unshielded  Features  Insulation Color  Voltage - Rated  Current Rating  Through Hole  Unshielded	Number of Positions/Contacts	2 Conductors, 3 Contacts	
Mounting Feature  Termination Solder Eyelet(s)  Unshielded  Features - Insulation Color Voltage - Rated Current Rating  -  Current Rating	Internal Switch(s)	Single Switch, Normally Closed	
Termination Solder Eyelet(s)  Shielding Unshielded  Features - Insulation Color - Voltage - Rated 24VDC  Current Rating 2A	Mounting Type	Through Hole	
Shielding Unshielded  Features - Insulation Color - Voltage - Rated 24VDC Current Rating 2A	Mounting Feature	-	
Features - Insulation Color - Voltage - Rated 24VDC Current Rating 2A	Termination	Solder Eyelet(s)	
Insulation Color  Voltage - Rated  Current Rating	Shielding	Unshielded	
Voltage - Rated 24VDC Current Rating 2A	Features	-	
Current Rating 2A	Insulation Color	-	
	Voltage - Rated	24VDC	
Report errors?	Current Rating	2A	
		Report erro	ors?

### **PJ-055C Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **PJ-055C Payment Methods**



















# **PJ-055C Shipping Methods**













If you have any question about PJ-055C, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com