

PJ-055D Information

www.helsener.com

For Reference Only

Part Number PJ-055D Manufacturer CUI Inc.

Category Connectors, Interconnects Barrel - Power Connectors

Description CONN PWR JACK 1.3X3.4MM SOLDER

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PJ-055D Specifications

Manufacturer Part NumberPJ-055DManufacturerCUI Inc.CategoryConnectors, InterconnectsBarrel - Power ConnectorsPackage-Series-Connector TypeJackGenderMaleIndustry Recognized Mating Diameter1.30mm ID (0.051"), 3.40mm OD (0.134")Actual Diameter0.039" (1.00mm ID), 0.150" (3.80mm OD)Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypeThrough HoleMounting Feature-TerminationSolder Eyelet(s)ShieldingUnshieldedFeatures-Insulation Color-Voltage - Rated24VDCCurrent RatingEepert errors?			
CategoryConnectors, InterconnectsPackage-Series-Connector TypeJackGenderMaleIndustry Recognized Mating Diameter1.30mm ID (0.051"), 3.40mm OD (0.134")Actual Diameter0.039" (1.00mm ID), 0.150" (3.80mm OD)Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypeThrough HoleMounting Feature-TerminationSolder Eyelet(s)ShieldingUnshieldedFeatures-Insulation Color-Voltage - Rated24VDCCurrent Rating2A	Manufacturer Part Number	PJ-055D	
Barrel - Power Connectors Package	Manufacturer	CUI Inc.	
Package-Series-Connector TypeJackGenderMaleIndustry Recognized Mating Diameter1.30mm ID (0.051"), 3.40mm OD (0.134")Actual Diameter0.039" (1.00mm ID), 0.150" (3.80mm OD)Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypeThrough HoleMounting Feature-TerminationSolder Eyelet(s)ShieldingUnshieldedFeatures-Insulation Color-Voltage - Rated24VDCCurrent Rating2A	Category	Connectors, Interconnects	
Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 1.30mm ID (0.051"), 3.40mm OD (0.134") Actual Diameter 0.039" (1.00mm ID), 0.150" (3.80mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Through Hole Mounting Feature - Cremination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color - Voltage - Rated 24VDC Current Rating 2A		Barrel - Power Connectors	
Connector TypeJackGenderMaleIndustry Recognized Mating Diameter1.30mm ID (0.051"), 3.40mm OD (0.134")Actual Diameter0.039" (1.00mm ID), 0.150" (3.80mm OD)Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypeThrough HoleMounting Feature-TerminationSolder Eyelet(s)ShieldingUnshieldedFeatures-Insulation Color-Voltage - Rated24VDCCurrent Rating2A	Package	-	
Gender Male Industry Recognized Mating Diameter 1.30mm ID (0.051"), 3.40mm OD (0.134") Actual Diameter 0.039" (1.00mm ID), 0.150" (3.80mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Through Hole Mounting Feature - Termination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color - Voltage - Rated 24VDC Current Rating 2A	Series	-	
Industry Recognized Mating Diameter 1.30mm ID (0.051"), 3.40mm OD (0.134") Actual Diameter 0.039" (1.00mm ID), 0.150" (3.80mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Through Hole Mounting Feature - Termination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color Voltage - Rated 24VDC Current Rating 2.30mm ID (0.051"), 3.40mm OD (0.134") 0.039" (1.00mm ID), 0.150" (3.80mm OD) Number of Positions/Colom (9.80mm OD) 2 Conductors, 3 Contacts Single Switch, Normally Closed Unshielded - - - - - - - - - - - - -	Connector Type	Jack	
Actual Diameter 0.039" (1.00mm ID), 0.150" (3.80mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Through Hole Mounting Feature - Termination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color - Voltage - Rated 24VDC Current Rating 2A	Gender	Male	
Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypeThrough HoleMounting Feature-TerminationSolder Eyelet(s)ShieldingUnshieldedFeatures-Insulation Color-Voltage - Rated24VDCCurrent Rating2A	Industry Recognized Mating Diameter	1.30mm ID (0.051"), 3.40mm OD (0.134")	
Internal Switch(s) Single Switch, Normally Closed Mounting Type Through Hole - Termination Solder Eyelet(s) Shielding Unshielded Features Insulation Color Voltage - Rated Current Rating Single Switch, Normally Closed Through Hole - Unshielded - 24VDC 2A	Actual Diameter	0.039" (1.00mm ID), 0.150" (3.80mm OD)	
Mounting Type Mounting Feature Termination Solder Eyelet(s) Shielding Unshielded Features Insulation Color Voltage - Rated Current Rating Through Hole Unshielded 24VDC 2A	Number of Positions/Contacts	2 Conductors, 3 Contacts	
Mounting Feature Termination Solder Eyelet(s) Unshielded Features - Insulation Color Voltage - Rated Current Rating - Current Rating - Solder Eyelet(s) Unshielded 24VDC 24VDC 24VDC	Internal Switch(s)	Single Switch, Normally Closed	
Termination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color - Voltage - Rated 24VDC Current Rating 2A	Mounting Type	Through Hole	
Shielding Unshielded Features - Insulation Color - Voltage - Rated 24VDC Current Rating 2A	Mounting Feature	-	
Features - Insulation Color - Voltage - Rated 24VDC Current Rating 2A	Termination	Solder Eyelet(s)	
Insulation Color Voltage - Rated Current Rating	Shielding	Unshielded	
Voltage - Rated 24VDC Current Rating 2A	Features	-	
Current Rating 2A	Insulation Color	-	
	Voltage - Rated	24VDC	
Report errors?	Current Rating	2A	
		Report errors	s?

PJ-055D Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PJ-055D Payment Methods





















PJ-055D Shipping Methods













If you have any question about PJ-055D, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com