



### **PJ1-023-SMT-TR Information**

Part Number PJ1-023-SMT-TR

Manufacturer CUI Inc.

**Category** Connectors, Interconnects

**Barrel - Power Connectors** 

**Description** CONN PWR JACK 0.7X2.35MM SOLDER

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **PJ1-023-SMT-TR Specifications**

Manufacturer Part Number  Manufacturer  Cull Inc.  Category  Connectors, Interconnects  Barrel - Power Connectors  Package  - Series  - Connector Type  Jack  Gender  Male  Industry Recognized Mating Diameter  Actual Diameter  O.026" (0.65mm ID), 0.110" (2.80mm OD)  Number of Positions/Contacts  Internal Switch(s)  Single Switch, Normally Closed  Mounting Type  Surface Mount, Right Angle  Mounting Feature  Shielding  Features  Board Guide  Insulation Color  Voltage - Rated  Cull Inc.  Cull Inc.  Connector Shierconnects  Barrel - Power Connectors  Barrel - Power Connectors  - Connectors  Actual Diameter  0.026" (0.65mm ID), 0.110" (2.80mm OD)  Single Switch, Normally Closed  Single Switch, Normally Closed  Shielded  Features  Board Guide  Insulation Color  Voltage - Rated  24VDC  Current Rating  Report errors?		
CategoryConnectors, InterconnectsBarrel - Power ConnectorsPackage-Series-Connector TypeJackGenderMaleIndustry Recognized Mating Diameter0.70mm ID (0.028"), 2.35mm OD (0.093") EIAJ-1Actual Diameter0.026" (0.65mm ID), 0.110" (2.80mm OD)Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypeSurface Mount, Right AngleMounting Feature-TerminationSolderShieldingShieldedFeaturesBoard GuideInsulation Color-Voltage - Rated24VDCCurrent Rating2.5A	Manufacturer Part Number	PJ1-023-SMT-TR
Package - Connector Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 0.70mm ID (0.028"), 2.35mm OD (0.093") EIAJ-1 Actual Diameter 0.026" (0.65mm ID), 0.110" (2.80mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Surface Mount, Right Angle Mounting Feature - Fermination Solder Shielding Shielded Features Board Guide Insulation Color - Voltage - Rated Current Rating 2.5A	Manufacturer	CUI Inc.
Package - Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 0.70mm ID (0.028"), 2.35mm OD (0.093") EIAJ-1 Actual Diameter 0.026" (0.65mm ID), 0.110" (2.80mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Surface Mount, Right Angle Mounting Feature - Termination Solder Shielding Shielded Features Board Guide Insulation Color - Voltage - Rated 24VDC Current Rating 2.5A	Category	Connectors, Interconnects
Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 0.70mm ID (0.028"), 2.35mm OD (0.093") EIAJ-1 Actual Diameter 0.026" (0.65mm ID), 0.110" (2.80mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Surface Mount, Right Angle Mounting Feature - Fermination Solder Shielding Shielded Features Board Guide Insulation Color - Voltage - Rated 24VDC Current Rating 2.5A		Barrel - Power Connectors
Connector Type Gender Male Industry Recognized Mating Diameter 0.70mm ID (0.028"), 2.35mm OD (0.093") EIAJ-1 Actual Diameter 0.026" (0.65mm ID), 0.110" (2.80mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Surface Mount, Right Angle Mounting Feature - Termination Solder Shielding Shielded Features Board Guide Insulation Color Voltage - Rated Current Rating  Jack Male  0.26" (0.62mm ID), 0.110" (2.80mm OD)  Single Switch, Normally Closed Shieldes Single Switch, Normally Closed Shieldes Single Switch, Normally Closed Shieldes Surface Mount, Right Angle	Package	-
GenderMaleIndustry Recognized Mating Diameter0.70mm ID (0.028"), 2.35mm OD (0.093") EIAJ-1Actual Diameter0.026" (0.65mm ID), 0.110" (2.80mm OD)Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypeSurface Mount, Right AngleMounting Feature-TerminationSolderShieldingShieldedFeaturesBoard GuideInsulation Color-Voltage - Rated24VDCCurrent Rating2.5A	Series	-
Industry Recognized Mating Diameter 0.70mm ID (0.028"), 2.35mm OD (0.093") EIAJ-1 Actual Diameter 0.026" (0.65mm ID), 0.110" (2.80mm OD)  Number of Positions/Contacts 2 Conductors, 3 Contacts  Internal Switch(s) Single Switch, Normally Closed  Mounting Type Surface Mount, Right Angle  Mounting Feature -  Termination Solder  Shielding Shielded  Features Board Guide  Insulation Color -  Voltage - Rated 24VDC  Current Rating 2.5A	Connector Type	Jack
Actual Diameter 0.026" (0.65mm ID), 0.110" (2.80mm OD)  Number of Positions/Contacts 2 Conductors, 3 Contacts  Internal Switch(s) Single Switch, Normally Closed  Mounting Type Surface Mount, Right Angle  Mounting Feature -  Termination Solder  Shielding Shielded  Features Board Guide  Insulation Color -  Voltage - Rated 24VDC  Current Rating 2.5A	Gender	Male
Number of Positions/Contacts  Internal Switch(s)  Single Switch, Normally Closed  Mounting Type  Surface Mount, Right Angle  Mounting Feature  - Termination  Solder  Shielding  Shielded  Features  Board Guide  Insulation Color  Voltage - Rated  24VDC  Current Rating  2 Conductors, 3 Contacts  Single Switch, Normally Closed  Surface Mount, Right Angle  -  -  Voltage - Rated  2 Conductors, 3 Contacts  Single Switch, Normally Closed  Surface Mount, Right Angle  -  -  -  -  -  -  -  -  -  -  -  -  -	Industry Recognized Mating Diameter	0.70mm ID (0.028"), 2.35mm OD (0.093") EIAJ-1
Internal Switch(s)  Single Switch, Normally Closed  Mounting Type  Surface Mount, Right Angle  - Termination  Solder  Shielding  Shielded  Features  Board Guide  Insulation Color  Voltage - Rated  Current Rating  Single Switch, Normally Closed  Surface Mount, Right Angle  -  Surface Mount, Right Angle  -  Solder  -  Solder  Shielded  Shielded  24VDC  2.5A	Actual Diameter	0.026" (0.65mm ID), 0.110" (2.80mm OD)
Mounting Type Surface Mount, Right Angle  Mounting Feature - Termination Solder Shielding Shielded Features Board Guide Insulation Color Voltage - Rated Current Rating Surface Mount, Right Angle - 24VDC 2.5A	Number of Positions/Contacts	2 Conductors, 3 Contacts
Mounting Feature  Termination Solder Shielding Shielded Features Board Guide Insulation Color Voltage - Rated Current Rating  Solder	Internal Switch(s)	Single Switch, Normally Closed
Termination Solder Shielding Shielded Features Board Guide Insulation Color - Voltage - Rated 24VDC Current Rating 2.5A	Mounting Type	Surface Mount, Right Angle
Shielding Shielded Features Board Guide Insulation Color - Voltage - Rated 24VDC Current Rating 2.5A	Mounting Feature	-
Features Board Guide Insulation Color - Voltage - Rated 24VDC Current Rating 2.5A	Termination	Solder
Insulation Color  Voltage - Rated  Current Rating  24VDC  2.5A	Shielding	Shielded
Voltage - Rated 24VDC Current Rating 2.5A	Features	Board Guide
Current Rating 2.5A	Insulation Color	-
	Voltage - Rated	24VDC
Report errors?	Current Rating	2.5A
		Report errors?

#### PJ1-023-SMT-TR Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **PJ1-023-SMT-TR Payment Methods**





















### **PJ1-023-SMT-TR Shipping Methods**













If you have any question about PJ1-023-SMT-TR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com