

PLB4G420008

PLB4G420008 Information





Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



PLB4G420008 Specifications

ManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsCategoryCircular ConnectorsPackage-SeriesPLConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionP150 - Dust ProtectedShell Material, FinishGoldFeatures-Voltage - Rated-Voltage - Rated-Steatense <t< th=""><th></th><th></th></t<>		
CategoryConnectors, InterconnectsPackage-Package-SeriesPLConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionPolysulfone (PSU)Shell Material, FinishPolysulfone (PSU)Contact Finish-Yoltage - Rated-Voltage - Rated-Current Rating5A	Manufacturer Part Number	PLB4G420008
Circular ConnectorsPackage-SeriesPLConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIpolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Kurent Rating5A	Manufacturer	ITT Cannon, LLC
Package-SeriesPLConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIPS0 - Dust ProtectedShell Material, FinishOlysulfone (PSU)Contact FinishGoldYoltage - Rated-Kurent Rating5A	Category	Connectors, Interconnects
SeriesPLConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishGoldContact FinishGoldFeatures-Voltage - Rated-Statem- <tr< td=""><td></td><td>Circular Connectors</td></tr<>		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionPolysulfone (PSU)Shell Material, FinishGoldFeatures-Voltage - Rated-Current Rating5A	Package	-
Number of Positions8Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact Finish-Features-Voltage - Rated-Current Rating5A	Series	PL
Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current Rating5A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current Rating5A	Number of Positions	8
Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current RatingSA	Shell Size - Insert	-
TerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current Rating5A	Shell Size, MIL	-
Fastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current Rating5A	Mounting Type	Panel Mount, Bulkhead - Rear Side Nut
Orientation0°Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current Rating5A	Termination	Solder Cup
Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current Rating5A	Fastening Type	Latch Lock, Push-Pull
Shell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current Rating5A	Orientation	0°
Contact FinishGoldFeatures-Voltage - Rated-Current Rating5A	Ingress Protection	IP50 - Dust Protected
Features-Voltage - Rated-Current Rating5A	Shell Material, Finish	Polysulfone (PSU)
Voltage - Rated-Current Rating5A	Contact Finish	Gold
Current Rating 5A	Features	-
-	Voltage - Rated	-
Report errors?	Current Rating	5A
		Report errors?

PLB4G420008 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

PLB4G420008 Payment Methods



PLB4G420008 Shipping Methods



If you have any question about PLB4G420008, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com