

## PLB4G520008

#### PLB4G520008 Information



For Reference Only

Part Number	PLB4G520008	
Manufacturer	ITT Cannon, LLC	
Category	Connectors, Interconnects Circular Connectors	
Description	CONN RCPT FMALE 8POS GOLD SLDR	
Package	-	
	For the pricing/inventory/lead time, please contact us	
	Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## PLB4G520008 Specifications

ManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsCategoryCircular ConnectorsPackage-SeriesPLConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionP50 - Dust ProtectedShell Material, FinishGoldFeatures-Voltage - Rated-Voltage - Rated-Steatenee- <trtr>Steatenee</trtr>		
CategoryConnectors, InterconnectsPackage-Package-SeriesPLConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionPolysulfone (PSU)Shell Material, FinishPolysulfone (PSU)Contact Finish-Yoltage - Rated-Voltage - Rated-Current Rating5A	Manufacturer Part Number	PLB4G520008
Circular ConnectorsPackage-SeriesPLConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIpolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Kurent Rating5A	Manufacturer	ITT Cannon, LLC
Package-SeriesPLConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIPS0 - Dust ProtectedShell Material, FinishOlysulfone (PSU)Contact FinishGoldYoltage - Rated-Kurent Rating5A	Category	Connectors, Interconnects
SeriesPLConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishGoldContact FinishGoldFeatures-Voltage - Rated-Statem- <tr< td=""><td></td><td>Circular Connectors</td></tr<>		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionPolysulfone (PSU)Shell Material, FinishGoldFeatures-Voltage - Rated-Current Rating5A	Package	-
Number of Positions8Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishGoldFeatures-Voltage - Rated-Current Rating5A	Series	PL
Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current Rating5A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current Rating5A	Number of Positions	8
Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current RatingSA	Shell Size - Insert	-
TerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current Rating5A	Shell Size, MIL	-
Fastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current Rating5A	Mounting Type	Panel Mount, Bulkhead - Rear Side Nut
Orientation0°Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current Rating5A	Termination	Solder Cup
Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current Rating5A	Fastening Type	Latch Lock, Push-Pull
Shell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current Rating5A	Orientation	0°
Contact FinishGoldFeatures-Voltage - Rated-Current Rating5A	Ingress Protection	IP50 - Dust Protected
Features-Voltage - Rated-Current Rating5A	Shell Material, Finish	Polysulfone (PSU)
Voltage - Rated-Current Rating5A	Contact Finish	Gold
Current Rating 5A	Features	-
-	Voltage - Rated	-
Report errors?	Current Rating	5A
		Report errors?

#### PLB4G520008 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE GUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### PLB4G520008 Payment Methods



### PLB4G520008 Shipping Methods



If you have any question about PLB4G520008, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com