

PLB4G820002 Information



For Reference Only

Part Number PLB4G820002 Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

Description CONN RCPT FMALE 2POS GOLD SLDR

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PLB4G820002 Specifications

| Manufacturer Part Number PLB4G820002 Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series PL Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert - Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Rear Side Nut Termination Solder Cup Fastening Type Latch Lock, Push-Pull Orientation 0° Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features - Voltage - Rated - Current Rating 10A | | |
|---|--------------------------|---------------------------------------|
| CategoryConnectors, InterconnectsPackage-SeriesPLConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current Rating10A | Manufacturer Part Number | PLB4G820002 |
| Package-SeriesPLConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current Rating10A | Manufacturer | ITT Cannon, LLC |
| Package-SeriesPLConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current Rating10A | Category | Connectors, Interconnects |
| SeriesPLConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current Rating10A | | Circular Connectors |
| Connector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current Rating10A | Package | - |
| Number of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current Rating10A | Series | PL |
| Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Rear Side Nut Solder Cup Fastening Type Latch Lock, Push-Pull Orientation O° Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features - Voltage - Rated Current Rating 10A | Connector Type | Receptacle, Female Sockets |
| Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Rear Side Nut Termination Solder Cup Fastening Type Latch Lock, Push-Pull Orientation 0° Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features - Voltage - Rated - Current Rating 10A | Number of Positions | 2 |
| Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current Rating10A | Shell Size - Insert | - |
| Termination Solder Cup Fastening Type Latch Lock, Push-Pull Orientation 0° Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features - Voltage - Rated - Current Rating 10A | Shell Size, MIL | - |
| Fastening Type Crientation Orientation Ingress Protection Shell Material, Finish Contact Finish Contact Finish Features - Voltage - Rated Current Rating Latch Lock, Push-Pull O° Latch Lock, Push-Pull O° Latch Lock, Push-Pull O° Latch Lock, Push-Pull O° Contact Finish Polysulfone (PSU) Gold - Latch Lock, Push-Pull O° Contact Finish Polysulfone (PSU) Contact Finish Latch Lock, Push-Pull O° Latch Lock Lock Lock Lock Polysulfone (PSU) Latch Lock Lock Lock Lock Lock Lock Lock Lock | Mounting Type | Panel Mount, Bulkhead - Rear Side Nut |
| Orientation 0° Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features - Voltage - Rated - Current Rating 10A | Termination | Solder Cup |
| Ingress Protection Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features - Voltage - Rated - Current Rating IP50 - Dust Protected Polysulfone (PSU) Following Polysulfone (PSU) IDA | Fastening Type | Latch Lock, Push-Pull |
| Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features - Voltage - Rated - Current Rating 10A | Orientation | 0° |
| Contact Finish Gold Features - Voltage - Rated - Current Rating 10A | Ingress Protection | IP50 - Dust Protected |
| Features - Voltage - Rated - Current Rating 10A | Shell Material, Finish | Polysulfone (PSU) |
| Voltage - Rated - Current Rating 10A | Contact Finish | Gold |
| Current Rating 10A | Features | - |
| | Voltage - Rated | - |
| Report errors? | Current Rating | 10A |
| | | Report errors? |

PLB4G820002 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PLB4G820002 Payment Methods



















PLB4G820002 Shipping Methods













If you have any question about PLB4G820002, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com