

PLC-050S330D Information

Heisener.com

Part Number PLC-050S330D

Manufacturer Qualtek

Category Power Supplies - External/Internal (Off-Board)

LED Drivers

Description LED DRIVER CC AC/DC 5-15V 3.3A

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PLC-050S330D Specifications

Manufacturer Part Number PLC-0508330D Manufacturer Qualtek Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series PLC-050 D Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 5 ~ 15 V Current - Output (Max) 3.3A Power (Watts) 50W Voltage - Isolation 2kV (2000V) Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 84% Termination Style Wire Leads Size / Dimension 7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)		
Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series PLC-050 D Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Output (Max) 305VAC Voltage - Output (Max) 3.3A Power (Watts) 50W Voltage - Isolation 2kV (2000V) Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 84% Termination Style Wire Leads Size / Dimension 7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Manufacturer Part Number	PLC-050S330D
Package - Series PLC-050 D Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 5 ~ 15 V Current - Output (Max) 3.3A Power (Watts) 50W Voltage - Isolation 2kV (2000V) Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 84% Termination Style Wire Leads Size / Dimension 7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Manufacturer	Qualtek
Package - Series PLC-050 D Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 5 ~ 15 V Current - Output (Max) 3.3A Power (Watts) 50W Voltage - Isolation 2kV (2000V) Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 84% Termination Style Wire Leads Size / Dimension 7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series PLC-050 D Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 5 ~ 15 V Current - Output (Max) 3.3A Power (Watts) 50W Voltage - Isolation 2kV (2000V) Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 84% Termination Style Wire Leads Size / Dimension 7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)		LED Drivers
Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 5 ~ 15 V Current - Output (Max) 3.3A Power (Watts) 50W Voltage - Isolation 2kV (2000V) Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 84% Termination Style Wire Leads Size / Dimension 7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Package	-
Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Output (Max) 305VAC Voltage - Output (Max) 3.3A Power (Watts) 50W Voltage - Isolation 2kV (2000V) Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 84% Termination Style Wire Leads Size / Dimension 7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Series	PLC-050 D
Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 5 ~ 15 V Current - Output (Max) 3.3A Power (Watts) 50W Voltage - Isolation 2kV (2000V) Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 84% Termination Style Wire Leads Size / Dimension 7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Type	Constant Current
Voltage - Input (Min)90VACVoltage - Input (Max)305VACVoltage - Output5 ~ 15 VCurrent - Output (Max)3.3APower (Watts)50WVoltage - Isolation2kV (2000V)DimmingAnalogFeaturesOTP, OVP, SCPRatingsIP67Operating Temperature-35°C ~ 70°CEfficiency84%Termination StyleWire LeadsSize / Dimension7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Topology	AC DC Converter
Voltage - Input (Max) 305VAC Voltage - Output 5 ~ 15 V Current - Output (Max) 3.3A Power (Watts) 50W Voltage - Isolation 2kV (2000V) Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 84% Termination Style Wire Leads Size / Dimension 7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Number of Outputs	1
Voltage - Output $5 \sim 15 \text{ V}$ Current - Output (Max) 3.3A Power (Watts) 50W Voltage - Isolation 2kV (2000V)DimmingAnalogFeaturesOTP, OVP, SCPRatingsIP67Operating Temperature $-35^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Efficiency 84% Termination StyleWire LeadsSize / Dimension $7.83^{\circ}\text{L x } 1.67^{\circ}\text{W x } 1.34^{\circ}\text{H } (199.0\text{mm x } 42.5\text{mm x } 34.0\text{mm})$	Voltage - Input (Min)	90VAC
Current - Output (Max) Power (Watts) 50W Voltage - Isolation 2kV (2000V) Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 84% Termination Style Wire Leads Size / Dimension 3.3A 3.3A 50W Company Size / Dimension 3.3A 50W Size / Dimension 3.3A 50W Size / 2000	Voltage - Input (Max)	305VAC
Power (Watts) Voltage - Isolation 2kV (2000V) Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 84% Termination Style Wire Leads Size / Dimension 50W Composition 50W Analog Analog Analog OTP, OVP, SCP Wire Leads 7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Voltage - Output	5 ~ 15 V
Voltage - Isolation 2kV (2000V) Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 84% Termination Style Wire Leads Size / Dimension 7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Current - Output (Max)	3.3A
DimmingAnalogFeaturesOTP, OVP, SCPRatingsIP67Operating Temperature-35°C ~ 70°CEfficiency84%Termination StyleWire LeadsSize / Dimension7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Power (Watts)	50W
Features OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 84% Termination Style Wire Leads Size / Dimension 7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Voltage - Isolation	2kV (2000V)
RatingsIP67Operating Temperature -35° C ~ 70° CEfficiency 84% Termination StyleWire LeadsSize / Dimension 7.83° L x 1.67° W x 1.34° H (199.0mm x 42.5 mm x 34.0 mm)	Dimming	Analog
Operating Temperature -35°C ~ 70°C Efficiency 84% Termination Style Wire Leads Size / Dimension 7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Features	OTP, OVP, SCP
Efficiency 84% Termination Style Wire Leads Size / Dimension 7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Ratings	IP67
Termination Style Wire Leads Size / Dimension 7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Operating Temperature	-35°C ~ 70°C
Size / Dimension 7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Efficiency	84%
	Termination Style	Wire Leads
Report errors?	Size / Dimension	7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)
		Report errors

PLC-050S330D Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PLC-050S330D Payment Methods





















PLC-050S330D Shipping Methods













If you have any question about PLC-050S330D, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com