



PLC1G621002 Information

Wielsenernstm

Part Number PLC1G621002 Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

Description CONN RCPT FMALE 2POS GOLD SLDR

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PLC1G621002 Specifications

Manufacturer Part Number PLCIG621002 Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series PL Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Latch Lock, Push-Pull Orientation 0° Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features - Voltage - Rated - Current Rating 10A	<u> </u>	
Category Connectors, Interconnects Circular Connectors Package - Series PL Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Fastening Type Latch Lock, Push-Pull Orientation O° Ingress Protection Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features Voltage - Rated Current Rating I Connectors, Interconnects Circular Connectors Package - Connectors Interconnectors PL Connectors Interconnectors Interc	Manufacturer Part Number	PLC1G621002
PackageCircular ConnectorsSeriesPLConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current Rating10A	Manufacturer	ITT Cannon, LLC
Package-SeriesPLConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current Rating10A	Category	Connectors, Interconnects
Series PL Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Latch Lock, Push-Pull Orientation 0° Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features - Voltage - Rated - Current Rating 10A		Circular Connectors
Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Latch Lock, Push-Pull Orientation O° Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features - Voltage - Rated - Current Rating IRECEPTACLE STATES 10A	Package	-
Number of Positions Shell Size - Insert - Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Latch Lock, Push-Pull Orientation O° Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features - Voltage - Rated Current Rating 10A	Series	PL
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Latch Lock, Push-Pull Orientation 0° Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features - Voltage - Rated Current Rating 10A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Latch Lock, Push-Pull Orientation O° Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features - Voltage - Rated Current Rating IF60 - Dust Protected Free Hanging (In-Line) Solder Cup Latch Lock, Push-Pull O° Latch Lock, Push-Pull O° Lock, Push-Pull O° Lock Following Following IP50 - Dust Protected Following IP50 - Dust Pro	Number of Positions	2
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current Rating10A	Shell Size - Insert	-
Termination Solder Cup Fastening Type Latch Lock, Push-Pull Orientation 0° Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features - Voltage - Rated - Current Rating 10A	Shell Size, MIL	-
Fastening Type Orientation O° Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features - Voltage - Rated Current Rating Latch Lock, Push-Pull O° IP50 - Dust Protected Folysulfone (PSU) And IP50 - Dust Protected IP50 - Dust Protected IP50 - Dust Protected Folysulfone (PSU) And IP50 - Dust Protected IP50 - Dust Pro	Mounting Type	Free Hanging (In-Line)
Orientation 0° Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features - Voltage - Rated - Current Rating 10A	Termination	Solder Cup
Ingress Protection Shell Material, Finish Contact Finish Features Voltage - Rated Current Rating IP50 - Dust Protected Polysulfone (PSU) Gold - Under Contact Finish For a sum of the protected of the polysulfone (PSU) For a sum of the polysulfone (PSU) For a sum of the protected of the polysulfone (PSU) For a sum of the polysulfone (PSU)	Fastening Type	Latch Lock, Push-Pull
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Polysulfone (PSU) Gold - 10A	Orientation	0°
Contact Finish Gold Features - Voltage - Rated - Current Rating 10A	Ingress Protection	IP50 - Dust Protected
Features - Voltage - Rated - Current Rating 10A	Shell Material, Finish	Polysulfone (PSU)
Voltage - Rated - Current Rating 10A	Contact Finish	Gold
Current Rating 10A	Features	-
-	Voltage - Rated	-
Report errors?	Current Rating	10A
		Report errors?

PLC1G621002 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PLC1G621002 Payment Methods



















PLC1G621002 Shipping Methods













If you have any question about PLC1G621002, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com